SWITCHES

BBULGIN

Stainless Steel - Momentary



Contact Layout



Specification	MP0045/1D0NN000	MP0045/3D0NN000	
Terminations:	Solder tags	Solder Tags	
Switching:	D.P.C.O Momentary Action	D.P.C.O Momentary Action	
Max. Rating:	3A, 250V	3A, 250V	
Contact Resistance:	50mΩ max. @ 1A, 2V	50mΩ max. @ 1A, 2V	
Insulation Resistance:	>10 ³ MΩ @ 500Vdc	>10 ³ MΩ @ 500Vdc	
Dielectric Strength:	> 2.0kVac	> 2.0kVac	
Operating Temp. Range:	-20°C to +55°C	–20°C to +55°C	
Operations Mechanical: Electrical:	200,000 (min) 30,000 (min)	200,000 (min) 30,000 (min)	
Rear Nut Fixing Torque:	12Nm max.	12Nm max.	
Materials Mouldings: Tags/Terminations: Switch Body & Button:	Nylon Brass, Silver Plated Stainless Steel	Nylon Brass, Silver Plated Stainless Steel	
Contacts:	Silver	Silver	
Variants:	Nickel Plated Brass version available details on request	Nickel Plated Brass version available details on request	
RoHS	Compliant	Compliant	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by Bulgin manufacturer:

Other Similar products are found below :

 8940K2012
 LW1L-M1C10V-A
 LW1L-M1C70-A
 LW2L-A1C20M-GD
 LW2L-M1C20M-A
 60324L
 M22-D-R-GB0/K11
 M7E-HRN2

 67021K512
 67081K512X
 701PB580
 7199K101
 810K12910
 810KSV30B
 MML21EA2ADK
 MML21KA3ABK
 MML23KA3AC05K-001

 MML23KW3AA01W
 8418K2
 8442K3
 8450K1
 860K11911T01A
 861901
 861K11911T01A07
 861K13810T00A14
 861K13911

 8646AB6X718UL
 8646ABUL
 9001KXRK
 907AYY100
 PMHD155A1
 9533CD4+U574+U4922
 95-414.000
 99-450.837
 99-453.837

 PV3H2B0NN-341
 1203MRA
 A22NZBGANGA
 A22NZBNANGA
 A22NZMPATRA
 A2PMA1X03EC56
 A3A-5123-02
 A3A-7140
 A3A-7340

 7310
 A3A-7340
 A3U-TMW-A2C-5M
 A595
 12037A2ULCSA
 ABD122N-B
 1211390004