


REV.	DESCRIPTION	ECN NO.	NAME	DATE


1




SPECIFICATIONS
 Current Rating: 1.0 Amps
 Withstanding Voltage: AC 500V
 Insulation Resistance: 1000MΩ Min
 Contact Resistance: 20mΩ Max
 Operation Temperature: -40° to +105°
 Insulator Material: Polyester(UL94V-0)
 Contact Material: Brass
 Standard: PA6T
 Contact Plating: Gold Flash
 Max.Processing Temp: 240°C for 30-60seconds
 (260°C for 5seconds)

P/N	PIN	DIM.A	DIM.B
A127UP-ZD1P	1	0.00	1.27
A127UP-ZD2P	2	1.27	2.54
A127UP-ZD3P	3	2.54	3.81
A127UP-ZD4P	4	3.81	5.08
A127UP-ZD5P	5	5.08	6.35
A127UP-ZD6P	6	6.35	7.62
A127UP-ZD7P	7	7.62	8.89
A127UP-ZD8P	8	8.89	10.16
A127UP-ZD9P	9	10.16	11.43
.....
A127UP-ZD50P	50	(PIN-1)x1.27	(PIN)x1.27

3



4



RECOMMEND P.C.B LAYOUT
 PCB TOLERANCE: ±0.05 (TOP VIEW)

5

GENERAL TOLERANCE		DONGGUAN BAOXUN PRECISION TECHNOLOGY CO., LTD				
DIM.	TOL.	TITLE: 1.27PH H1.0 1xnPin 180度 W2.0 PC2.3 PA3.9 PB1.0 L7.2				
X		6T 0.4#				
X.X	±0.30	DWG. NO.: A127UP-ZDNP		DRAWN: MAX		
X.XX	±0.25	PART NO.: A127UP-ZDNP		CHECKED: ELLA		
X.XXX	±0.15	UNIT: mm		SCALE: none	SHEET: 1 of 1	
GENERAL ANGLE:	±3°	DWG. SIZE: A4	LAYER: bxconn	APPROVED: WILL		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [BXCONN](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [0010894062](#) [0010977306](#) [0015477636](#) [0015917161](#) [0022104068](#) [0022121042](#) [0022155065](#) [0022281023](#) [57102-F02-18ULF](#) [PCN6B-10P-2.5DS](#) [58102-G61-06LF](#) [582553-1](#) [0015911208](#) [01.001.5753.1](#) [0022285048](#) [0050291907](#) [02.125.8002.8](#)
[CSU011177004](#) [622-0430](#) [63453-116](#) [636-1030](#) [636-4007](#) [641938-9](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#) [67095-007LF](#)
[67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#)
[8-1437020-4](#) [819-22-004-30-001101](#)