

A	B	C
---	---	---



Technical drawing of a rectangular plate. The overall width is labeled $B \pm 0.3$ and the overall height is labeled 2.00 . The distance between the first and last holes is labeled $A \pm 0.1$. The plate contains a row of 10 square holes. A break symbol (two wavy lines) is shown in the center of the plate, indicating that the drawing is not to scale.

Withstanding Voltage:	AC 500V
Insulation Resistance:	1000MΩ Min
Contact Resistance:	20mΩ Max
Operation Temperature:	-40° to +105°
Insulator Material:	Polyester(UL94V-0)
Contact Material:	Brass
Standard:	PA6T
Contact Plating:	Gold Flash
Max.Processing Temp:	240°C for 30-60 seconds (260°C for 5 seconds)



5	
---	--

5

RECOMMEND P.C.B LAYOUT

PCB TOLERANCE: ± 0.05 (TOP VIEW)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [BXCONN](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [0010894062](#) [0010977306](#) [0015477636](#) [0015917161](#) [0022104068](#) [0022121042](#) [0022155065](#) [0022281023](#) [57102-F02-18ULF](#) [PCN6B-10P-2.5DS](#) [58102-G61-06LF](#) [582553-1](#) [0015911208](#) [01.001.5753.1](#) [0022285048](#) [0050291907](#) [02.125.8002.8](#)
[CSU011177004](#) [622-0430](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#)
[65817-010LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#)
[71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[803-43-024-10-001000](#)