

	A	B	C	D	E
REV.	DESCRIPTION			ECN NO.	NAME

SPECIFICATIONS
Current Rating:1.0 Amps
Withstanding Voltage:AC 500V
Insulation Resistance:1000MΩ Min
Contact Resistance:20mΩ Max
Operation Temperature:-40° to +105°
Insrlator Material:Polyester(UL94V-0)
Contact Material:Brass
Standard:PA6T
Contact Plating:Gold Flash
Max.Processing Temp: 240°C for30~60seconds
(260°C for5seconds)

P/N	PIN	DIM.A	DIM.B
A127UP-ZS1P	1	0.00	1.27
A127UP-ZS2P	2	1.27	2.54
A127UP-ZS3P	3	2.54	3.81
A127UP-ZS4P	4	3.81	5.08
A127UP-ZS5P	5	5.08	6.35
A127UP-ZS6P	6	6.35	7.62
A127UP-ZS7P	7	7.62	8.89
A127UP-ZS8P	8	8.89	10.16
A127UP-ZS9P	9	10.16	11.43
.....			
A127UP-ZS50P	50	(PIN-1)x1.27	(PIN)x1.27

RECOMMEND P.C.B LAYOUT
PCB TOLERANCE:±0.05 (TOP VIEW)

GENERAL TOLERANCE		DONGGUAN BAOXUN PRECISION TECHNOLOGY CO., LTD	
DIM. X X.X X.XX X.XXX	TOL. ±0.30 ±0.25 ±0.15	TITLE: 1.27PH H1.0 2xnPin 180度 W3.4 PC2.3 PA3.9 PB1.0 L7.2 6T	
GENERAL ANGLE: ±3°		DWG. NO.: A127UP-ZSNP DRAWN: MAX	
		PART NO.: A127UP-ZSNP CHECKED: ELLA	
UNIT:	mm	SCALE:	none
SHEET:	1of 1	DWG. SIZE:	A4
LAYER:	bxcnnc	APPROVED:	WILL

BXCONN®

	A	B	C	D	E
	REV.	DESCRIPTION	ECN NO.	NAME	DATE

$B \pm 0.3$
 $A \pm 0.1$
3.40

SPECIFICATIONS
Current Rating:1.0 Amps
Withstanding Voltage:AC 500V
Insulation Resistance:1000MΩ Min
Contact Resistance:20mΩ Max
Operation Temperature:-40° to +105°
Insrlator Material:Polyester(UL94V-0)
Contact Material:Brass
Standard:PA6T
Contact Plating:Gold Flash
Max.Processing Temp: 240°C for30–60seconds
(260°C for5seconds)

P/N	PIN	DIM.A	DIM.B
A127UP-ZS1P	1	0.00	1.27
A127UP-ZS2P	2	1.27	2.54
A127UP-ZS3P	3	2.54	3.81
A127UP-ZS4P	4	3.81	5.08
A127UP-ZS5P	5	5.08	6.35
A127UP-ZS6P	6	6.35	7.62
A127UP-ZS7P	7	7.62	8.89
A127UP-ZS8P	8	8.89	10.16
A127UP-ZS9P	9	10.16	11.43
.....			
A127UP-ZS50P	50	(PIN-1)x1.27	(PIN)x1.27

1.00
0.40 SQ
 1.27 ± 0.1

3.90 ± 0.2
 2.30 ± 0.2
 1.27 ± 0.1

1.27
1.27
ø0.65
A

RECOMMEND P.C.B LAYOUT
PCB TOLERANCE:±0.05 (TOP VIEW)

GENERAL TOLERANCE		DONGGUAN BAOXUN PRECISION TECHNOLOGY CO., LTD			
DIM. X X.X X.XX X.XXX GENERAL ANGLE:	TOL. ±0.30 ±0.25 ±0.15 ±3°	TITLE: 1.27PH H1.0 2xnPin 180度 W3.4 PC2.3 PA3.9 PB1.0 L7.2 6T			
		DWG. NO.: A127UP-ZSNP		DRAWN: MAX	
		PART NO.: A127UP-ZSNP		CHECKED: ELLA	
		UNIT: mm	SCALE: none	SHEET: 1 of 1	DWG. SIZE: A4 LAYER: bxconn APPROVED: WILL

A

B

C

D

E

REV.	DESCRIPTION	ECN NO.	NAME	DATE

1

2

3

4

5

$B \pm 0.3$
 $A \pm 0.1$
3.40

SPECIFICATIONS
Current Rating:1.0 Amps
Withstanding Voltage:AC 500V
Insulation Resistance:1000MΩ Min
Contact Resistance:20mΩ Max
Operation Temperature:-40° to +105°
Insrlator Material:Polyester(UL94V-0)
Contact Material:Brass
Standard:PA6T
Contact Plating:Gold Flash
Max.Processing Temp: 240°C for30–60seconds
(260°C for5seconds)

Ø0.65
1.27
A

RECOMMEND P.C.B LAYOUT
PCB TOLERANCE:±0.05 (TOP VIEW)

P/N	PIN	DIM.A	DIM.B
A127UP-ZS1P	1	0.00	1.27
A127UP-ZS2P	2	1.27	2.54
A127UP-ZS3P	3	2.54	3.81
A127UP-ZS4P	4	3.81	5.08
A127UP-ZS5P	5	5.08	6.35
A127UP-ZS6P	6	6.35	7.62
A127UP-ZS7P	7	7.62	8.89
A127UP-ZS8P	8	8.89	10.16
A127UP-ZS9P	9	10.16	11.43
.....			
A127UP-ZS50P	50	(PIN-1)x1.27	(PIN)x1.27

GENERAL TOLERANCE

DONGGUAN BAOXUN PRECISION TECHNOLOGY CO., LTD

TITLE: 1.27PH H1.0 2xnPin 180度 W3.4 PC2.3 PA3.9 PB1.0 L7.2 6T

DWG. NO.: A127UP-ZSNP

DRAWN: MAX

PART NO.: A127UP-ZSNP

CHECKED: ELLA

UNIT: mm

SCALE: none

SHEET: 1of 1

DWG. SIZE: A4

LAYER: bxconn

APPROVED: WILL

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [BXCONN](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [0010894062](#) [0010977306](#) [0015477636](#) [0015917161](#) [0022104068](#) [0022121042](#) [0022155065](#) [0022281023](#) [57102-F02-18ULF](#) [PCN6B-10P-2.5DS](#) [58102-G61-06LF](#) [582553-1](#) [0015911208](#) [01.001.5753.1](#) [0022285048](#) [0050291907](#) [02.125.8002.8](#)
[CSU011177004](#) [622-0430](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#)
[65817-010LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#)
[71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[803-43-024-10-001000](#)