

SPECIFICATIONS

- Current Rating: 0.75 Amps
- Withstanding Voltage: AC 500V
- Insulation Resistance: 1000MΩ Min
- Contact Resistance: 20mΩ Max
- Operation Temperature: -40°C to +105°C
- Insulator Material: Polyester (UL94V-0)
- Contact Material: Phosphor bronze
- Standard: PA6T
- Contact Plating: Gold Flash
- Max. Processing Temp: 240°C for 30-60 seconds (260°C for 5 seconds)

RECOMMEND P.C.B LAYOUT
PCB TOLERANCE: ±0.05 (TOP VIEW)

P/N	PIN	DIM.A	DIM.B
B100UP-ZD1P	1	0.00	1.00
B100UP-ZD2P	2	1.00	2.00
B100UP-ZD3P	3	2.00	3.00
B100UP-ZD4P	4	3.00	4.00
B100UP-ZD5P	5	4.00	5.00
B100UP-ZD6P	6	5.00	6.00
B100UP-ZD7P	7	6.00	7.00
B100UP-ZD8P	8	7.00	8.00
B100UP-ZD9P	9	8.00	9.00
.....			
B100UP-ZD40P	40	(PIN-1)	(PIN)

GENERAL TOLERANCE				DONGGUAN BAOXUN PRECISION TECHNOLOGY CO., LTD			
DIM. X X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 GENERAL ANGLE: ±3°				TITLE: 1.0FH H2.0 1xNPin 180度 W1.5 U型 PC2.0 6T			
				DWG. NO.: B100UP-ZDNP		DRAWN: MAX	
				PART NO.: B100UP-ZDNP		CHECKED: ELLA	
				UNIT: mm SCALE: none SHEET: 1 of 1 DWG. SIZE: A4 LAYER: bxconn APPROVED: WILL			

	A	B	C	D	E
				REV.	DESCRIPTION ECN NO. NAME DATE

SPECIFICATIONS

- Current Rating: 0.75 Amps
- Withstanding Voltage: AC 500V
- Insulation Resistance: 1000MΩ Min
- Contact Resistance: 20mΩ Max
- Operation Temperature: -40°C to +105°C
- Insulator Material: Polyester (UL94V-0)
- Contact Material: Phosphor bronze
- Standard: PA6T
- Contact Plating: Gold Flash
- Max. Processing Temp: 240°C for 30~60 seconds (260°C for 5 seconds)

P/N	PIN	DIM.A	DIM.B
B100UP-ZD1P	1	0.00	1.00
B100UP-ZD2P	2	1.00	2.00
B100UP-ZD3P	3	2.00	3.00
B100UP-ZD4P	4	3.00	4.00
B100UP-ZD5P	5	4.00	5.00
B100UP-ZD6P	6	5.00	6.00
B100UP-ZD7P	7	6.00	7.00
B100UP-ZD8P	8	7.00	8.00
B100UP-ZD9P	9	8.00	9.00
.....			
B100UP-ZD40P	40	(PIN-1)	(PIN)

GENERAL TOLERANCE		DONGGUAN BAOXUN PRECISION TECHNOLOGY CO., LTD			
DIM.	TOL.	TITLE: 1.0FH H2.0 1xnPin 180° W1.5 U型 PC2.0 6T			
X		DWG. NO.: B100UP-ZDNP		DRAWN: MAX	
X.X	±0.30	PART NO.: B100UP-ZDNP		CHECKED: ELLA	
X.XX	±0.25				
X.XXX	±0.15	UNIT: mm		SCALE: none	SHEET: 1of1
GENERAL ANGLE:	±3'	DWG. SIZE: A4		LAYER: bxconn	APPROVED: WILL

[illegible]

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) *category:*

Click to view products by [BXCONN](#) *manufacturer:*

Other Similar products are found below :

[892-18-020-10-001101](#) [0010894062](#) [0010977306](#) [0015477636](#) [0015917161](#) [0022104068](#) [0022121042](#) [0022155065](#) [0022281023](#) [57102-F02-18ULF](#) [PCN6B-10P-2.5DS](#) [58102-G61-06LF](#) [582553-1](#) [0015911208](#) [01.001.5753.1](#) [0022285048](#) [0050291907](#) [02.125.8002.8](#)
[CSU011177004](#) [622-0430](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#)
[65817-010LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#)
[71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[803-43-024-10-001000](#)