



Specifications:
 Current Rating: 1A
 Voltage Rating: 50V AC/DC
 Contact Resistance: 20 Milliohms Max
 Contact Resistance: 500MΩ/min
 Withstanding Voltage: 500V AC/min
 Operating Temperature Range: -25°C ~ +85°C

Material:
 Insulation: PA66 UL94-V0

Poles	Part No.	Dimension mm	
		A	B
2	2-1501H02P-0000	1.5	4.5
3	2-1501H03P-0000	3.0	6.0
4	2-1501H04P-0000	4.5	7.5
5	2-1501H05P-0000	6.0	9.0
6	2-1501H06P-0000	7.5	10.5
7	2-1501H07P-0000	9.0	12.0
8	2-1501H08P-0000	10.5	13.5
9	2-1501H09P-0000	12.0	15.0
10	2-1501H10P-0000	13.5	16.5
11	2-1501H11P-0000	15.0	18.0
12	2-1501H12P-0000	16.5	19.5
13	2-1501H13P-0000	18.0	21.0
14	2-1501H14P-0000	19.5	22.5
15	2-1501H15P-0000	21.0	24.0
16	2-1501H16P-0000	22.5	25.5

TOLERANCE TABLE	
.0	±0.20
.00	±0.10
.000	±0.05

APPROVED:	DATE:	深圳市灿科盟实业有限公司 CHANKLEMENT INDUSTRYCO., LTD
CHECKED:	DATE:	
DRAWN:	DATE:	TITLE:
LXF	2019-04-08	1501H-xP 白色 (Pitch:1.5mm)
CLIENT P/N /		
UNIT	mm	SCALE
FILE NO.	Ckmtw-1501-0017	Free
REV.	A	JLXI

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [0010894062](#) [0010977306](#) [0015477636](#) [0015917161](#) [0022104068](#) [0022121042](#) [0022155065](#) [0022281023](#) [57102-F02-18ULF](#) [PCN6B-10P-2.5DS](#) [58102-G61-06LF](#) [582553-1](#) [0015911208](#) [01.001.5753.1](#) [0022285048](#) [0050291907](#) [02.125.8002.8](#)
[CSU011177004](#) [622-0430](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#)
[65817-010LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#)
[71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[803-43-024-10-001000](#)