








Specifications:
Current Rating: 1A
Voltage Rating: 50V AC/DC
Contact Resistance: 20 Milliohms Max
Contact Resistance: 100MΩ/min
Withstanding Voltage: 500V AC/min
Operating Temperature Range: -25°C ~ +85°C

Poles	Part No.	Dimension mm	
		A	B
2	W-1001M02P-R000	1.0	4.5
3	W-1001M03P-R000	2.0	5.5
4	W-1001M04P-R000	3.0	6.5
5	W-1001M05P-R000	4.0	7.5
6	W-1001M06P-R000	5.0	8.5
7	W-1001M07P-R000	6.0	9.5
8	W-1001M08P-R000	7.0	10.5
9	W-1001M09P-R000	8.0	11.5
10	W-1001M10P-R000	9.0	12.5
11	W-1001M11P-R000	10.0	13.5
12	W-1001M12P-R000	11.0	14.5
13	W-1001M13P-R000	12.0	15.5
14	W-1001M14P-R000	13.0	16.5
15	W-1001M15P-R000	14.0	17.5

序号	零件名称	数量	材料	备注
①	底座	1	LCP	
②	端子	N	磷铜	磷底, 镀锡
③	焊片	2	黄铜	镍底, 镀锡

TOLERANCE TABLE

	±0.20
.0	±0.10
.00	±0.05

APPROVED:	DATE:	TITLE: SH1.0SMT-XP 卧贴 (Pitch:1.5mm) 深圳市灿科盟实业有限公司 Ckmtw CHANKLEMENT INDUSTRYCO., LTD			
CHECKED:	DATE:				
DRAWN:	DATE:				
LYF	2019-04-08	CLIENT P/N	/	UNIT	mm
		SCALE	free	REV.	A
		FILE NO.	Ckmtw-SH10-0022	REV.	1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) ***category:***

Click to view products by [Cankemeng](#) ***manufacturer:***

Other Similar products are found below :

[892-18-020-10-001101](#) [0010894062](#) [0010977306](#) [0015477636](#) [0015917161](#) [0022104068](#) [0022121042](#) [0022155065](#) [0022281023](#) [57102-F02-18ULF](#) [PCN6B-10P-2.5DS](#) [58102-G61-06LF](#) [582553-1](#) [0015911208](#) [01.001.5753.1](#) [0022285048](#) [0050291907](#) [02.125.8002.8](#)
[CSU011177004](#) [622-0430](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#)
[65817-010LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#)
[71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[803-43-024-10-001000](#)