

MOSFET BASED DC SOLID-STATE RELAY

- ▶ Latest MOSFET technology generation.
- ▶ Ultra low on-state resistance.
- ▶ Low output leakage current.
- ▶ Low control current consumption.
- ▶ Built-in overvoltage protection
- ▶ Reverse protected triggered control input to avoid linear control risks
- ▶ No radiated or conducted disturbances
- ▶ Touch protected housing IP20



SOM040100



Control voltage range	3.5-32VDC
Max. permanent output voltage	60VDC
Max. load current with heatsink	40ADC

Load voltage range	Load current range	Control input voltage range	In & case / Out Insulation	Connections	Dimensions (WxHxD)	Weight
5-60VDC	Up to 40A (with heatsink)	3.5-32VDC	2.5kV	Screw terminals	45 x 58.5 x 30	80g

Fig. 1


HIGH SIDE WIRING DIAGRAM
(Load connected to “-“)

Fig. 2



LOW SIDE WIRING DIAGRAM
(Load connected to “+“)

Fig. 3

INTERNAL DIAGRAM



Proud to serve you

Data given at Tambient=25°C and subject to modification without previous notice


CONTROL INPUT CHARACTERISTICS

INPUT CIRCUIT	CHARACTERISTIC	LABEL	VALUE	INFO.
	Nom. Control voltage	Ucnom	12-24VDC	
	Min. Control current	Icmin	35mA DC	-100µA/°C
	Control voltage range	Uc	3.5 - 32VDC	typical ON=3.3V
	Control current consumption	Ic	32 - 35mA DC (for control voltage range)	See fig. 5
	Releasing control voltage	Ucoffmax	1VDC	typical OFF= 2.6V
	Max. reverse control voltage	-Ucmax	32VDC	-Icmax<100µA
	Input impedance	Rin	Current limitation	See fig. 5

POWER OUTPUT CHARACTERISTICS

POWER CIRCUIT	CHARACTERISTIC	LABEL	VALUE	INFO.
	Nominal voltage	Uenom	48VDC	
	Voltage range	Ut Ue	5-60VDC	
	Non-repetitive peak voltage	Utp	100V	
	Overvoltage protection	D1	Transient voltage suppressor 56V (1500W/1ms)	
	Max reverse voltage drop (internal diode at OFF state)	-Ut	1.3V	@Ie=80A @Uc=0
	Maximum nominal currents	Ie max	Resistive Motor 40A Please contact us	See fig. 7 (limits)
	Non-repetitive peak overload current	Id max	320A	See fig. 8
	Min. load current	Iemin	5mA	
	Max. leakage current	Ielk max	3mA	@Utmax @Tjmax
	Max. on-state resistance	RDSon	30mOhms	@Iemax @Tjmax
	Typ. output capacitance	Cout	0.7nF	
	Junction/case thermal resistance per power element	Rthjc	0.9K/W	
	Built-in heatsink thermal resistance vertically mounted	Rthra	10K/W	@ΔTra=75°C
	Heatsink thermal time constant	Tthra	10 minutes	@ΔTra=75°C
	Control inputs/power outputs insulation voltage	Uiimp	2.5kV	
	Inputs/case insulation voltage	Uiimp	2.5kV	
	Outputs/case insulation voltage	Uiimp	2.5kV	
	Isolation resistance	Rio	1GΩ	
	Isolation capacitance	Cio	<8pF	
	Maximum junction temperature	Tjmax	175°C	
	Storage ambient temperature	Tstg	-40->+100°C	
	Operating ambient temperature	Tamb	-25->+90°C	See fig. 7
	Max. case temperature	Tc	100°C	


PROTECTION CHARACTERISTICS



TIME CHARACTERISTICS

Fig. 4

TIME DIAGRAMS



TIME CHARACT.	CHARACTERISTIC	LABEL	VALUE	INFO.
	Turn on time	t_{on}	20µs	
	Turn on delay	t_{don}	20µs	
	Turn off time	t_{off}	20µs	
	Turn off delay	t_{doff}	20µs	
	Max. On-Off frequency	$F_{(on-off)}$	>1000Hz (for high frequency, take 2 x I_e to calculate the heatsink; the protections must be chosen carefully)	Refer to the instruction sheet

GENERAL INFORMATION

CONNECT IONS	Connections	Power	Control	
	Screwdriver advised		POZIDRIV2	
	Min and max tightening torque	2 N.m	1.2 N.m	
	Insulated crimp terminals (round tabs, eyelet type)	M5	M4	

MISC.	Display	Green LED (indicates relay has switched ON)	
	Housing	UL94V0	
	Mounting	2 screws (M4x12mm ; tightening = 1.2N.m)	See mounting sheet
	Noise level	None	
	Weight	80g	

STANDARDS

GENERAL	Standards		IEC60947-1	
	Protection level		IP20	
	Protection against direct touch		Yes	
	CE marking		Yes	
	UL, cULUS		Yes	

E.M.C. IMMUNITY	TYPE OF TEST	STANDARD	LEVEL	EFFECT
	Fast transients bursts	EN61000-4-4	4kV criterion B	
	Electric shocks	EN61000-4-5	1kV criterion B	
	Voltage drop	EN61000-4-11	-	

CHARACTERISTIC CURVES

Fig. 5

INPUT CHARACTERISTIC




Fig. 6

ON RESISTANCE VS JUNCTION TEMPERATURE





Fig. 7

POWER DISSIPATED AND LOAD CURRENT LIMIT VS TEMPERATURE



10K/W = No Heatsink
 2.1K/W = WF210000
 0.75K/W = WF070000



4K/W = $150 \times 150 \times 3\text{mm}$ aluminium sheet
 1.2K/W = WF121000
 0.55K/W = WF050000

2.2K/W = WF262100
 1.1K/W = WF131100
 0.3K/W = WF031100

2.2K/W = WF151200
 0.9K/W = WF115100

Fig. 8

PEAK OVERLOAD CURRENT vs. PULSE DURATION CHARACTERISTIC



DIMENSIONS AND ACCESSORIES

Fig. 9

DIMENSIONS (mm)







Fig.
10

ACCESSORIES

FASTON : Please contact us



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Celduc manufacturer:

Other Similar products are found below :

[2YB20051](#) [2YB20111](#) [D31A3100](#) [D31A5100](#) [D31A7110](#) [D32A3100](#) [D32A5100](#) [D71A2100](#) [ESD05000](#) [PAA10060](#) [PHA01200](#) [PLA10160](#)
[PLA13750](#) [PSA60010](#) [PSL40010](#) [PTA10440](#) [PTA10490](#) [PTA50010](#) [PTFA0100](#) [PTFA3115](#) [PTI40020](#) [PTPA0230](#) [PW520000](#) [PWB01501](#)
[SA842070](#) [SA942460](#) [SAL961360](#) [SC842110](#) [SC869110](#) [SCF42324](#) [SCF62160](#) [SCM0100200](#) [SCM030200](#) [SF541310](#) [SF542310](#)
[SF546310](#) [SGT8658500](#) [SGT8658502](#) [SGT8670500](#) [SGT8678500](#) [SGT8850200](#) [SGT965360E](#) [SGT9854300](#) [SILD867170](#) [SIT867570](#)
[SKA10420](#) [SKA20421](#) [SKA20440](#) [SKA20441](#) [SKB10440](#)