CMPD7000

SURFACE MOUNT DUAL, IN SERIES SILICON SWITCHING DIODES



www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMPD7000 type is a ultra-high speed silicon switching diode manufactured by the epitaxial planar process, in an epoxy molded surface mount package, connected in a series configuration, designed for high speed switching applications.

MARKING CODE: C5C



SOT-23 CASE

MAXIMUM RATINGS: (T _A =25°C)	SYMBOL		UNITS
Peak Repetitive Reverse Voltage	V_{RRM}	100	V
Average Forward Current	IO	200	mA
Peak Forward Current	I _{FM}	500	mA
Power Dissipation	P_{D}	350	mW
Operating and Storage Junction Temperature	T _J , T _{stg}	-65 to +150	°C
Thermal Resistance	$\Theta_{\sf JA}$	357	°C/W

ELECTRICAL CHARACTERISTICS PER DIODE: (TA=25°C unless otherwise noted)


SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
I_{R}	V _R =50V			300	nA
I_{R}	V _R =50V, T _A =125°C			100	μΑ
I_{R}	V _R =100V			500	nA
BV_R	I _R =100μA	100			V
V_{F}	I _F =1.0mA	0.55		0.70	V
V_{F}	I _F =10mA	0.67		0.82	V
V_{F}	I _F =100mA	0.75		1.10	V
C_T	$V_R=0$, $f=1.0MHz$		1.5	2.6	pF
t _{rr}	$I_R=I_F=10$ mA, $R_L=100\Omega$, Rec. to 1.0mA		2.0	4.0	ns


CMPD7000

SURFACE MOUNT DUAL, IN SERIES SILICON SWITCHING DIODES




SOT-23 CASE - MECHANICAL OUTLINE





PIN CONFIGURATION



LEAD CODE:

- 1) Anode D2 2) Cathode D1
- 3) Anode D1, Cathode D2

MARKING CODE: C5C

DIMENSIONS							
	INCHES		MILLIMETERS				
SYMBOL	MIN	MAX	MIN	MAX			
Α	0.003	0.007	0.08	0.18			
В	0.006	-	0.15	-			
С	-	0.005	-	0.13			
D	0.035	0.043	0.89	1.09			
E	0.110	0.120	2.80	3.05			
F	0.075		1.90				
G	0.037		0.95				
Н	0.047	0.055	1.19	1.40			
	0.083	0.098	2.10	2.49			
J	0.014	0.020	0.35	0.50			

SOT-23 (REV: R3)

R7 (27-January 2010)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Diodes - General Purpose, Power, Switching category:

Click to view products by Central Semiconductor manufacturer:

Other Similar products are found below:

RD0306T-H BAV17-TR BAV19-TR 1N3611 NTE156A NTE525 NTE571 NTE574 NTE5804 NTE5806 NTE6244 1SS181-TP

1SS193,LF 1SS400CST2RA SDAA13 SHN2D02FUTW1T1G LS4151GS08 1N4449 1N456A 1N4934-E3/73 1N914B 1N914BTR

RFUH20TB3S BAS 28 E6327 BAV199-TP BAW56DWQ-7-F BAW75-TAP MM230L-CAA IDW40E65D1 JAN1N3600 LL4151-GS18

053684A SMMSD4148T3G 707803H NSVDAN222T1G SP000010217 CDSZC01100-HF BAV199E6433HTMA1 BAV70M3T5G

SMBT2001T1G NTE5801 NTE5800 NTE5808 NTE6240 NTE6248 DLM10C-AT1 BAS28-7 BAW56HDW-13 BAS28 TR VS-HFA04SD60STR-M3