


Core:TCS044125

Copper wire:2UEW-0.8




Part Number	Electrical Specifications @25°C			
	Core	Inductance (1KHZ/0.25) (uH Min)	Turns	Withstand Voltage 3S 5mA 60HZ Max(V)
10306400045	TCS044125	22	0.80mm*17.5TS	500

MECHANICAL




Horizontal Type



UL:Black heat shrink catheter

SCHEMATICS



Packaging material requirements

- 1.Cartn and bubble wrap
- 2.The foam thickness is 7mm thicker than the pin length
(Prevent component deformation)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Inductors](#) category:

Click to view products by [CND-tek](#) manufacturer:

Other Similar products are found below :

[CR32NP-100KC](#) [70F224AI](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#)
[PG0936.113NLT](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2-R47-R](#) [HC8-1R2-R](#) [HCF1305-3R3-R](#) [1206CS-151XG](#)
[RCH664NP-4R7M](#) [RCP1317NP-391L](#) [DH2280-4R7M](#) [DS1608C-106](#) [B10TJ](#) [B82498B3101J000](#) [ELJ-RE27NJF2](#) [1812CS-153XJ](#) [1812CS-](#)
[183XJ](#) [1812CS-223XJ](#) [1812LS-104XJ](#) [1812LS-105XJ](#) [1812LS-124XJ](#) [1812LS-154XJ](#) [1812LS-223XJ](#) [1812LS-224XJ](#) [1812LS-563XJ](#)
[1812LS-683XJ](#) [1812LS-824XJ](#) [BYP60K2](#) [NIN-PB330KTR300F](#) [NIN-PB3R3KTR750F](#) [NIN-PC3R3MTR340F](#) [NPI16W331MTRF](#)
[NPIM74C4R7MTRF](#) [LQBRHL2518T1R5M](#) [A04TJ](#) [SMD37-2](#) [SMD37-4](#) [SMD50-1](#) [SMD50-4](#) [1812CS-103XJ](#)