



1. Compatible with various 10/100 Base-TX transceiver requiring 1:1 transmit and receive turns ratio
2. Compliant with IEEE 802.3af standard including baseline wander compensation specification of $350\mu\text{H}$ OCL when Biased at 8mA
3. Low profile Surface Mount Packaging designed for Hi-Temp Reflow Process
4. Single channel interface for 10/100Mbps Ethernet applications with CMC's tuned to Enhance EMC system performance
5. Operating Temperature range: -40°C TO $+85^{\circ}\text{C}$
6. Storage temperature range: -40°C TO $+125^{\circ}\text{C}$



DIMENSIONS & SCHEMATICS




All 12 terminals must lie on a plane within .004mm of surface a after lead tinning


TECHNICAL SPECIFICATIONS

Inductance :	$350\mu\text{H}$ Min. @ 100 KHz, 100mV with 8mA DC Bias Lp(1-3) $350\mu\text{H}$ Min. @ 100 KHz, 100mV with 8mA DC Bias Lp(4-6)
Turns Ratio($\pm 2\%$):	1CT:1CT,(1-3):(12-10) 1CT:1CT,(4-6):(9-7)
DCR:	0.95Ω Max.(1-3,4-6)
Leakage Inductance:	$0.50\mu\text{H}$ Max.(1-3,4-6)
Interwinding Capacitance :	15pF(1-12,4-9)
Isolation HI-POT:	4500Vrms 1mA 60Second or 5000Vrms 1mA 3Second

PACKING SPECIFICATION



1. units/reel:300PCS
2. reel/carton:3PCS
3. units/carton :900PCS



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [CND-tek](#) manufacturer:

Other Similar products are found below :

[10306230004](#) [103062300040](#) [103062300055](#) [10306230033H](#) [10306230038H](#) [10306230041H](#) [10306230046DH](#) [10306230047](#)
[10306230049H](#) [10306230056](#) [10306230069](#) [10306230083H](#) [10306230154H](#) [10306230178](#) [10306230181](#) [10306230223DH](#) [10306230241D](#)
[10306230242DH](#) [10306230353](#) [103064000045](#) [10306400046](#) [10306400053H](#) [10306400058](#) [10CLD106415MH](#) [10CLD106520MH](#)
[20306230262](#) [303062300049](#) [30306230035D](#) [A102N3200200N](#) [AE71A2000010](#) [AE71A4100010](#) [AE71K4000010](#) [AE90A2104405](#)
[AE90A4004105](#) [AE90K1104000](#) [AE90K2104005](#) [AE90K4104105](#) [B1201D](#) [B1202D](#) [B1203D](#) [B16011S](#) [B1601S](#) [B1603S](#) [B1605S](#) [B1608S](#)
[B1617S](#) [B2009D](#) [B2018D](#) [B4001S](#) [B4004S](#)