

Technical specification:

Rated voltage: IEC 61076-2-101 4pol 5pol 240 V 60 V

Current rating: 4 A at 40℃

IEC 61076-2-101

Insulation resistance: >=100 MΩ

IEC 60512

3/2

Pollution degree: IEC 60664-1

Degree of protection: IEC 60529

IP 67, in mated condition

-30℃ ... +80℃

Temperature range:

IEC 60664-1

Mating cycles: IEC 60512-9a

>=100

Materials:

Contact: CuZn

Contact plating: Nickel, gold plated

Contact carrier: TPU GF, UL 94

Sealing: **FPM**

Coupling nut/

GD-Zn, nickel plated

screw:

Moulding body: TPU, UL 94, grey

Installation specification:

Recommended torque:

0,6 Nm


Conec Torque wrench:


installation tool: 36-000200

Insert across flats 13:

36-000220

Contact assignment:





Part no:	Description:
43-05130	SAL - 12 - TS4 - TK4
43-05131	SAL - 12 - TS5 - TK5

ALTER CAD DRAWING BY HAND 2002/95/EC RoHS compliant DO NOT

Index: a 28.03.11 VF Ä3767 Coupling nut/ screw modified, spanner flats added, data sheet modified

0

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSIO OWNERSHIP AND COPYRIGHT OF CONEC GmbH

0,0

0,00

tolerance of cable:

general tolerance:

± 0,50mm

± 0,25mm

± 0,10mm

dim. in mm

date name 06.10.09 drawn Fromm appd. 06.10.09 Mankopf

title:

Adapter, male connector M12x1 female connector M12x1

dwg no:

43K1A958

part no: see table

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by CONEC manufacturer:

Other Similar products are found below:

600X518037X 6STD15PCR99B70A 8R4000A16M020 8R5000A16M005 1200910002 1203580030 1200910008 1200910011 1300140094 130203-0054 1300140026 1300150099 RF-12S1N8A90DU 1-3637-600-5205 1612618 21036836414 8R4006A16M010 8R5006A18A120 1604232 1R3006A20M005 RF-12P1N8A80DU RF-12P1N8A90DU 41-40011 42-01015 4-22279-4 4-22281-1 4-22284-9 43-01088 43-01203 41-40013 42-00008 43-00343 43-01032 43-01162 43-10000 600X518050X SACC-DSI-FS-5P-PG9-L180 SC 8R5006A16M020 8R5006A16M005 8R4000A16M010 6-22279-3 1605332 N03FA03144 1300140077 43-01338 XS2RD4265 RSC 4/9 XS2R-D426-1 XS8A-0441 859RD04-103R004