

> HUL
 > Monitoring Relays
 > Voltage Monitoring Relays
 > DIN Rail Mount 35 mm

- > Control of AC and DC voltages
- > Automatic recognition of AC/DC
- > Measurement ranges from 0.2 V to 600 V
- > Choice between under and overvoltage
- > True RMS measurement
- > Selectable latching (memory) function



Specifications			
Functions	Measurement range	Nominal voltage (V)	Code
Under/O vervoltage	0,2 V → 60 V	24 → 240 V AC/DC	84872120
Power supply			
Supply voltage Un		24 V → 240 V AC/DC	
Voltage supply tolerance		-15 % / +10 %	
Operating range		20,4 V → 264 V AC/DC	
Polarity with DC voltage		No	
AC supply voltage frequency		50 / 60 Hz ±10 %	
Galvanic isolation of power supply/measurement		No	
Power consumption at Un		3.5 VA in AC/0.6 W in DC	
Immunity from micro power cuts		10 ms	
Inputs and measuring circuit			
Frequency of measured signal		0 Hz, 40 → 70 Hz	
Max. measuring cycle time		30 ms/True RMS measurement	
Threshold adjustment		10 → 100 % of the range	
Hysteresis		Adjustable from 5 → 50 % of displayed threshold	
Display precision		±10 % of full scale	
Repetition accuracy with constant parameters		± 0,5 %	
Measuring error with voltage drift		< 1 % across the whole range	
Measuring error with temperature drift		± 0,05 % / °C	
Time delays			
Delay on threshold crossing Tt		0,1 → 3 s (0, + 10 %)	
Repetition accuracy with constant parameters		± 2 %	
Reset time		1500 ms	
Delay on pick-up		< 600 ms	
Outputs			
Type of output		1 double changeover relay	
Type of contacts		No cadmium	

Outputs	
Maximum breaking voltage	250 V AC/ DC
Max. breaking current	5 AAC/DC
Min. breaking current	10 mA / 5 VDC
Electrical life (number of operations)	1 x 10 ⁵
Breaking capacity (resistive)	1250 VA AC
Maximum rate	360 operations/hour at full load
Operating categories acc. to IEC/EN 60947-5-1	AC12, AC13, AC14, AC15, DC12, DC13, DC14
Mechanical life (operations)	30 x 10 ⁶
Insulation	
Nominal insulation voltage IEC/EN 60664-1	250 V
Insulation coordination (IEC/EN 60664-1)	Overvoltage category III : degree of pollution 3
Rated impulse withstand voltage (IEC/EN 60664-1)	4 KV (1,2 / 50 µs)
Dielectric strength (IEC/EN 60664-1)	2 KV AC 50 Hz 1 min.
Insulation resistance (IEC/EN 60664-1)	> 500 MΩ(s) / 500 V DC
General characteristics	
Display power supply	Green LED
Display relay	Yellow LED
Casing	35 mm
Mounting	On 35 mm symmetrical DIN rail, IEC/EN 60715
Mounting position	All positions
Material : enclosure plastic type VO to UL94 standard	Incandescent wire test according to IEC/EN 60695-2-11
Protection (IEC/EN 60529)	Terminal block : IP 20 Casing : IP 30
Weight	130 g
Connecting capacity IEC/EN 60947-1	Rigid : 1 x 4 ² - 2 x 2.5 ² mm ² 1 x 11 AWG - 2 x 14 AWG Flexible with ferrules : 1 x 2.5 ² - 2 x 1.5 ² mm ² 1 x 14 AWG - 2 x 16 AWG
Max. tightening torques IEC/EN 60947-1	0,6 → 1 Nm / 5,3 → 8,8 Lbf.In
Operating temperature IEC/EN 60068-2	-20 → +50 °C
Storage temperature IEC/EN 60068-2	-40 → +70 °C
Humidity IEC/EN 60068-2-30	2 x 24 hr cycle 95 % RH max. without condensation 55 °C
Vibrations according to IEC/EN60068-2-6	10 → 150 Hz, A = 0.035 mm
Shocks IEC/EN 60068-2-6	5 g
Standards	
Product standard	IEC/EN 60255-1
Electromagnetic compatibility (EMC)	IEC/EN 61000-6-1, IEC/EN 61000-6-2, IEC/EN 61000-6-3, IEC/EN 61000-6-4
Certifications	UL, CSA
Marking	CE (DBT) 2006/95/EC - EMC 2004/108/EC
Conformity with environmental directives	RoHS

Dimensions

HUL-HUH		
---------	--	--

Curves

--	--

Connections

HUL-HUH	
---------	--

PP-YYYY-WWW
12345

HUL 84 872 120

3 5 89 190 0024400

OVERVOLTAGE
Un
H
U
R
without memory / with memory

UNDERVOLTAGE
Un
H
U
R
without memory / with memory

TORQUE: 0.8...Nm
5.3...8.8 lbf.in
0.5...2.5mm²
2x 20L16AWG
2x 20L16AWG

UL
IEC
IND.CONT.EQ.
Made in [XXXXXX]

CE

Crouzet

Undervoltage
Overvoltage
No Memory / with memory

U Value
Hysteresis
Tt

HUL

12 11 14 22 21 24

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Controllers](#) category:

Click to view products by [Crouzet](#) manufacturer:

Other Similar products are found below :

[61FGPN8DAC120](#) [CV500SLK21](#) [70177-1011](#) [F03-03 HAS C](#) [F03-31](#) [81550401](#) [FT1A-C12RA-W](#) [88981106](#) [H2CAC24A](#) [H2CRSAC110B](#)
[R88A-CRGB003CR-E](#) [R88ARR080100S](#) [R88A-TK01K](#) [DCN1-1](#) [AFP0RT32CT](#) [DRT2ID08C](#) [DTB4896VRE](#) [DTB9696CVE](#)
[DTB9696LVE](#) [E53-AZ01](#) [E53E01](#) [E53E8C](#) [E5C4Q40J999FAC120](#) [E5CWLQ1TCAC100240](#) [E5GNQ03PFLKACDC24](#) [B300LKL21](#)
[NSCXDC1V3](#) [NSH5-232CW-3M](#) [NT20SST122BV1](#) [NV-CN001](#) [OAS-160-N](#) [C40PEDRA](#) [K31S6](#) [K33-L1B](#) [K3MA-F](#) [100-240VAC](#)
[K3TX-AD31A](#) [89750101](#) [L595020](#) [SRM1-C02](#) [SRS2-1](#) [G32X-V2K](#) [26546803](#) [26546805](#) [PWRA440A](#) [CPM1AETL03CH](#) [CV500SLK11](#)
[3G2A5BI081](#) [3G2A5IA122](#) [3G2A5LK010E](#) [3G2A5OA223](#)