

## TOP VIEW



## SIDE VIEW (2)





	16.1±0.3	0.7±0.1
4.75±0.2	- 6±0	46.5±0.2

Specifications		Notes		Revision History						
Description	Value	Unit	Notes		Version	Description			Date	Approved
Shape	Rectangle		1) All dimensions are in mm (	1	Released from Engineering			2/8/2014	J.S.	
Resonant Frequency	600	(Hz)	2) All parts meet RoHS							
Frequency Range	600 ~ 5,000	(Hz)								
SPL @ 10cm	93	(dBA)								
Impedance	8	(Ohm)								
Cone Material	Polyetherimide									
Nominal Power	1.0	(W)								
Max Power	1.5	(W)								
Mount Type	Thru Hole			Draw	Drawn by	Date	Checked by	Date	Approved by	Date
Operating Temperature	-40 ~ +85	°C			G.W.	1/27/2014	C.E.	2/5/2014	J.S.	2/8/2014
Storage Temperature	-40 ~ +85	°C	High Town Dynamic Su		akor	SM420608-1				
Weight	9	(g)		High Temp Dynamic Speaker						

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Speakers & Transducers category:

Click to view products by DB Unlimited manufacturer:

Other Similar products are found below:

FC-30814-P127 AS02832MR-2-R PB-1220PE PB-2015PQ 900-00001 AB2025B-LW50-R SWFK-31736-000 PT-2065FW PT-4175W AT-2830-TW-LW35-R ED-30761-000 CI-30120-A42 SMT-0440-T-2-R PB-0927PQ BF-7083-000 SMS2020-08H4.5 LF BDT1717-08H6.5W56MLF GSPK1003PN-8R0.2W-L100 GSPK151103TN-8R0.2W GSPK2014035PN-8R0.5W-L100 AS03608MR-LW100-R 24520 SMT-0540-S-2-R 1450069 9091653 9091661 IPS-G6000-5 9090231 FS50MS0820-H9.7 FS4014-4-2W PBM4-13.B29R.A115.0663 PBM4-13.B31R.A115.0663 PBM4-13.B33R.A115.0663 PBM4-13.B35R.A115.0663 A-10-6-BG360-HD1Z-GA-M4Z-ZW A-10-6-BG410-HD1Z-AA-AGZ-ZW A-10-6-BG410-HD1Z-AA-M4Z-ZW A-10-6-BG310-HD1Z-AA-M4Z-ZW A-10-6-BG310-HD1Z-AA-AGZ-ZW A-10-6-BG310-HD1Z-AA-M4Z-ZW A-10-6-BG310-HD1Z-AA-AGZ-ZW A-10-6-BG340-HD1Z-AA-AGZ-ZW A-10-6-