
	LED CO	LOR = YE	LOW / G	REEN BI-	COLOR	
	OPERATING	CHARACT	ERISTICS	AT 25°C	AMBIENT	
CHARACTERISTICS	COLOR	MIN	TYP	MAX	UNITS	TEST CONDITIONS
LUMINOUS INTENSITY	GREEN	2.5	6.3			l = 10 mA
	YELLOW	2.5	4.3		mc d	
FORWARD VOLTAGE	GREEN		2.1	2.8	v	l = 20 mA
	YELLOW		2.1			
PEAK WAVELENGTH	GREEN		565			
	YELLOW		585		nm	
VIEWING ANGLE	ALL	80		Degree		

ABSOLUTE MAXIMUM RATING AT 25°C AMBIENT	UNITS	GREEN	YELLOW
POWER DISSIPATION	mW	100	60
CONTINUOUS FORWARD CURRENT	mA	30	20
DERATE LINEARLY FROM 25°C	mA/°C	0.4	0.25
OPERATING TEMPERATURE	•c	-55 TO 100	
STORAGE TEMPERATURE	•c	-55 TO 100	



REVISIONS

NEW RELEASE

THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE WRITTEN CONSENT OF DIALIGHT.

C-16546

3mm BI-LEVEL CBI BLOCK

FAMILY TABLE:

1913 ATLANTIC AVE. MANASQUAN, N.J. 08736

DRAWING NUMBER

TITLE

MATERIAL

SHEET

SCALE 8:1

TOLERANCES: UNLESS OTHERWISE SPECIFIED

DECIMALS (.XXX): ±.020
DECIMALS (.XXXX): ±.015
DECIMALS (.XXXX):
ANGLES: ±3\*

83330

FRACTIONS: ±1/64

FINISH:

FSCM

ALL DIM'S IN: INCHES


REV. ECN NO.

DRN. CKD. APP.

A۷

DATE

REV



LED COLOR					
POSITION I	YEL / GRN				
POSITION 2	YEL / GRN				

## NOTES :

- I- LEADS TO FIT INTO HOLES SPACED AS PER HOLE PATTERN
   2- LEADS TO BE FREE OF DEFORMATION AFTER BENDING AND CUTTING
   3- DIALIGHT PART NUMBER = 553-0744-838

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LED Circuit Board Indicators category:

Click to view products by Dialight manufacturer:

Other Similar products are found below:

568-0701-841F LTL-4221NH129 LTL-42DGNMHDP1 HLMP1521101 HLMP1523802F HLMP1700101F HLMP1700104F BHA-1564-G SMF-HM1530YD-305 SSF-LXH409SYSUGW AM2520EHSGD HLMP1301104F HLMP1385101F HLMP1421101 HLMP1503103F HLMP1503104F HLMP1700102F HLMP1700106F HLMP1700107F HLMP1790101F HLMP1790103F LTL-4211NHBP 5390H3 551-2802F 552-0794-810F 553-0222-812F HT3-BC-T 564-0700-831F WP59BLGEW 103-3101-1231-403 5502407811F 550-3007-810F 551-3307MF 552080-1 573-2399-100F 592-2020-302F 5932-927-2701-3F SMF-HM1530SRD-509 SSF-LXH100MID SSF-LXH2103SRSRDRP SSF-LXH555USBW WP937SB/4YGW WP937EB2EGW 551-0312-802F 553-0110-802F 561-5501-050F 6202T3-5VLC LTL-307G08A-D CMD57164 568-2231-313F