

# SM2400 EVK2

Complete Evaluation Kit for SM2400 N-PLC Modem

# Configurable Evaluation Kit (V2)

**Improved solution with flexible interfaces to facilitate engineering evaluation via a PC-based GUI application. Easily enables comprehensive configuration, control and monitoring/testing of the communication performance of the SM2400 modem subsystem.**

Kit includes a baseboard for flexible connectivity and a swappable modem module for optimized configurations.

## Product Overview

### Baseboard

- mini-USB for PC connection and JTAG connector
- UART and SPI interface
- External 12V/15V DC supply
- Zero Crossing Detector

### Downloadable Firmware builds

- OFDM: PRIME, G3-PLC, IEEE 1901.2, Full-Band Mode
- XXR High Robust mode
- SunSpec
- Simple Mesh Networking (SMESH)

### Interchangeable Modem Modules

- Module Dimensions:  
83mm(L) x 45mm(W)
- Built-in power line coupling circuit
- Supports up to 400VDC or 240VAC
- Modules with optimized operational bands
  - CENELEC A
  - CENELEC B/BC
  - FCC/ARIB
  - Full Band
- Line Driver Options
  - Intersil
  - Discrete Front End
  - SG Micro
  - ON Semiconductor

## Kit Content & Configurations

### Includes:

- Base board
- SM2400 EV1Mn-x module
- USB cables
- User Guide (Download)
- Firmware + GUI (Download)
- DC Power Supply



*Additional firmware packages become available from time to time. These and other reference material such as schematics and bill of material are downloadable from the Adesto website.*

### Evaluation Kit Ordering Options:

#### SM2400-EVK2Mn-x


n options:

- 1 = Reserved
- 2 = Intersil Line Driver
- 3 = Discrete Front End
- 4 = SG Micro Line Driver
- 5 = ON Semiconductor Line Driver



x options:


- A = CENELEC A Band
- B = CENELEC B/BC Band
- C = FCC Band
- D = Full Band



# FAST COMPREHENSIVE EVALUATION TOOL FOR RAPID DEPLOYMENT

## INTERFACES

There are 4 headers on the back of the SM2400 EV1Mn-x modules. The designator Pin 1 and the location of each header can be found in the board layout below. The pin out and description of each header are described in the following tables.



SM2400 EV1Mn-x Top View

### Header H2

Pin #	Name	Functionality
1,2	ACTIVE	Mains Active
3,4,5,6	NC	
7,8	NEUTRAL	Mains Neutral

### Header H6 (DNP)

Pin #	Name	Dir	Functionality
1	JTDO	O	JTAG Interface
2	JTMS	I	JTAG Interface
3	JTDI	I	JTAG Interface
4	JTCK	I	JTAG Interface
5	JTRSTB	I	JTAG Interface
6	GND	P	Ground
7	COREIO14	IO	COREIO
8	COREIO10	IO	COREIO
9	COREIO12	IO	COREIO
10	COREIO13	IO	COREIO
11	NC		
12	GND	P	Ground

### Header H7

Pin #	Name	Dir	Functionality
1	NC		NC for SM2400 based module
2	NC		NC for SM2400 based module
3, 4	3V3	P	External 3.3V Supply
5, 6	AFE_VCC	P	15V @ 125mA
7, 8, 9	GND	P	Ground
10	UART_TDO	O	SM2400 UART TXD
11	UART_RDI	I	SM2400 UART RXD
12	UART_HSI	I	SM2400 UART Handshake Input
13	UART_HSO	O	SM2400 UART Handshake Output
14	Mode2	I	Boot mode pin 2
15	Mode1	I	Boot mode pin 1
16	Mode0	I	Boot mode pin 0
17	RESETb	I	Reset
18	COREIO15	IO	COREIO
19	GND	P	Ground
20	SPIS_OUT	O	Host SPI Slave Interface
21	SPIS_SCK	I	Host SPI Slave Interface
22	SPIS_IN	I	Host SPI Slave Interface
23	GND	P	Ground
24	SPIS_SSb	I	Host SPI Slave Interface

### Header H8 (DNP)

Pin #	Name	Dir	Functionality
1	NC		NC for SM2400 based module
2	SPIM_OUT	O	SPI Master Interface
3	SPIM_SCK	O	SPI Master Interface
4	SPIM_IN	I	SPI Master Interface
5	SPIM_SS0b	O	SPI Master Interface (Mapped to on board SPI boot memory)
6	SPIM_SS1b	O	SPI Master Interface
7	SPIM_SS2b	O	SPI Master Interface
8	GND	P	Ground
9	COREIO02	IO	PHYLED (Output)
10	COREIO01	IO	RXRANGE1 (output)
11	COREIO00	IO	RXRANGE0 (output)
12	COREIO11	IO	Overcurrent Flag (Output)
13	COREIO09	IO	COREIO
14	COREIO08	IO	TX Enable (Output)
15	GND	P	Ground
16	NC		NC for SM2400 based module



# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for Networking Development Tools category:***

***Click to view products by Dialog Semiconductor manufacturer:***

Other Similar products are found below :

[MAX79356CAEVK1#](#) [MAX2982EVSYS](#) [BASENODE-EK](#) [DC-ME-9210-LX](#) [DC9018B-B](#) [DC9007A](#) [DC9021B](#) [ATPANCOORDINATOR-EK](#) [SM2400-EVK2M2-C](#) [SM2400-EVK2M5-A](#) [Pi01-2](#) [Pi01-3](#) [Pi01-4](#) [Pi01-42](#) [Pi01-43](#) [pind-4ge](#) [pind-4ga](#) [tbit-32](#) [DC9020B](#) [DC9022B](#) [RAPID-TSNEK-V0001](#) [ABX00017](#) [GKX00006](#) [DC-ACC-DBME](#) [DC-ME-01T-MF-10](#) [DG-EXT-300-RR](#) [XP10010NMK-01](#) [XPC100100K-02](#) [XPC240300EK](#) [XPC250300EK](#) [XPE200100EK](#) [Development Kit, RS232](#) [Development Kit, USB](#) [RD-HNPH2DCP962KIT-01](#) [ATPL360-EK](#) [MIKROE-3739](#) [MIKROE-3888](#) [MIKROE-2747](#) [NNDK-MOD5213-KIT](#) [SB800EX-KIT](#) [ESP32-GATEWAY](#) [NCN5110ASGEVB](#) [NCN5121ASGEVB](#) [FPWEB2](#) [XENNKIT](#) [604565285904](#) [110060622](#) [110060623](#) [SLUSB001A](#) [SLWRB4305D](#)