











REV.	REVISION DESCRIPTION	DATE	APPD

NOTES

Available in 04 through 60 Circuits.
Mates with DL25028-Y Series Housing.
Material : Nylon UL94V-0(2)
0.50mm Square Pin.
Pin Material : Brass / Tin-Plated.



嵌合状态



Circuits	Product name	Dimension mm				
		A	B	C	D	E
2X2	HX2.5-4AWD	2.5	5.3	7.45	1.55	2.5
2X3	HX2.5-6AWD	5.0	7.8	9.95	4.05	2.5
2X4	HX2.5-8AWD	7.5	10.3	12.45	6.55	2.5
2X5	HX2.5-10AWD	10.0	12.8	14.95	9.05	2.5
2X6	HX2.5-12AWD	12.5	15.3	17.45	11.55	2.5
2X7	HX2.5-14AWD	15.0	17.8	19.95	14.05	2.5
2X8	HX2.5-16AWD	17.5	20.3	22.45	16.55	2.5
2X9	HX2.5-18AWD	20.0	22.8	24.95	19.05	2.5
2X10	HX2.5-20AWD	22.5	25.3	27.45	21.55	3.0
2X11	HX2.5-22AWD	25.0	27.8	29.95	24.05	2.5
2X12	HX2.5-24AWD	27.5	30.3	32.45	26.55	2.5
2X13	HX2.5-26AWD	30.0	32.8	34.95	29.05	2.5
2X14	HX2.5-28AWD	32.5	35.3	37.45	31.55	2.5
2X15	HX2.5-30AWD	35.0	37.8	39.95	34.05	3.0
2X16	HX2.5-32AWD	37.5	40.3	42.45	36.55	2.5
~	~	~	~	~	~	~
2X30	HX2.5-60AWD	72.5	75.3	77.45	71.55	2.5

GENERAL TOLERANCES (UNLESS SPECIFIED)		ZHE JIANG DELI CONNECTORS CO., LTD			
.X: ± 0.25	X°: ± 3.0°	PRODUCT NAME: DL25028 (HX2.5)-AWD		TITLE: 2.5 mm Pitch Wire To Board Wafer	
.XX: ± 0.15	.X°: ± 2.0°	DR: Chen Quan Long	DATE: 20.12.20	PART NO:	
.XXX: ± 0.01	.XX°: ± 1.0°	CHKD: Wu Hui	DATE: 20.12.20	SCALE: N/A	PAGE: 1/1
FINISH:		APPD: Ren An De	DATE: 20.12.20	UNITS: mm	REV.: A
DRAWING NO:					

REV.	REVISION DESCRIPTION	DATE	APPD





NOTES

Available in 08 through 40 Circuits.


Mates with DL25028-A Or DL25028-AWD Series WAFER.

Material : Nylon UL94V-0(2).

Accepts DL25028-T Crimp Terminal.



嵌合状态



Circuits	Product name	Dimension mm		Circuits	Product name	Dimension mm	
		A	B			A	B
2X2	HX2. 5-4Y	2. 5	5. 0	2X12	HX2. 5-24Y	27. 5	30. 0
2X3	HX2. 5-6Y	5. 0	7. 5	2X13	HX2. 5-26Y	30. 0	32. 5
2X4	HX2. 5-8Y	7. 5	10. 0	2X14	HX2. 5-28Y	32. 5	35. 0
2X5	HX2. 5-10Y	10. 0	12. 5	2X15	HX2. 5-30Y	35. 0	37. 5
2X6	HX2. 5-12Y	12. 5	15. 0	2X16	HX2. 5-32Y	37. 5	40. 0
2X7	HX2. 5-14Y	15. 0	17. 5	2X17	HX2. 5-34Y	40. 0	42. 5
2X8	HX2. 5-16Y	17. 5	20. 0	2X18	HX2. 5-36Y	42. 5	45. 0
2X9	HX2. 5-18Y	20. 0	22. 5	2X19	HX2. 5-38Y	45. 0	47. 5
2X10	HX2. 5-20Y	22. 5	25. 0	~	~	~	~
2X11	HX2. 5-22Y	25. 0	27. 5	2X30	HX2. 5-60Y	72. 5	75. 0

GENERAL TOLERANCES (UNLESS SPECIFIED)		ZHE JIANG DELI CONNECTORS CO.,LTD	
.X: ± 0.25	X° : ± 3.0°	PRODUCT NAME: DL25028 (HX2. 5)-Y	TITLE: 2.50 mm Pitch Wire To Board Housing
.XX: ± 0.15	.X° : ± 2.0°		DR:Chen Quan Long
.XXX: ± 0.01	.XX° : ± 1.0°	DATE:20. 12. 20	PART NO:
FINISH:		CHKD: Wu Hui	DATE:20. 12. 20
DRAWING NO:		APPD: Ren An De	DATE:20. 12. 20
			SCALE: N/A
			PAGE: 1/1
			UNITS: mm
			REV.: A

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [DLL](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [0010894062](#) [0010977306](#) [0015477636](#) [0015917161](#) [0022104068](#) [0022121042](#) [0022155065](#) [0022281023](#) [57102-F02-18ULF](#) [PCN6B-10P-2.5DS](#) [58102-G61-06LF](#) [582553-1](#) [0015911208](#) [01.001.5753.1](#) [0022285048](#) [0050291907](#) [02.125.8002.8](#)
[CSU011177004](#) [622-0430](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#)
[65817-010LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#)
[71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[803-43-024-10-001000](#)