

ECS-TXO-25CSMV

Clipped Sine Wave TCXO

MultiVolt™

ECS-TXO-25CSMV Clipped Sine Wave SMD TCXO MultiVolt™ capability of 1.7 ~ 3.465V. The 2.5 x 2.0 x 1.0 mm ceramic package is ideal for portable, wireless applications where stability is critical.

[Request a Sample](#)

OPERATING CONDITIONS / ELECTRICAL CHARACTERISTICS

ECS-TXO-25CSMV



- Clipped Sine Wave TCXO
- 2.5 x 2.0 mm Footprint
- MultiVolt™ (1.7 ~ 3.465V)
- PbFree/RoHS Compliant
- MSL 1
- Lead Finish Au
- Compatible with 1.8V, 2.5V or 3.3V Power Supply

Parameters	Conditions	ECS-TXO-25CSMV			Units
		MIN	TYP	MAX	
Frequency Range		10.000		52.000	MHz
Frequency Tolerance	@ +25°C ±2°C			±2.0	PPM
Frequency Stability	Vs. Temp (-40 ~ +85°C) BN Opt			±1.0	PPM
	Vs. Supply Change (±5%)			±0.2	PPM
	Vs. Load Change (±10%)			±0.2	PPM
	Vs. Aging 1 st Year			±1.0	PPM
Input Voltage	VDD	+1.7		+3.465	VDC
Current Consumption	10 ~ 26 MHz			2.0	mA
	26.1 ~ 52 MHz			2.5	mA
Output Level	Clipped Sine Wave	0.8			V p-p
Output Load		10KΩ//10 pF			
Start-up Time				2	mS
Phase Noise	@ 10 KHz Offset		-145		dBc/Hz
Operating Temperature	* N Option	-40		+85	°C
Storage Temperature		-40		+90	°C

Part Numbering Guide: Example ECS-TXO-25CSMV-320-BN-TR

ECS	-	Series	-	Frequency Abbreviations	-	Stability	-	Temperature	-	Packaging
ECS		TXO-25CSMV = Clipped Sine Wave TCXO		260 = 26.000 MHz		A= ±0.5 ppm B= ±1.0 ppm C= ±1.5 ppm D= ±2.0 ppm E= ±2.5 ppm		L= -10 ~ +70°C M= -20 ~ +70°C Y= -30 ~ +85°C N= -40 ~ +85°C		TR = Tape & Reel 1K/reel

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [TCXO Oscillators](#) category:

Click to view products by [ECS Inc](#) manufacturer:

Other Similar products are found below :

[SIT5000ACC8E-33VQ-19.200000X](#) [SiT5001AI-2E-33N0-48.000000X](#) [TG3225CEN 25.0000M-KFGNNAB](#) [SIT5001AI-2E-33N0-24.000000x](#)
[SIT1566AC-JV-18E-32.768E](#) [KT1612A26000AAW18NBL](#) [X1G005421031215](#) [TX0408CB](#) [NT1220HH3I106EN100](#)
[NT1220HS3I106EN100](#) [NT1220HS3I507EN100](#) [BT0507BC3I507CN27](#) [SIT5146AI-FA-33N0A40.000000F](#) [SiT9551AI-02B1A3310-](#)
[312.500000](#) [NT1220HH3I507EN100](#) [BT0914AD3C507DN100](#) [BT0914AD3C106DN100](#) [9132S-26.000N30FT1XL](#) [8132S-10.000MN18DTL](#)
[8153S-26.000NL33DTL](#) [9175S-10.000K33FT1JL](#) [SX2T25.000B010J020S](#) [ATXAIG-H13-F-26.000MHZ-F25-T3](#) [ATX-13-D-26.000MHZ-](#)
[E05-T3](#) [LFPTXO000291](#) [LFTCXO073006](#) [SIT5356AI-FQ-33E0-25.000000X](#) [SIT5357AI-FQ-33N0-100.000000X](#) [ECS-TXO-2520-33-120-](#)
[AN-TR](#) [SiT5000AICGE-33E0-25.000000X](#) [SiT1568AI-JE-DCC-32.768E](#) [AST3TQ-T-20.000MHz-28](#) [AST3TQ-T-25.000MHz-28](#)
[SiT1552AC-JE-DCC-32.768D](#) [AST3TQ-V-30.720MHz-28](#) [AST3TQ-T-30.720MHz-28](#) [AST3TQ-T-40.000MHz-28](#) [ABDFTCXO-](#)
[20.000MHz-L-2-CT](#) [718-24-15](#) [AST3TQ-10.00MHz-2](#) [AST3TQ-19.20MHz-5](#) [AST3TQ-25.00MHz-5](#) [ASGTX-D-100.000MHz-1](#) [ASGTX-D-](#)
[106.250MHz-1](#) [ASGTX-P-1.500GHz-1](#) [AST3TDA-0000-T5](#) [AST3TDA53TACJ2-19.2000MHz](#) [AST3TDATAACJ5-20.0000MHz](#) [AST3TQ53-](#)
[T-10.000MHz-5-C](#) [AST3TQ53-T-20.000MHz-5-C](#)