

ECS-TXO-3225MV


MultiVolt™ HCMOS TCXO

ECS-TXO-3225MV HCMOS SMD TCXO MultiVolt™ capability of 1.7 ~ 3.6V. The 3.2 x 2.5 x 1.2 mm ceramic package is ideal for portable, wireless applications where stability is critical.

[Request a Sample](#)

OPERATING CONDITIONS / ELECTRICAL CHARACTERISTICS

ECS-TXO-3225MV



© ECS, Inc. International

- HCMOS TCXO
- 3.2 x 2.5 mm Footprint
- MultiVolt™ (1.7 ~ 3.6V)
- PbFree/RoHS Compliant
- MSL 1
- Lead Finish Au
- Compatible with 1.8V, 2.5V or 3.3V Power Supply

Parameters	Conditions	ECS-TXO-3225MV			Units
		MIN	TYP	MAX	
Frequency Range		8.000		60.000	MHz
Operating Temperature	* Standard	-30		+85	°C
Storage Temperature		-40		+90	°C
Input Voltage	VDD	+1.7		+3.6	VDC
Frequency Stability	Vs. Temp (-30 ~ +85°C)			±2.5	PPM
	Vs. Supply Change (±5%)			±0.3	PPM
	Vs. Load Change (±5%)			±0.3	PPM
	Vs. Aging/Year			±1.0	PPM
Frequency Tolerance	@ +25°C ±2°C			±1.5	PPM
Current Consumption				6.0	mA
"0" Level	VOL			10% Vdd	VDC
"1" Level	VOH	90% Vdd			VDC
Output Symmetry	@50% VDD Level			45/55	%
Rise and Fall Times	10% VDD to 90% Level			5	ns
Output Load	CMOS			15	pF
Start-up Time				10	mS
Phase Noise	@ 10 KHz Offset		-145		dBc/Hz

Part Numbering Guide: Example ECS-TXO-3225MV-250-TR

ECS	-	Series	-	Frequency Abbreviations	-	Stability Tolerance	-	Temperature	-	Packaging
ECS		TXO-3225MV = TCXO		250 = 25.000 MHz		Standard Blank = ±2.5 ppm		Standard Blank = -30 ~ +85°C Custom Options * N = -40 ~ +85°C		TR = Tape & Reel 1K/reel

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [TCXO Oscillators](#) category:

Click to view products by [ECS Inc](#) manufacturer:

Other Similar products are found below :

[SIT5000ACC8E-33VQ-19.200000X](#) [SiT5001AI-2E-33N0-48.000000X](#) [TG3225CEN 25.0000M-KFGNNAB](#) [SIT5001AI-2E-33N0-24.000000x](#)
[SIT1566AC-JV-18E-32.768E](#) [KT1612A26000AAW18NBL](#) [X1G005421031215](#) [TX0408CB](#) [NT1220HH3I106EN100](#)
[NT1220HS3I106EN100](#) [NT1220HS3I507EN100](#) [BT0507BC3I507CN27](#) [SIT5146AI-FA-33N0A40.000000F](#) [SiT9551AI-02B1A3310-](#)
[312.500000](#) [NT1220HH3I507EN100](#) [BT0914AD3C507DN100](#) [BT0914AD3C106DN100](#) [9132S-26.000N30FT1XL](#) [8132S-10.000MN18DTL](#)
[8153S-26.000NL33DTL](#) [9175S-10.000K33FT1JL](#) [SX2T25.000B010J020S](#) [ATXAIG-H13-F-26.000MHZ-F25-T3](#) [ATX-13-D-26.000MHZ-](#)
[E05-T3](#) [LFPTXO000291](#) [LFTCXO073006](#) [SIT5356AI-FQ-33E0-25.000000X](#) [SIT5357AI-FQ-33N0-100.000000X](#) [ECS-TXO-2520-33-120-](#)
[AN-TR](#) [SiT5000AICGE-33E0-25.000000X](#) [SiT1568AI-JE-DCC-32.768E](#) [AST3TQ-T-20.000MHz-28](#) [AST3TQ-T-25.000MHz-28](#)
[SiT1552AC-JE-DCC-32.768D](#) [AST3TQ-V-30.720MHz-28](#) [AST3TQ-T-30.720MHz-28](#) [AST3TQ-T-40.000MHz-28](#) [ABDFTCXO-](#)
[20.000MHz-L-2-CT](#) [718-24-15](#) [AST3TQ-10.00MHz-2](#) [AST3TQ-19.20MHz-5](#) [AST3TQ-25.00MHz-5](#) [ASGTX-D-100.000MHz-1](#) [ASGTX-D-](#)
[106.250MHz-1](#) [ASGTX-P-1.500GHz-1](#) [AST3TDA-0000-T5](#) [AST3TDA53TACJ2-19.2000MHz](#) [AST3TDATAACJ5-20.0000MHz](#) [AST3TQ53-](#)
[T-10.000MHz-5-C](#) [AST3TQ53-T-20.000MHz-5-C](#)