SPRING RF CONNECTOR ——弹片系列



技术参数 Technology Parameters

- Frequency Range 頻率范围: DC ~ 3GHz
- Impedance 特性阻抗: 50 Ω
- · Pre-load Force 承受压力: 0.4N.Min
- Solder Ability 焊接能力: sold coverage 95%
- Center Contact Resistance 接触电阻: 50m Ω Max
- Voltage Standing wave Ratio(VSWR) 电压驻波比: 1.5 Max(DC~3GHz);
- Insertion Loss 插入损耗: -0.6 dB Max(DC-3GHz);
- Mechanical Durability 机械寿命: 100 Cycles
- · Operating Temperature 工作温度: -40℃ -- +65℃

Appearance Dimensions 外形尺寸:

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cylindrical Battery Contacts, Clips, Holders & Springs category:

Click to view products by ECT manufacturer:

Other Similar products are found below:

753-00001 12BH36A-GR 273 183 270 274 QX3506 5220 5230 1055 1088 1102 1101 5250 166 1044 1194 KT0008 2134167-1 1012 1020 1023 1024C 1025 1027 103 1075 1077 1080 1088 1090 1095 1096 1097 1098 1101 1109 1126 1127 1128 1162 1173 BH383B 1199 147 148 149 150 151 152