



Modular Jacks



ORDERING GUIDE



FEATURES

- Top performance for high speed networking, voice and data applications
- Meets FCC 68 requirements
- ISDN standard
- Industry standard footprint and height with low profile options available
- Available with or without shielding
- Ganged and / or stacked for multiple port requirements
- Advanced EMI/RFI protection
- Both plugs and jacks can be fully or partially loaded

SPECIFICATIONS

- Modular jack housing: PBT polyester, UL94V-0
- Modular plug housing: Polycarbonate, UL94V-2
- Operating temperature: -40 + 80 degrees C
- Contact: Phosphor bronze, gold on contact area, Tin/lead over nickel on tails
- Voltage: 1.25V
- Current: 1.5A
- Contact resistance: 20 milliohms maximum
- Dielectric withstanding voltage: 1000 VAC
- Insulation resistance: 500 M ohms minimum

Series

- A0 Modular Jacks
- A1 Modular Plugs

of Ports

Depending on requirement

Total # of Contacts

2-96 Depending on configuration

Contact Plating Code

- 2 gold flash
- 3 15u" gold
- 6 30u" gold
- 9 50u" gold

Contact Tail Type

- 2 Vertical
- 6 Right angle
- 9 Surface Mount

Shielding

- 0 Unshielded
- 1 Metal Shield (Ground Back)
- 2 Metal Shield (Ground Front)
- 3 Half Metal Shield

Connector Type

- 45 Category 5


Variations

- 0 No Key (low profile)
- 1 Keyed (low profile)
- 2 No Key (high profile)
- 3 Keyed (high profile)
- 4 Vertical with flange
- 5 Vertical no flange




FOR MORE INFORMATION VISIT www.edac.net OR EMAIL edac@edac.net
 Phone: 416-754-3322 Fax: 416-754-3299

Modular Jack Part Number A00-108-290-450



NO. OF POSITIONS	NO. OF CONTACTS	"A"	"B"	"C"
8	8	.520 (13.21)	.400 (10.16)	.260 (6.35)
8	8	.600 (15.24)	.450 (11.43)	.360 (9.14)

Modular Jack Part Number A00-432-261-450



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Modular Connectors](#) / [Ethernet Connectors](#) category:

Click to view products by [EDAC](#) manufacturer:

Other Similar products are found below :

[8949-H88/06BLKA/SN](#) [74441-0010/BKN](#) [MP1010RX-1000](#) [MP44RX-1000](#) [PHJ-4P4C-1-V-4](#) [PHP-6P6C-5](#) [GAX-3-66](#) [GAX-8-62](#) [GDCX-PA-66-50](#) [GDCX-PN-64](#) [GDCX-PN-66](#) [GDCX-PN-66-50](#) [GDLX-A-66](#) [GDLX-N-66](#) [GDLX-S-66](#) [GDLX-S-88K](#) [GDTX-S-88-50](#) [GDX-PA-1010](#) [GLX-N-1010M-BLK](#) [GLX-S-88M-BLK](#) [GMX-N-1010](#) [GMX-S-1010](#) [GMX-S-66](#) [GMX-SMT4-N-88](#) [GPX-2-64](#) [GSGX-N-2-88](#) [GSGX-N-4-88](#) [GSX-NS2-88-3.05-50](#) [PT-108A-8C-UL](#) [PT-J951-8C](#) [PTS-J531-8CS-50UL](#) [1-1775629-2](#) [A-2014-0-4](#) [GWLX-S-88-GR](#) [GWLX-S9-88-YG](#) [DC-1021-8-WH-6](#) [1300530003](#) [1324640-4](#) [RJ11FTVC2G](#) [RJ11FTVC2N](#) [RJFTVX2SA1G](#) [132764-001](#) [1413235](#) [MP88X-1000](#) [MPS88RX-5000](#) [MRJR-5481-0F2](#) [E5288-S000K3-L](#) [E5908-15A242-L](#) [155302-001](#) [AX100653](#)