



Cost-effective and easy to use, Efest SLIM K4 charger comes with novel 7 languages packaging and user user manual! Incredibly lightweight and conveniently portable



**SLIM**



**K4**

Compatible With Lithium  
IMR 3.6V/3.7V Batteries:

- 10440
- 18500
- 14500
- 18650
- 16340
- 26500
- 17340
- 26650
- 18350
- 20700
- 18490
- 21700

Input power-----DC 5V 2A  
 2\*1A CC current ----- 2000mA±10%  
 1\*1A CC current ----- 1000mA±10%  
 4\*0.5A/3\*0.5A CC current ----- 500mA±10%  
 Auto cut-off voltage ----- 4.20±0.05V  
 CV cut-off current ----- <100mA  
 Standby current ----- <20mA  
 Activation current ----- 50mA~100 mA  
 Auto recharge voltage ----- 4.10±0.10V  
 Operation Temperature ----- 0°C ~ 40°C  
 Storage Temperature ----- -40°C ~ +70°C



HIGH QUALITY ABS FIRE-RETARDANT MATERIAL& ELECTRONIC COMPONENT

## LED INDICATOR DESCRIPTION

Efest SLIM K4 USB Charger

- After insert the battery to the slot correctly, SLIM K4 will charge the battery automatically in few seconds.
- Indicator in standby mode/fully charged turns blue color, white color while in charging.





## FEATURES

- Auto detect charging current: 2×1.0A/ 1×1.0A /4×0.5A/3×0.5A
- Safe charging mode: CC & CV
- Safe and convenient: USB charger (5V 2A)
- Monitors and charges each slot independently
- Low voltage smart activation recovery function
- Incredibly lightweight and conveniently portable



## CRAFTSMANSHIP

- Spring made by piano wire, it provides a smooth sliding action when installing and removing batteries.
- Steel cathode with low resistance and hard chromium plating processing to achieve a more precise charging voltage.
- 15,000+ times spring testing quality warranty



## USB PORT DESIGN

Type-C USB port reduce the heat of the port effectively



# 6

## Protection Levels Built-in Intelligent Protection Chip

1. Short circuit protection
2. Automatic over-charging protection
3. Automatic over-discharging protection
4. Reverse polarity protection
5. 0V activation recovery function
6. Hardware and software double protection

## CERTIFICATIONS



Global Insurance technical support with  
FCC, CE, RoHS certification.



# PACKAGE

Newest 7 Languages Version  
(EN/DE/FR/IT/ES/RU/JA)

## WARNING



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Adapters category](#):*

*Click to view products by [EFEST manufacturer](#):*

Other Similar products are found below :

[11904](#) [86-208-1-22](#) [13905](#) [86-207-1-22](#) [13904](#) [51957](#) [K-KJ55MCD40E](#) [HT8G616](#) [11903](#) [EE UNIVERSAL CHARGER 57658101401](#)  
[EPA1205L](#) [PEAK POWER U813](#) [L3EFT-SLIMK4](#) [L3EFT-LUSHQ8](#) [L3EFT-LUSHBOX](#) [L3EFT-IMATER4](#) [L3EFT-IMATER2](#) [L3EFT-](#)  
[SODA](#) [L3EFT-PROC4](#) [L3EFT-LUCV2](#) [L3EFT-ELITEV4](#) [L3EFT-LUCV4](#) [GDPT P2012-L2](#) [GDPT G600-168030](#) [BG21](#) [BM6018](#) [BM200-](#)  
[05](#) [PCM-L03-D142](#) [PCM-L08-D142](#) [PCM-L07-D142](#) [PCM-L04-D142](#) [POLOLU MICROSD ADAPTER](#) [GROVE CAPE FOR](#)  
[BEAGLEBONE](#) [GROVE BREAKOUT FOR LINKIT SMART 7688 DUO](#) [RBFN-EU-SEN-BMT-12](#) [9546](#) [9755](#) [9983](#) [51955](#) [51956](#) [51958](#)  
[51959](#) [52479](#) [52480](#) [52481](#) [I2C HUB](#) [DUAL MAX14870 MOTOR DRIVER SHIELD](#) [6PRO122420](#) [AB-12.100/ST8VA](#) [B631-2B1](#)