



## NOTES:

- 1. ALL DIMENSIONS IN MM
- 2. GENERAL TOLERANCE: X.X=±0.4

 $X.XX = \pm 0.25$ 

- 3. TERM. NOS. FOR REFERENCE ONLY.
- 4. RATING: 1A @125VAC, 0.5A @250VAC
- 5. CONTACT RESISTANCE: 10mILLI-OHMS
- 6. DIELECTRIC STRENGTH: 1000 VAC-1Minute
- 7. MATERIALS:

HOUSING: ZINC ALLOY DIE CAST

CYLINDER: ZINC ALLOY W/CHROME PLATING TERMINAL AND CONTACTS: SILVER PLATED KEYS (2): ZINC ALLOY, CHROME PLATING



## CIRCUIT: SPST CONTACT CONFIGURATION

SWITCH FUNCTION		
POS 1	POS 2	
<b>1</b>	$\rightarrow$	
OFF	(ON)	

**LEGEND** 

( )= MOMENTARY

○ =OFF POSITION

- =INDICATES KEY PULL
- X = INDICATES NO KEY PULL

ø 12.00 [.472] 10.80 [.425]

RECOMMENDED PANEL CUTOUT

D	13405	CORRECT OVERALL LENGTH	8/27/03	AR
С	13056	DESC. WAS KO133C-801	4/17/03	AR
В	12767	DESC WAS K0133E-801	1/27/03	CJB
Α	11735	RELEASED FOR PRODUCTION	10/12/01	СЈВ
REV.	ECN No.	DESCRIPTIΩN	DATE	CHKD
	THE INFORMATION CONTAINED IN THIS DOCUMENT			

IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

SCALE DATE 10/12/01

CJB DWG K4

**E-SWITCH®** 

K400109 REV D

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Keylock Switches category:

Click to view products by E-Switch manufacturer:

Other Similar products are found below:

89496-09 58J1007 58J8A45-01B05N 719-0201-000 719-0202-000 719-0702-000 719-5504-000 84800-04 GKNC33L GKNC3L

PVA2OAH5 HA1K-2C2VA-2 14-136.025K 14-235.022K AS6H-2K2A AS6M-2K1B AS6Q-2K2A AS6Q-3K2A 1571487-1 HW4K-2BF20

KEY-AS6 KH3C-20C 8928K493 2SWK131AL102 AS6M-2K1A AS6Q-2K1PB 51-401.036D 51-401.036K 51-414.036D HW1K-31BF20

HW1K-3HF20 Y1112-2027CLFT 51-155.025D 51-295.022D 51-404.036D 51-405.036D 51-415.036D 1-1437597-8 58J8A36-01B04N

58M1422 86945-05 719-0204-000 719-0205-000 719-0801-000 719-0804-000 719-0805-000 88422-18 58J8A90-01C02N 58J9P36
01B09N 58J8A36-01C03N