

TECHNICAL DATA

Fluke 87V MAX True-rms Digital Multimeter



The 87V MAX contains all the trusted features of the most popular DMM used today, the Fluke 87V, plus much more.

IP67 RATED

Fully waterproof and dust proof, to work reliably in all the places that you need to work.

WITHSTANDS DROPS UP TO 4-METERS (13 FEET)

Fluke's most rugged digital multimeter. The 87V MAX is built with an industrial strength case and a removable holster. The holster doubles as a test probe holder for one-handed operation.

WORKS AS LONG AS YOU DO

The 87V MAX provides double the battery life of the original 87V.

WITHSTANDS HEAT AND COLD

The meter has an extended operating temperature range of -40 °C (for up to 20 minutes) to +55 °C.

For use in extreme environments

The Fluke 87V MAX True-rms Digital Multimeter defines a new standard for operating in extreme conditions, with the features and accuracy to troubleshoot most electrical problems. The 87V MAX has an IP 67 (waterproof and dustproof) rating, extended operating temperature range of -15 °C to +55 °C (5 °F to 131 °F, -40 °C for up to 20 minutes) and 95 % humidity, and has been designed and tested to withstand a 4 m (13 ft) drop. The Fluke 87V MAX True-rms Digital Multimeter is built to work in the toughest environments you might face.

The 87V MAX also has an industrial-strength outer shell and a removable holster that doubles as test lead storage and a test probe holder for one-handed operation.

Product highlights

- True-rms ac voltage and current for accurate measurements on non-linear signals
- Measure up to 1,000 V ac and dc
- Measure up to 10 A (20 A for 30 seconds)
- Frequency to 200 kHz
- Built in temperate function conveniently allows you to take temperature readings without having to carry a separate instrument using supplied thermocouple
- Min/Max/Average recording, plus 250 µs Peak min-max to capture variations automatically
- Unique function for accurate voltage and frequency measurements on variable frequency motor drives (VFDs) and other electrically noisy equipment
- Large display digits, 2-level bright white backlight and backlit keypad buttons for increased visibility
- Hi resolution 19,999 count display mode
- Long battery life (800 hours)



Specifications

| Accuracy | | |
|--|---|----------------------------------|
| DC voltage | Max. resolution Accuracy | 0.1 mV to 1000 V 0.05 % + 1 |
| AC voltage | Max. resolution Accuracy | 0.1 mV to 1000 V 0.7 % + 4 |
| DC current | Max. resolution Accuracy | 0.1 μ A to 10 A 0.2 % + 2 |
| AC current | Max. resolution Accuracy | 0.1 μ A to 10 A 1.0 % + 2 |
| Resistance | Max. resolution | 0.1 Ω to 50 M Ω |
| Display counts | 6,000/19,999 | |
| Capacitance | 0.01 nF to 9999 μ F | |
| Frequency | 0.5 Hz to 199.99 kHz | |
| Temperature | -200 $^{\circ}$ C to +1090 $^{\circ}$ C | |
| Low pass filter (Measurement on VFDs) | Yes | |
| Safety rating | CAT IV 600 V, CAT III 1000V | |
| IP rating | IP 67 | |
| Power | Three AA batteries | |
| Battery life | 800 hours | |
| Display | | |
| Bar graph/backlight | Yes/Yes | |
| Data storage | | |
| Peak transient capture | 250 μ s | |
| Min/Max/Avg | Yes | |
| Reading hold | Yes | |
| Other features | | |
| Relative readings (zero) | Yes | |
| Battery type | Three AA batteries | |
| Warranty and protection | | |
| Safety rating | CAT IV 600 V/CAT III 1000 V | |
| External protection | Rubber holster | |
| Drop test | 4 meter (13 feet) drop test | |
| Dustproof/waterproof | Yes, IP 67 rated | |
| Warranty | Limited lifetime | |
| Size (HxWxL) with holster | 6.0 cm x 10.1 cm x 21.5 cm (2.4 in x 4.3 in x 8.5 in) | |
| Weight with holster | 698.5 g (1.54 lb) | |

Ordering information

Fluke 87V MAX True-rms Digital Multimeter

Included

Removable holster with test lead storage

TL175 TwistGuard® test leads

AC175 Alligator clips

80BK-A temperature probe

Three AA batteries (installed)



Fluke. *Keeping your world up and running.®*

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

Fluke Europe B.V.

PO Box 1186, 5602 BD
Eindhoven, The Netherlands

For more information call:

In the U.S.A. (800) 443-5853 or

Fax (425) 446-5116

In Europe/M-East/Africa +31 (0)40 267 5100 or

Fax +31 (0)40 267 5222

In Canada (800)-36-FLUKE or

Fax (905) 890-6866

From other countries +1 (425) 446-5500 or

Fax +1 (425) 446-5116

Web access: <http://www.fluke.com>

©2019 Fluke Corporation.

Specifications subject to change without notice.

Printed in U.S.A. 10/2019 6012841b-en

Modification of this document is not permitted without written permission from Fluke Corporation.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Digital Multimeters](#) category:

Click to view products by [Fluke](#) manufacturer:

Other Similar products are found below :

[6111-517](#) [FS881](#) [40705X](#) [C.A 6133 LAUNCH KIT](#) [P 1020 A](#) [P 3340](#) [SEFRAM7303](#) [BS K-CLIP](#) [19290](#) [DM285-FLEX-KIT](#) [IBT6K](#) [1000-219](#) [1001-613](#) [1006-969](#) [1008-221](#) [1012-597](#) [1013-099](#) [30XR](#) [34XR](#) [35XP](#) [TESTO 745](#) [0590 7450](#) [TESTO 760-2](#) [0590 7602](#) [TESTO 760-3](#) [0590 7603](#) [440012](#) [AX-155](#) [AX-174](#) [AX-178](#) [AX-18B](#) [AX-190A](#) [AX-503](#) [AX-507B](#) [AX-594](#) [AX-LCR42A](#) [AX-MS811](#) [AX-MS8250](#) [AX-PDM01](#) [AX-T520](#) [AX-T901](#) [AX-T903](#) [BAT-250-EUR](#) [BM525S](#) [BM805S](#) [BM807S](#) [BM817S](#) [BM827S](#) [BM829S](#) [BM857S](#) [BM859S](#) [BM867S](#) [BM907S](#)