



H
G
F
E
D
C
B
A



Recommended Mounting Hole
Applicable Panel Thickness:
Min. 0.7mm ~ Max. 3.2mm

Top Bottom
Recommended Footprint
Tolerance: ±0.05

Ordering Grid

RFPC = SMA40 = FN = 180 = X [Request Samples and Quotation](#)

Washer and nut options:
A = All Assembled with Connector (Standard)
Blank = Separately Packed

Specifications

Material
Body: Brass, Gold Plated.
Pin: Brass, Gold Plated.
Insulator: PTFE, White.
O-ring: Silicone Rubber, Red.
Washer: Brass, Gold Plated.
Nut: Brass, Gold Plated.

Electrical
Impedance: 50 Ohm
Working Frequency Range: DC - 18GHz

Mechanical & Environmental
Operating Temperature: - 55 °C to +125°C
Ingress Protection Rating: IP67
IP6x - Dust tight - no particle ingress.
IPx7 Waterproof for 30 minutes up to 1m underwater.
(Requires plug with inner gasket)
Recommended PCB Thickness: 1.60mm.
Other PCB thickness available on request

Part Number		Product Description	
RFPC-SMA40-FN		RP SMA Bulkhead Jack With O-ring, Edge Mount,	
Drawing Date		IP67, 18GHz	
18th February 2025			
By	CC	Tolerances (Except as Noted)	Units:
Detail	Drawing Release	Length	Metric (mm)
Revision	A1	Angle	± 1°
Date	14/07/25	X.X ± 0.20 X.XX ± 0.10	3rd Angle Projection
		RoHS COMPLIANT 2011/65/EU	
		This drawing is confidential and copyright of Global Connector Technology, Ltd (GCT). This drawing must not be copied or disclosed without written consent. E & OE	
		Not to Scale	
		Drawn By CC	
		Sheet No. 1/1	



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Connectors](#) / [Coaxial Connectors](#) ***category:***

Click to view products by [GCT](#) ***manufacturer:***

Other Similar products are found below :

[6002-7051-003](#) [6059674-1](#) [630059-000](#) [M55339/15-00491](#) [7002-1541-010](#) [7002-1572-002](#) [7003-1572-002](#) [7004-1512-000](#) [7009-1511-004](#)
[7105-1521-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7405-1521-005](#) [7405-1521-019](#) [7405-1521-802](#) [755-74-5](#) [7706-2](#) [873183](#)
[PL375-33](#) [95-850-148-3](#) [R107003010W](#) [R112186000](#) [R113082097](#) [R113236000](#) [R113240097](#) [R114083000](#) [R114670000W](#) [R121053000](#)
[R124072220W](#) [R124076450](#) [R124175123](#) [R125075001](#) [R125414001](#) [R125415030](#) [R125415271](#) [R141007161](#) [R141574161W](#)
[R142004000W](#) [R142076000W](#) [R142076161W](#) [R142184000W](#) [R142676700](#) [R143012000](#) [R143075000W](#) [R143089117](#) [R143235161W](#)
[R143292700](#) [R143557000](#) [R161008000](#)