

# Test Equipment

## *NEW! 5Mhz Function Generator with Frequency Counter*

### Model 4005

Engineers, Technicians, Electricians, Maintenance, Manufacturing, Quality Control & Educators can all use the 4005 in confidence with its exceptional quality, rugged design & housed in high impact case with convent multiple-position handle.



#### **Features:**

- 4 product in one low cost package
- Function generator, multiple waveforms
- Sweep generator, wide sweep range
- Pulse generator, great accuracy
- Frequency counter, 2Hz to 50MHz with auto range
- 6 digit seven segment, eye pleasing green LED display
- Display indicates, gate time, MHz, KHz, Hz, mHz

The 4005 is designed to be used, not only as a function generator, but also as a sweep generator, pulse generator and a frequency counter.

The VCF (voltage controlled frequency) produces precision sine, square and triangle waves over the 0.05Hz to 5MHz for sub-audible, audio, ultrasonic and RF applications. A continuously variable DC offset allows the output to be injected directly into circuits at the correct bias level. Variable symmetry of the output waveforms converts the instrument to a pulse generator capable of generating rectangular waves or pulses, ramp or sawtooth waves and skewed sine waves of variable duty cycle.

The sweep generator offers linear sweep with variable sweep rate and sweep width up to 100:1 frequency change. The frequency response of any active or passive device up to 5 MHz can be determined.

The new Model 4005 is a great product for use in a wide range of applications in both analog and digital electronics such as engineering, manufacturing, servicing, maintenance, education and hobbyist



# Test Equipment

## NEW! 5MHz Function Generator with Frequency Counter

### Specifications

Model 4005	
<b>OUTPUT CHARACTERISTICS</b>	
Waveforms	Sine, Square, Triangle, Skewed Sine, Pulse, Ramp Sawtooth, TTL/CMOS Leveled Square, DC
Frequency Range	0.05Hz to 5MHz in 7 Ranges (5, 50, 500, 5k, 50k, 500k, 5M)
Frequency Accuracy	± 2% 2% (5, 50, 500, 5K, 50K, 500K, 5MHz Range, Full Scale)
Output Level: Sine & Triangle wave	20 Vpp in open circuit, 10 Vpp into 50 Load
Square Wave	19 Vpp in open circuit, 9.5 Vpp into 50 Load
Output Impedance	50 ±5%
Attenuator	-20 dB fixed and continuously variable (more than -20dB)
<b>WAVEFORM CHARACTERISTICS</b>	
Sine wave -Flatness	± 3dB to 5 MHz (more than 14Vpp)
Distortion	Less than 1% at 10 Hz to 100 KHz
Square wave -Rise and Fall Time	Less than 25 nS (at 5MHz)
Triangle wave -Linearity	More than 99% at 0.5 Hz to 100 KHz
TTL Output -Rise and Fall Time	Less than 30 nS (at 1MHz)
Output Level	TTL Level (H >/_ 2.4V, L </_ 0.4V)
CMOS Output -Rise and Fall Time	Less than 180 nS (at 1MHz)
Output Level	4V to 15V ± 2V, Variable
DUTY RATIO	1:1 to 10:1
<b>SWEEP FUNCTION CHARACTERISTICS</b>	
Mode	Linear
Width	Variable from 1:1 to 100:1
Rate	0.5 Hz to 50 Hz (20 mS to 2 S)
External VCF Input	Input Voltage: 0 to 10 V
Input Impedance	Approx. 1 K



# Test Equipment

## NEW! 5Mhz Function Generator with Frequency Counter

### Specifications

Model		4005	
<b>FREQUENCY COUNTER CHARACTERISTICS</b>			
Display	6 Digit Seven Segment – Green LED, Gate time, MHz, KHz, Hz and mHz		
Frequency Range	2Hz to 50 MHz with Auto Range		
Accuracy	±Time base Error ± 1 count		
Time base	10 MHz Crystal Oscillator, ±20ppm		
Input Sensitivity	200 mVrms (2Hz ~100Hz), 100mV rms (100Hz~50MHz)		
Input Impedance	50		
Max. Input Voltage	250 Vpp		
<b>PHYSICAL CHARACTERISTICS</b>			
Dimensions WHD	3.4 x 3.5 x 10.6" (240 x 90 x 270mm)		
Weight	Approx. 5.5 lb (2.5 k)		
<b>Equipment Ratings</b>			
Plug and Socket	3 wire AC power plug and 3 wire outlet		
Power & Fuse Ratings	<u>Input Voltage:</u>	<u>Fuse</u>	<u>Power Max</u>
	103 126V AC (50/60Hz)	F 0.5A / 250V	15 W
	206 252V AC (50/60Hz)	F 0.2A / 250V	
<b>Operating Environment</b>			
Temperature	0 °C to + 40 °C (Accuracy Specified at 23°C ± 5 °C)		
Humidity	up to 85% to 40°C without temperature extremes which may cause condensation within the instrument.		
<b>Storage Environment</b>			
Temperature	-20°C to +70°C		
Humidity	below 85% RH		
Overvoltage Category	CAT II		
Insulation Category II	Portable equipment		
Pollution Degree	2		
Protection to IEC 529	Ordinary		

Note: Specifications are subject to change without notice. Please visit [www.globalspecialties.com](http://www.globalspecialties.com) for the most current product information

#### Supplied Accessories

- User's Manual ----- 1
- BNC Cable ----- 1
- Power Cord ----- 1
- Spare Fuse ----- 1



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for* [Function Generators & Synthesisers](#) *category:*

*Click to view products by* [Global Specialties](#) *manufacturer:*

Other Similar products are found below :

[3001](#) [CT3734](#) [4047B](#) [4010A](#) [SFG-210](#) [SFG-205](#) [4013B](#) [AD9166BBPZ](#) [CT3736](#) [FIT0778](#) [28II](#) [28IIEX/ETL](#) [3446GPBU](#) [EDU33211A](#)  
[EDU33212A](#) [U2010A](#) [MOKU:GO M1 \(STORM\)](#) [MOKU:GO M0 \(STORM\)](#) [MOKU:GO M2 \(STORM\)](#) [MOKU:GO M0 \(WHITE\)](#)  
[MOKU:GO M1 \(WHITE\)](#) [MOKU:GO M2 \(WHITE\)](#) [IZD0024](#) [T3AFG10](#) [T3AFG120](#) [T3AFG500](#) [T3AFG40](#) [T3AFG5](#) [T3AFG30](#) [T3AFG60](#)  
[T3AFG80](#) [W09-4A-12V](#) [33519B](#) [33512B](#) [33520B](#) [33522B](#) [AFG31051](#) [AFG31101](#) [AFG31152](#) [AFG31252](#) [CT3733](#) [33510B/903](#)  
[33511B/903](#) [33522B/903](#) [33612A](#) [4010](#) [4053](#) [4001A](#) [4003A](#) [4005DDS](#)