

SUPERCRAFT Sledge Hammers • with vibration-reducing, ergonomic and varnished Hickory handle

3366.081



Product Description

The tubular head of the SUPERCRAFT sledge hammers is filled with steel shot. The resulting effect is that the energy of the steel shot is transferred with a slight delay when the mallet's contact surface hits the workpiece. The reduced rebound allows the impact energy to be absorbed with perfect efficiency. The result is impact of exceptional magnitude. What is more, SUPERCRAFT sledge hammers allow for work with greatly improved safety, reduced strain on the joints and greater noise-dampening when compared to ordinary steel mallets.

The inserts offer outstanding impact qualities and are guaranteed to combine maximum strength with unique durability. They consist of extruded and extremely homogeneous material. Compared to injection moulded plastic inserts, they are therefore considerably more wear-resistant and durable and will never chip even in sub-zero temperatures.

The ergonomically shaped, varnished and ultra stable hickory handle is exceptionally rugged and has a vibration-dampening effect. The handle protection sleeve acts as an overstrike protector. A secure handle-head connection is ensured by an aluminium wedge and a safety pin. The wear-resistant powder coating prevents corrosion.

Handle and inserts are replaceable.

This version is available in three sizes: D80mm with a total weight of 4,410g, D100mm with a total weight of 7,050g, and D100mm with a total weight of 9,300g.

Product features:

- Non-rebound, for extra powerful strikes.
- Noise-dampening and gentle on the joints.
- Inserts made of special nylon with maximum strength.
- Vibration-dampening, ergonomically shaped, very stable and varnished hickory handle.
- Handle protection sleeve acts as an overstrike protector.
- Handle and inserts replaceable.
- Available in D80mm (total weight 4,410g), D100mm (total weight 7,050g), and D100mm (total weight 9,300g).

Application Areas

Formwork, hall construction, steel construction, exhibition stand construction, concrete formwork, scaffold construction, tent construction, fence construction, driving steel wedges, straightening work, maintenance working, changing stucked tires

Material

Inserts

- Nylon, white
- hard
- Very wear-resistant
- no chipping (even at temperatures below zero)
- noise-dampening
- very high impact

Handle

- Hickory

Order information

| Ø | Dimensions | |  [g] | GTIN | proficl@ss 5.0 | ecl@ss 10.1 | Art. No. |
|----|---|---|--|---------------|-------------------|-------------|----------|
| |  [mm] |  | | | | | |
| 80 | 200 | 880 | 4410 | 4030618301851 | AAA938c002 | 21-04-09-20 | 3366.081 |

Application example









Compliance

RoHS compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863

Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 10.06.2022

Does not contain Proposition 65 substances

No Proposition 65 substances included
<https://www.P65Warnings.ca.gov/>

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Halder manufacturer](#):

Other Similar products are found below :

[3001.030](#) [3001.040](#) [3002.030](#) [3002.050](#) [3002.060](#) [3002.080](#) [3002.081](#) [3002.082](#) [3003.030](#) [3003.050](#) [3006.030](#) [3006.040](#) [3007.030](#)
[3009.030](#) [3009.040](#) [3009.050](#) [3012.040](#) [3012.050](#) [3013.030](#) [3013.040](#) [3013.050](#) [3017.040](#) [3022.260](#) [3023.040](#) [3023.050](#) [3023.060](#)
[3023.080](#) [3027.050](#) [3027.060](#) [3027.080](#) [3027.082](#) [3028.060](#) [3028.080](#) [3089.050](#) [3107.050](#) [3113.030](#) [3117.051](#) [3202.040](#) [3202.050](#)
[3202.060](#) [3202.080](#) [3202.260](#) [3202.280](#) [3206.060](#) [3207.040](#) [3208.030](#) [3208.080](#) [3209.040](#) [3244.060](#) [3244.080](#)