

NEMA Rated Swing-Out Wall Mount Cabinet EN4DH Series

Up to 180 lbs|82 kg Weight Capacity

















Designed for housing network access equipment in harsh environments using 19" mounting rails The EN4DH Series, features dual access to both front and rear of the equipment that allows for easy install and connection between the main cable route and equipment. The UL and CSA tested NEMA ratings provide outstanding protection against dust, oil and water with both solid and window door options.

Features

- Dual access to equipment via the double hinge design.
- Allows for 120 degrees of access to both front and rear of equipment allowing for easy maintenance.
- Heavy duty wall mounting back pan can be used for cable entry and includes collar stud provision for optional inner panel.
- Back pan can be mounted with optional external mounting feet.
- Interior latch releases the center section for added security, no tools required.
- Both solid and window door options include a combination key and padlock handle for added security.
- 1 pair tapped 10-32 L rails with cable pass through are included.
 Includes starter pack (25) 10-32 screws.
- Rails are adjustable and can be installed at your desired location.
 Additional rails are available and sold separately.
- Bonding studs provided on door, body and back pan.

Standards

- Solid Door
 - UL 508A Type 1, 3, 3R, 4, 12
 - CSA Type 1, 3, 3R, 4, 12
- Plexi Viewing
 - UL 508A 1, 3, 3R, 4, 12
 - CSA Type 1, 3, 3R, 4, 12
- Complies with
 - NEMA type 3R, 4 and 12
 - IEC 60529, IP54, IP6

Specifications

- Back pan, body and doors are made from 14 gauge steel.
- Smooth continuous welded seams without knockouts, cutouts or holes.
- Seamless poured-in place gasket for added protection in both indoor and outdoor environments.
- Window door constructed with UV resistant polycarbonate material.
- Zinc-plated rack rails are drilled and tapped 10-32 to EIA 19" standards.
- 25 pack of 10-32 mounting hardware is included.
- Finished in a textured RAL7035 light gray powder paint.
- TAA compliant for GSA Schedule purchases.
- RoHS Compliant.





• Manufactured in North America.

Accessories

- Rack Panels
- Horizontal Steel Finger Cable Manager
- Universal Rack Shelf
- Rack Unit Label
- Pole Mounting Kit
- Climate Control Sizing Software
- 900-1200 BTU/H Outdoor Air Conditioner
- 10-32 Mounting Hardware

- Horizontal Hinged Cable Manager
- Horizontal Lacing Strip
- Adjustable Rack Mount DIN Rail Kit
- Mounting Foot Kit
- 17-38 CFM Filterfans
- 900-1300 BTU/H Indoor Air Conditioner
- Grounding & Bonding
- Outlet Strips



| Solid Door | Window Door | Overa | all Dimens | ions | Rack | N | lounting D | imensions | Suggested |
|---------------|----------------|--------|------------|-------|-------|--------|------------|--------------|----------------|
| Part No. | Part No. | Height | Width | Depth | Units | Height | Width | Center Depth | Load Capacity |
| EN4DH162415LG | EN4DH162415WLG | 16.00 | 24.00 | 15.01 | 7U | 12.25 | 19.00 | 9.51 | 100 lb (45 kg) |
| EN4DH162424LG | EN4DH162424WLG | 16.00 | 24.00 | 24.00 | 7U | 12.25 | 19.00 | 18.50 | 100 lb (45 kg) |
| EN4DH202424LG | EN4DH202424WLG | 20.00 | 24.00 | 24.00 | 10U | 17.50 | 19.00 | 18.50 | 100 lb (45 kg) |
| EN4DH242424LG | EN4DH242424WLG | 24.00 | 24.00 | 24.00 | 12U | 21.00 | 19.00 | 18.50 | 120 lb (54 kg) |
| EN4DH362424LG | EN4DH362424WLG | 36.00 | 24.00 | 24.00 | 19U | 33.25 | 19.00 | 18.50 | 140 lb (64 kg) |
| EN4DH482424LG | EN4DH482424WLG | 48.00 | 24.00 | 24.00 | 26U | 45.50 | 19.00 | 18.50 | 180 lb (82 kg) |

Clearance Products

| Window Door | Overall Dimensions | | Rack | Mounting Dimensions | | | Suggested | |
|----------------|--------------------|-------|-------|---------------------|--------|-------|--------------|----------------|
| Part No. | Height | Width | Depth | Units | Height | Width | Center Depth | Load Capacity |
| EN4DH242415WLG | 24.00 | 24.00 | 15.01 | 12U | 21.00 | 19.00 | 9.51 | 120 lb (54 kg) |
| EN4DH362415WLG | 36.00 | 24.00 | 15.01 | 19U | 33.25 | 19.00 | 9.51 | 140 lb (64 kg) |

Optional Rear Inner Panel

Optional Additional Pair of Panel Rails

Overall Dimensions https://www.hammfg.com/dci/products/wall-mount/en4dh 8/4/2020

NEMA Rated Swing-Out Wall Mount Cabinet (EN4DH Series) - Hammond Mfg.

| Part No. | H Overall DimensionsW | | | |
|-----------|-----------------------|-------|--|--|
| Part No. | н | W | | |
| EPGDH1624 | 12.20 | 20.20 | | |
| EPGDH2024 | 16.20 | 20.20 | | |
| EPGDH2424 | 20.20 | 20.20 | | |
| EPGDH3624 | 32.20 | 20.20 | | |
| EPGDH4824 | 44.20 | 20.20 | | |

| Part No. | Rack Units |
|----------|------------|
| EPDHR7 | 7 |
| EPDHR10 | 10 |
| EPDHR12 | 12 |
| EPDHR19 | 19 |
| EPDHR26 | 26 |

Tags: Sectional Wall Mount Rack, Pivoting Rack, Data Wall Cabinet, Dual Hinge, Hinged Swing Gate, Data subject to change without notice NEMA 4 Wall Cabinet, Dust-Tight Wall Mount, outdoor network enclosures

© 2020. Hammond Manufacturing Ltd. All rights reserved.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Electrical Enclosures category:

Click to view products by Hammond manufacturer:

Other Similar products are found below :

 120-902
 120-403
 120-475
 120-901
 127-410
 130-007
 130-504
 130-506
 MR-25L+
 30-8739
 PIP-11774SCREW
 30-9715
 MR

 25LW+
 110-407
 111-004
 111-008
 110-402
 110-901
 110-907
 111-002
 110-406
 110-910
 110-404
 110-409
 110-410
 120-405
 106-009

 106-505
 105-401
 106-006
 104-406
 137-002
 105-405
 111-005
 127-909
 106-502
 130-475
 130-503
 127-401
 106-010
 127-455
 127-475

 110-903
 R260-180-300
 9511020
 9822029
 9820014
 P61603000P
 9823009