



REV.	ECN NO OR DESCRIPTION	REVISED	DATE

技术要求:

- 1) 材质: 见附表;
- 2) 电镀: 见附表;
- 3) 塑件表面平整、光洁、无毛刺、气泡、烧焦、变形、浇口无拉伤、多料或缺料等不良现象;
- 4) 端子表面无氧化、电镀无不良现象。

适用线规: AWG#24~#20

额定电压: 250V AC/DC

额定电流: 5A

耐压: 1000V AC/minute

温度范围: -25°C~+85°C

绝缘电阻: $\geq 1000M\Omega$

接触电阻: $\leq 10M\Omega$






TABLE:

CSG PART NO.	Dimension mm		
	PIN#	A	B
WAFER-MX300WZ-22A	2*2P	3.00	9.65
WAFER-MX300WZ-23A	2*3P	6.00	12.65
WAFER-MX300WZ-24A	2*4P	9.00	15.65
WAFER-MX300WZ-25A	2*5P	12.00	18.65
WAFER-MX300WZ-26A	2*6P	15.00	21.65
WAFER-MX300WZ-27A	2*7P	18.00	24.65
WAFER-MX300WZ-28A	2*8P	21.00	27.65
WAFER-MX300WZ-29A	2*9P	24.00	30.65
WAFER-MX300WZ-210A	2*10P	27.00	33.65
WAFER-MX300WZ-211A	2*11P	30.00	36.65
WAFER-MX300WZ-212A	2*12P	33.00	39.65



P.C.B LAYOUT

注: 2*1~2*3只有一个定位柱孔, 且居中。

2	接触针	n PCS	材质: 黄铜
1	胶壳	1 PCS	材质: PA66 (UL94-V2)
NO.	NAME	QTY	DESCRIPTION

UNLESS OTHERWISE
SPECIFIED TOLERANCES

DECIMALS: ANGLES:
X :±0.35 X :±2°
X.X :±0.25 X.X :±1°
X.XX :±0.15



东莞市汉博电子科技有限公司
DONGGUAN HANBO TECHNOLOGY CO., LTD

TITLE	MX 3.0 双排带扣弯针			
DWN	xiong	PART NO.WAFER-MX300WZ-2NA		
CHKD	lee	SCALE:1:1	UNIT: mm	
APVD	wang	SIZE: A4	SHEET:10F 1	
CUSTOMER COPY				

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) ***category:***

Click to view products by [Hanbo Electronic](#) ***manufacturer:***

Other Similar products are found below :

[892-18-020-10-001101](#) [0010894062](#) [0010977306](#) [0015477636](#) [0015917161](#) [0022104068](#) [0022121042](#) [0022155065](#) [0022281023](#) [57102-F02-18ULF](#) [PCN6B-10P-2.5DS](#) [58102-G61-06LF](#) [582553-1](#) [0015911208](#) [01.001.5753.1](#) [0022285048](#) [0050291907](#) [02.125.8002.8](#)
[CSU011177004](#) [622-0430](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#)
[65817-010LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#)
[71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[803-43-024-10-001000](#)