



SPECIFICATIONS
 Current Rating: 0.75 Amps
 Withstanding Voltage: AC 500V
 Insulation Resistance: 1000MΩ Min
 Contact Resistance: 20mΩ Max
 Operation Temperature: -40° to +105°
 Insulator Material: Polyester (UL94V-0)
 Contact Material: Phosphor bronze
 Standard: PA6T
 Contact Plating: Gold Flash
 Max. Processing Temp: 240° C for 30-60 seconds
 (260° C for 5 seconds)

韩下 HANXIA 深圳市韩下电子有限公司

| No. of | DIM. A | DIM. B | No. of | DIM. A | DIM. B | No. of | DIM. A | DIM. B | No. of | DIM. A | DIM. B |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 1 | 0.00 | 1.00 | 11 | 10.00 | 11.00 | 21 | 20.00 | 21.00 | 31 | 30.00 | 31.00 |
| 2 | 1.00 | 2.00 | 12 | 11.00 | 12.00 | 22 | 21.00 | 22.00 | 32 | 31.00 | 32.00 |
| 3 | 2.00 | 3.00 | 13 | 12.00 | 13.00 | 23 | 22.00 | 23.00 | 33 | 32.00 | 33.00 |
| 4 | 3.00 | 4.00 | 14 | 13.00 | 14.00 | 24 | 23.00 | 24.00 | 34 | 33.00 | 34.00 |
| 5 | 4.00 | 5.00 | 15 | 14.00 | 15.00 | 25 | 24.00 | 25.00 | 35 | 34.00 | 35.00 |
| 6 | 5.00 | 6.00 | 16 | 15.00 | 16.00 | 26 | 25.00 | 26.00 | 36 | 35.00 | 36.00 |
| 7 | 6.00 | 7.00 | 17 | 16.00 | 17.00 | 27 | 26.00 | 27.00 | 37 | 36.00 | 37.00 |
| 8 | 7.00 | 8.00 | 18 | 17.00 | 18.00 | 28 | 27.00 | 28.00 | 38 | 37.00 | 38.00 |
| 9 | 8.00 | 9.00 | 19 | 18.00 | 19.00 | 29 | 28.00 | 29.00 | 39 | 38.00 | 39.00 |
| 10 | 9.00 | 10.00 | 20 | 19.00 | 20.00 | 30 | 29.00 | 30.00 | 40 | 39.00 | 40.00 |

UNLESS OTHERWISE SPECIFIED TOLERANCE
 X : ±0.30 X° : ±5°
 X.X : ±0.25 X.X° : ±1°
 X.XX : ±0.20 X.XX° : ±0.5°

DRAWN NAME: HX PM1.0-2x4P TP

| | | | | |
|------|----|-------|-----|------------|
| SIZE | A4 | SCALE | N:1 | PROUCT NO. |
| REV | A | UNIT | mm | PROJECT |

APPROVED: 罗小春 2020.6.24

DRAWN: 黄彬 2020.6.24

CHECKED: 张伟 2020.6.24

PAGE 1/1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [hanxia](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [0010894062](#) [0010977306](#) [0015477636](#) [0015917161](#) [0022104068](#) [0022121042](#) [0022155065](#) [0022281023](#) [57102-F02-18ULF](#) [PCN6B-10P-2.5DS](#) [58102-G61-06LF](#) [582553-1](#) [0015911208](#) [01.001.5753.1](#) [0022285048](#) [0050291907](#) [02.125.8002.8](#)
[CSU011177004](#) [622-0430](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#)
[65817-010LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#)
[71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[803-43-024-10-001000](#)