



Pushing Performance
Since 1945

UICIT_8/8_HMC_MI_CRT_009-052mm²



Image is for illustration purposes only. Please refer to product description.

Part number	09 58 016 3001
Specification	UICIT_8/8_HMC_MI_CRT_009-052mm²
HARTING eCatalogue	https://harting.com/09580163001

Identification

Category	Inserts
Series	HARTING UIC
Identification	UIC IT

Version

Termination method	Crimp termination
Gender	Male
Number of contacts	16
Details	Please order crimp contacts separately. Please order moduls separately.

Technical characteristics

Conductor cross-section (mm²)	0.08 ... 0.21 mm²
Conductor cross-section (AWG)	AWG 28 ... AWG 24
Rated current	1 A
Rated voltage	50 V
Transmission characteristics	Cat. 7 _A Class F _A up to 1,000 MHz Cat. 8 Class II up to 2000 MHz
Data rate	10 Mbit/s
	100 Mbit/s
	1 Gbit/s
	2.5 Gbit/s
	5 Gbit/s
	10 Gbit/s
	25 Gbit/s
	40 Gbit/s

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heavy Duty Power Connectors](#) ***category:***

Click to view products by [HARTING](#) ***manufacturer:***

Other Similar products are found below :

[6646137-1](#) [6646138-1](#) [6646940-1](#) [6651091-1](#) [6651525-1](#) [6651529-1](#) [73080254296](#) [73080255059](#) [7310205040001](#) [7487](#) [PS25/A0420/63](#)
[AN0024023](#) [1643543-1](#) [1791340000](#) [NLDFT-3-BL-L-S120-M40A](#) [NLDFT-N-W-L-C240-M40B](#) [NLS-2-R-C240-M40B](#) [NLS-3-BL-C240-](#)
[M40B](#) [NLS-N-W-C240-M40B](#) [NPS-3-BL-T6](#) [C148 10A005 000 9](#) [2-1589900-8](#) [9300480317](#) [19000005132](#) [AN0024202](#) [AN0264023](#) [279-](#)
[0841-10100A](#) [281-0334-00100A](#) [419-2083-301](#) [078238-1613](#) [078238-2910](#) [078239-2912](#) [078239-2910](#) [078239-2911](#) [078239-2913](#)
[09370009946](#) [09305160521](#) [09370240318](#) [1-1104457-5](#) [5352I](#) [73000005327](#) [73000005329](#) [73080956756](#) [73080965056](#) [1926075-1](#)
[6646136-1](#) [6646979-1](#) [1103021-2](#) [NPDFT-3-BL-L-T6](#) [46562-1559](#)