

ICC20 Plug



Part number	19 59 120 1010
Specification	ICC20 Plug
HARTING eCatalogue	https://b2b.harting.com/19591201010

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connectors
Series	HARTING ICC
Type of hood/housing	Cable housing

Version

Size	20
Locking type	Bayonet locking
Details	Please order backshell separately.

Technical characteristics

Limiting temperature	-40 +125 °C
Number of relockings	≥500
Degree of protection acc. to IEC 60529	IP67
	IPX9

Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Nickel plated
Material (seal)	EPDM
Colour (seal)	Black
RoHS	compliant
ELV status	compliant
China RoHS	е



Material properties

REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained

Specifications and approvals

Specifications	IEC 61984 IEC 60664-1
CE	Yes

Commercial data

Packaging size	1
Net weight	83 g
European customs tariff number	85389099
GTIN	5713140481121
eCl@ss	27440224 Shell for circular connectors

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Standard Circular Connector category:

Click to view products by HARTING manufacturer:

Other Similar products are found below:

600273N007 6134-336-13149 6134-337-11149 6134-337-2390 6134-341-17149 67-02E12-60PX 680-SMG CXS3102A181S 75-19021810P 75-474014-05S 75-474211-03P 75-474618-04P 75-474618-04S 75-474620-07P 799539-000 805-005-07NF11-19PC 805-005-07NF157PA 836783-1 866857-1 867865-1 121583-0217 RD10A16-19-P6CS051/1 RD16A14-12-S6CS051/2 1301240268 1301240275 14482
16283-18 1877910-1 206039-3 206323-1 207682-1 CA01COM-E24-28P-B-03 CA06COME14SA7P JL04-1012CK(05)-R JL04V-2A2811PE-R JL04V-2E10SL-3PE-B-R JL04V-2E20-15PE-B-R JL04V-2E20-4PE-B-R JL04V-2E24-10PE(G)-B-R JL04V-6A24-11SE-EB-R
JN1AS04MK1X JN1HS10PLKS2 JN2AS04MK2X-R JN2DS10SL3-R JN2FW15SL1 JR16PK-10S 2-206934-7 24282 25.320.3853.1 301105