

M12-CC-SCR-PUSH-IN-5P-LCOD-M-STR



Image is for illustration purposes only. Please refer to product description.

Part number	21 12 999 1510
Specification	M12-CC-SCR-PUSH-IN-5P-LCOD-M-STR
HARTING eCatalogue	https://b2b.harting.com/21129991510

Identification

Category	Connectors
Series	Circular connectors M12
Identification	Power
Element	Cable connector
Specification	Straight

Version

Termination method	Push-In
Gender	Male
Shielding	Unshielded
Number of contacts	5
Number of power contacts	4
Number of special contacts	1
Specification of special contacts	FE contact
Coding	L-coding
Locking type	Screw locking

Technical characteristics

Conductor cross-section	0.5 ... 2.5 mm ²
Rated current	16 A
Rated voltage	63 V
Rated impulse voltage	1.5 kV
Pollution degree	3



Pushing Performance
Since 1945

Technical characteristics

Overvoltage category	III
Insulation resistance	$>10^8 \Omega$
Contact resistance	$\leq 10 \text{ m}\Omega$
Tightening torque	0.6 Nm
Wrench size (knurled screw / knurled nut)	24
Limiting temperature	-40 ... +125 °C
Mating cycles	≥ 100
Degree of protection acc. to IEC 60529	IP65 mated condition
Cable diameter	6.6 ... 11.6 mm
Isolation group	I ($600 \leq \text{CTI}$)

Material properties

Material (insert)	Polyamide (PA)
Material (hood/housing)	Zinc die-cast
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained

Specifications and approvals

Specifications	IEC 61076-2-111
PROFINET	Yes

Commercial data

Packaging size	1
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140454989
ETIM	EC002635
eCl@ss	27440116 Circular connector (for field assembly)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Circular Metric Connectors](#) category:

Click to view products by [HARTING](#) manufacturer:

Other Similar products are found below :

[600X518037X](#) [6STD09SAM99B70X](#) [1-3637-600-5205](#) [1545399](#) [1R3006A20M005](#) [1R3006A20M030](#) [41-01016](#) [4-22281-1](#) [4-22284-9](#) [41-40005](#) [600X518050X](#) [SACC-DSI-FS-5P-PG9-L180 SC](#) [8R5006A16M020](#) [1406328](#) [XS2R-D426-1](#) [XS8A-0441](#) [2273142-2](#) [41-50000](#) [41-50002](#) [ASB 8-S3064/5 M](#) [43-02534](#) [MA1LKE1700](#) [1400943](#) [1201010003](#) [SACC-DSI-FS-4CON-PG9/2 0UL](#) [BEDC854NN0000052A000](#) [BKUA854NN0086155A000](#) [60.312.11](#) [1302010338](#) [BAE00010129](#) [1426186](#) [1612166](#) [1628138](#) [1597940](#) [1415374](#) [1413539](#) [1605969](#) [1416742](#) [7000-88601-0000000](#) [7000-P4421-0000000](#) [WY16K2BZM1](#) [SA1211/S2IB](#) [SA2010/P12IB](#) [SA2010/P2IS](#) [SA2010/P9IB](#) [SA2011/P2IB](#) [SA2013/S12B](#) [SA2013/S9B](#) [SA2810/P2IS](#) [SA610/S3B](#)