



Pushing Performance
Since 1945

M8-PCB-THR-2PC-2P-SPE-F-STR-SHLD



Image is for illustration purposes only. Please refer to product description.

Part number	21 82 339 2201
Specification	M8-PCB-THR-2PC-2P-SPE-F-STR-SHLD
HARTING eCatalogue	https://harting.com/21823392201

Identification

Category	Connectors
Series	HARTING T1 Industrial Circular connectors M8
Element	PCB connector

Version

Termination method	Reflow soldering termination (THR)
Gender	Female
Shielding	Fully shielded, 360° shielding contact
Number of contacts	2
further contacts	+ shielding

Technical characteristics

Rated current	4 A
Rated voltage	60 V DC
Transmission characteristics	4 GHz Bandwidth
Data rate	10 Mbit/s
	100 Mbit/s
	1 Gbit/s
	2.5 Gbit/s
	5 Gbit/s
	10 Gbit/s
Contact resistance	≤20 mΩ
Shielding resistance	≤100 mΩ
Limiting temperature	-40 ... +85 °C



Pushing Performance
Since 1945

Technical characteristics

Mating cycles	≥100
Test voltage U _{DC}	1 kV (contact-contact) 2.25 kV (contact-ground)
Moisture Sensitivity Level (MSL)	1 acc. to ECA/IPC/JEDEC J-STD-020D
Process Sensitivity Level (PSL)	R0 acc. to ECA/IPC/JEDEC J-STD-020D

Specifications and approvals

Specifications	IEC 63171-6
	IEEE 802.3bu (remote power supply over PoDL = Power over Data Line)
	IEEE 802.3cg (10BASE-T1)
	IEEE 802.3bw (100BASE-T1)
	IEEE 802.3bp (1000BASE-T1)
	IEEE 802.3ch (2.5GBASE-T1 / 5GBASE-T1 / 10GBASE-T1)

Commercial data

Packaging size	150
Net weight	6.667 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140336735
eCl@ss	27460201 PCB connector (board connector)
UNSPSC 24.0	39121415

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Circular Metric Connectors](#) category:

Click to view products by [HARTING](#) manufacturer:

Other Similar products are found below :

[600X518037X](#) [6STD09SAM99B70X](#) [1-3637-600-5205](#) [1545399](#) [1R3006A20M005](#) [1R3006A20M030](#) [41-01016](#) [4-22284-9](#) [41-40005](#)
[600X518050X](#) [SACC-DSI-FS-5P-PG9-L180 SC](#) [8R5006A16M020](#) [1406328](#) [XS2R-D426-1](#) [XS8A-0441](#) [2273142-2](#) [41-50000](#) [41-50002](#)
[ASB 8-S3064/5 M](#) [43-02534](#) [MA1LKE1700](#) [1400943](#) [1201010003](#) [SACC-DSI-FS-4CON-PG9/2 0UL](#) [BEDC854NN0000052A000](#)
[BKUA854NN0086155A000](#) [60.312.11](#) [1302010338](#) [BAE00010129](#) [1426186](#) [1612166](#) [1628138](#) [1597940](#) [1415374](#) [1413539](#) [1605969](#)
[1416742](#) [7000-88601-0000000](#) [7000-P4421-0000000](#) [WY16K2BZM1](#) [SA1211/S2IB](#) [SA2010/P12IB](#) [SA2010/P2IS](#) [SA2010/P9IB](#)
[SA2011/P2IB](#) [SA2013/S12B](#) [SA2013/S9B](#) [SA2810/P2IS](#) [SA610/S3B](#) [SA810/S8B](#)