

Specification Sheet

Part Number: 156-02462

Versatile and robust fir tree design provides low insertion effort yet delivers exceptional retention strength in an 8 mm hole and M10 threaded hole.

Wider and thinner strap design increases flexibility and minimizes pinching of bundles, hoses and tubing.

PA46 nylon material provides great performance at up to 135°F continuous operating temperature.



2-Piece Cable Tie with Fir Tree Mount, 8mm Hole and M10 Threaded Hole, PA66HIRHSUV, BK, 1200/ctn

Article Number	156-02462
----------------	-----------

Type	WSSDFTM10WSSDSET
------	------------------

Color	Black (BK)
-------	------------

Quantity Per	pack
--------------	------

Product Description	These two-piece fasteners are pre-assembled and offer a simple and versatile method of bundling and mounting cables. Sold as an unassembled set, this oval fir tree and tie combination allows the user to install the tie in two different directions, securing the bundle perpendicular or inline to the oval mounting hole.
---------------------	--

Short Description	2-Piece Cable Tie with Fir Tree Mount, 8mm Hole and M10 Threaded Hole, PA66HIRHSUV, BK, 1200/ctn
-------------------	--

Global Part Name	WSSDFTM10WSSDSET-PA66HIRHSUV-BK
------------------	---------------------------------

Minimum Tensile Strength (Imperial)	120
-------------------------------------	-----

Minimum Tensile Strength (Metric)	533
-----------------------------------	-----

Length L (Imperial)	9.1
---------------------	-----

Length L (Metric)	231.14
-------------------	--------

Fixation Method	Fir tree for round holes
-----------------	--------------------------

Identification Plate Position	none
-------------------------------	------

Releasable Closure	No
--------------------	----

Tie Closure	plastic pawl
-------------	--------------

Variant	Inside Serrated
---------	-----------------

Width W (Imperial)	0.88
--------------------	------

Width W (Metric)	22.6
------------------	------

Bundle Diameter Min (Imperial)	0.37
--------------------------------	------

Bundle Diameter Min (Metric)	9.4
------------------------------	-----

Bundle Diameter Max (Imperial)	2.25
--------------------------------	------

Bundle Diameter Max (Metric)	57.15
------------------------------	-------

Height H (Imperial)	0.98
Height H (Metric)	23.7
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.23
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.3 - 0.33
Mounting Hole Diameter D (Metric)	7.6 - 8.4 mm M10 Threaded
Mounting Hole Diameter D Min (Imperial)	0.3
Mounting Hole Diameter D Max (Imperial)	0.33
Mounting Hole Diameter D Max (Metric)	8.4
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Cable Tie Mounts](#) category:

Click to view products by [HellermannTyton](#) manufacturer:

Other Similar products are found below :

[CTB75X75BKA-C](#) [08443-0](#) [10035-0](#) [1689174-1](#) [08445-0](#) [10351-0](#) [10029-0](#) [08484-0](#) [08446-0](#) [08318-0](#) [FTH-5-DHB](#) [BMB0901](#) [BMB0902](#)
[BMB0903](#) [151-02258](#) [151-25619](#) [151-00356](#) [PKB-1/4-0](#) [61724510](#) [70362](#) [17104](#) [70431](#) [17084](#) [7TAG009820R0050](#) [61724910](#) [S4NY-140-](#)
[0-C](#) [TC1103](#) [TC223-TB](#) [TTCC-R14](#) [TTCC-S8](#) [TTCC-R5](#) [TTCC-R6](#) [TTCC-R9](#) [TTCC-R12](#) [TTCC-R4](#) [TTCC-S6](#) [TTCC-R10](#) [TTCC-S5](#)
[TTCC-S14](#) [TTCC-S7](#) [TTCC-R7](#) [TTCC-S10](#) [FTH-13R-19-M](#) [SMP18A-C](#) [150-77950](#) [156-02462](#) [156-02527](#) [SMP16A-C0](#) [06290](#) [10044](#)