




IONS	
	C
Thick	kness
	ı mm.
	111111.
0.0	1
·	
·	
6,7	
3,0	1,9
3,8	
3,2	
0.3	
9,6	
.	
8.8	
·	1,9
. 1 N76	
.	
.	
0,0	
·	
·	
6,7 .076	1,9
3,0	
3,8	
	Thick r nm. in. 18,8 22,0 26,7 33,0 13,8 33,2 30,3 39,6 18,8 22,0 26,7 30,1 33,0 133,0 133,0 133,0 133,0 133,0

Standard color black.







- for easier assembly.
- Liquid tight, dust tight, and oil tight at enclosure.
- Suitable for wet locations requiring a separate gasket between the box and fitting.
- Also suitable for other panel sealing applications.
- Easy to install since washers seal off on the perimeter, not on the connector threads.
- Special double sealing ridges compensate for minor unevenness at enclosure.

Material SBR (Styrene Butadiene)

Flammability Rating

-4°F (-20°C) to 212°F (100°C) Temperature Range

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Conduit Fittings & Accessories category:

Click to view products by Heyco manufacturer:

Other Similar products are found below:

M3231GAB M3231GAC M3231GAE M3231GL M3231GN M3231GT VC-937-16/RED VC-562-16/RED VC-1125-16/RED DM02401/2A 3408B G6002 M4340GAE C2016-P C2012-P 3407B 1660-P 561-87BG11BLK 561-75BG11B BVNV-P428 BVBV-P366 2276

2663-P 3405B C2070-P 3582V 4975 2644-P 2955 M50 2404-P 2291 2133-P 3048F VC12516 RC156-0500 DM0523-1/2A 1035A

DMS0250-1A DMS0313-1A 1040A 1050A R1/8A DMPC0490-1/2A DMPC0521-1/2A DMPC0552-1/2A 1070A R1/2A E1-7/8B 061A

R3/4A