



Recommend of PC Board Holes
Tolerance : ±0.05(Top view)

主要技术特性要求:

- 使用条件:
环境温度: -25~70°
相对湿度: 95% (40°)
- 额定负荷: DC20V 15A
- 接触电阻: ≤30mΩ 寿命测试后: ≤60mΩ
- 绝缘电阻: ≥100MΩ
- 耐压: AC500V (50Hz) 1min
- 插拔力: 3-20N 寿命测试后: 3-20N
- 寿命: 5000次
- 焊接耐热: 红外回流焊
- 包装: 盘装

				TOLERANCE UNLESS SPECIFIED							
				UP TO 5mm: ±0.1	ANGULAR	1					
				ABOVE 5mm: ±0.2	±1°	NO	DATE	REVISIONS		BY	APPD
6	中心针	BRASS	1	Au/Sn-PLATED	TITLE: DC JACK		UNIT : MM	ROHS	DWN		
5	正极针	CORSON ALLOY	1	Au-PLATED	MODEL: DC-7406-04		SCALE: 1:1	COMPLIANT	CHK'D		
4	负极长针	CORSON ALLOY	1	Au-PLATED	 DONGGUANG HAOYU ELECTRONICS CO., LTD 东莞市弘皓电子有限公司		APPD				
3	负极短针	CORSON ALLOY	1	Au-PLATED			PRO.AGL: 		REV :A0		
2	屏蔽外壳	BRASS	1	Ni-PLATED							
1	主体	PA10T	1	BLACK							
NO.	PART NAME	MATERIAL	QTY	FINISHING							

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DC Power Connectors](#) category:

Click to view products by [HOOYA](#) manufacturer:

Other Similar products are found below :

[KLDX-SMT-0202-BPTR](#) [171-0722-E](#) [K596](#) [4C6831AX](#) [10073976-112LF](#) [LCB60PW-M](#) [LCB60PB-M](#) [LCB50PW-M](#) [LCB40PW-M](#)
[LCC30PW-M](#) [LCC40PB-M](#) [LCB40PB-M](#) [LCB50PB-M](#) [DC-002-100](#) [DC-031A-130](#) [DC-031A-100](#) [DC-003A-130](#) [DC-045-130](#) [DC-192-](#)
[130](#) [DC-033-130](#) [DC-011-100](#) [DC-002F-130](#) [DC-002-130](#) [DB-14-2F](#) [DC-183B](#) [DC-060-04A](#) [DC-099-200](#) [DC-015-250-A](#) [DC-016-200-A](#)
[DC-005A-200](#) [DC-044A-200](#) [DC-088-200](#) [DC-022A-200](#) [DC-038-150](#) [DC-012A-250](#) [DC-005C-130](#) [DC-012A-200](#) [DC-098-200](#) [DC-015-](#)
[250-P](#) [DC-015-200-A](#) [DC-013-200](#) [DC550250-1047-2H](#) [DC550250-1046-2H](#) [DC511B-117L0-001-C1](#) [DC-005A-25A](#) [DT-5525008](#) [DC-](#)
[005R-8A-2.5](#) [DC-044G2.0-PU](#) [DC-019-2.0](#) [DC-033A-1.0](#)