

## Description

The HSBB3909 is the high performance complementary N-ch and P-ch MOSFETs with high cell density, which provide excellent RDSON and gate charge for most of the synchronous buck converter applications.


The HSBB3909 meet the RoHS and Green Product requirement 100% EAS guaranteed with full function reliability approved.

- 100% EAS Guaranteed
- Green Device Available
- Super Low Gate Charge
- Excellent CdV/dt effect decline
- Advanced high cell density Trench technology

## Product Summary

BVDSS	RDSON	ID
30V	20mΩ	24A
-30V	18mΩ	-27A

## PRPAK3\*3 Pin Configuration



## Absolute Maximum Ratings

Symbol	Parameter	Rating		Units
		N-Ch	P-Ch	
V <sub>DS</sub>	Drain-Source Voltage	30	-30	V
V <sub>GS</sub>	Gate-Source Voltage	±20	±20	V
I <sub>D</sub> @T <sub>C</sub> =25°C	Continuous Drain Current, V <sub>GS</sub> @ 10V <sup>1</sup>	24	-27	A
I <sub>D</sub> @T <sub>C</sub> =70°C	Continuous Drain Current, V <sub>GS</sub> @ 10V <sup>1</sup>	19	-22	A
I <sub>DM</sub>	Pulsed Drain Current <sup>2</sup>	60	-60	A
EAS	Single Pulse Avalanche Energy <sup>3</sup>	22	72	mJ
I <sub>AS</sub>	Avalanche Current	21	-38	A
P <sub>D</sub> @T <sub>C</sub> =25°C	Total Power Dissipation <sup>4</sup>	20	20	W
T <sub>STG</sub>	Storage Temperature Range	-55 to 150	-55 to 150	°C
T <sub>J</sub>	Operating Junction Temperature Range	-55 to 150	-55 to 150	°C

## Thermal Data

Symbol	Parameter	Typ.	Max.	Unit
R <sub>θJA</sub>	Thermal Resistance Junction-Ambient <sup>1</sup>	---	62.5	°C/W
R <sub>θJC</sub>	Thermal Resistance Junction-Case <sup>1</sup>	---	6	°C/W

**N-Ch and P-Ch Fast Switching MOSFETs**
**N-Channel Electrical Characteristics ( $T_J=25^{\circ}\text{C}$ , unless otherwise noted)**

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}$ , $I_{\text{D}}=250\mu\text{A}$	30	---	---	V
$\Delta \text{BV}_{\text{DSS}}/\Delta T_J$	$\text{BV}_{\text{DSS}}$ Temperature Coefficient	Reference to $25^{\circ}\text{C}$ , $I_{\text{D}}=1\text{mA}$	---	0.023	---	$\text{V}/^{\circ}\text{C}$
$R_{\text{DS}(\text{ON})}$	Static Drain-Source On-Resistance <sup>2</sup>	$V_{\text{GS}}=10\text{V}$ , $I_{\text{D}}=10\text{A}$	---	---	20	$\text{m}\Omega$
		$V_{\text{GS}}=4.5\text{V}$ , $I_{\text{D}}=5\text{A}$	---	---	30	
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	$V_{\text{GS}}=V_{\text{DS}}$ , $I_{\text{D}}=250\mu\text{A}$	1.0	---	2.5	V
$\Delta V_{\text{GS}(\text{th})}$	$V_{\text{GS}(\text{th})}$ Temperature Coefficient		---	-5.2	---	$\text{mV}/^{\circ}\text{C}$
$I_{\text{DS}(\text{SS})}$	Drain-Source Leakage Current	$V_{\text{DS}}=24\text{V}$ , $V_{\text{GS}}=0\text{V}$ , $T_J=25^{\circ}\text{C}$	---	---	1	$\text{uA}$
		$V_{\text{DS}}=24\text{V}$ , $V_{\text{GS}}=0\text{V}$ , $T_J=55^{\circ}\text{C}$	---	---	5	
$I_{\text{GSS}}$	Gate-Source Leakage Current	$V_{\text{GS}}=\pm 20\text{V}$ , $V_{\text{DS}}=0\text{V}$	---	---	$\pm 100$	nA
$g_{\text{fs}}$	Forward Transconductance	$V_{\text{DS}}=5\text{V}$ , $I_{\text{D}}=10\text{A}$	---	4.5	---	S
$R_g$	Gate Resistance	$V_{\text{DS}}=0\text{V}$ , $V_{\text{GS}}=0\text{V}$ , $f=1\text{MHz}$	---	2.5	5	$\Omega$
$Q_g$	Total Gate Charge (4.5V)	$V_{\text{DS}}=20\text{V}$ , $V_{\text{GS}}=4.5\text{V}$ , $I_{\text{D}}=10\text{A}$	---	7.2	---	$\text{nC}$
$Q_{\text{gs}}$	Gate-Source Charge		---	1.4	---	
$Q_{\text{gd}}$	Gate-Drain Charge		---	2.2	---	
$T_{\text{d}(\text{on})}$	Turn-On Delay Time	$V_{\text{DD}}=12\text{V}$ , $V_{\text{GS}}=10\text{V}$ , $R_{\text{G}}=3.3\Omega$ , $I_{\text{D}}=5\text{A}$	---	4.1	---	$\text{ns}$
$T_r$	Rise Time		---	9.8	---	
$T_{\text{d}(\text{off})}$	Turn-Off Delay Time		---	15.5	---	
$T_f$	Fall Time		---	6.0	---	
$C_{\text{iss}}$	Input Capacitance	$V_{\text{DS}}=15\text{V}$ , $V_{\text{GS}}=0\text{V}$ , $f=1\text{MHz}$	---	572	---	$\text{pF}$
$C_{\text{oss}}$	Output Capacitance		---	81	---	
$C_{\text{rss}}$	Reverse Transfer Capacitance		---	65	---	

**Diode Characteristics**

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$I_s$	Continuous Source Current <sup>1,5</sup>	$V_G=V_D=0\text{V}$ , Force Current	---	---	20	A
$I_{\text{SM}}$	Pulsed Source Current <sup>2,5</sup>		---	---	60	A
$V_{\text{SD}}$	Diode Forward Voltage <sup>2</sup>	$V_{\text{GS}}=0\text{V}$ , $I_s=1\text{A}$ , $T_J=25^{\circ}\text{C}$	---	---	1.2	V

Note :

- 1.The data tested by surface mounted on a 1 inch<sup>2</sup> FR-4 board with 2OZ copper.
- 2.The data tested by pulsed , pulse width  $\leq 300\text{us}$  , duty cycle  $\leq 2\%$
- 3.The EAS data shows Max. rating . The test condition is  $V_{\text{DD}}=25\text{V}$ , $V_{\text{GS}}=10\text{V}$ , $L=0.1\text{mH}$ , $I_{\text{AS}}=21\text{A}$
- 4.The power dissipation is limited by  $150^{\circ}\text{C}$  junction temperature
- 5.The data is theoretically the same as  $I_{\text{D}}$  and  $I_{\text{DM}}$  , in real applications , should be limited by total power dissipation.

**N-Ch and P-Ch Fast Switching MOSFETs**
**P-Channel Electrical Characteristics ( $T_J=25^{\circ}\text{C}$ , unless otherwise noted)**







Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$\text{V}_{\text{GS}}=0\text{V}$ , $\text{I}_{\text{D}}=-250\mu\text{A}$	-30	---	---	V
$\Delta \text{BV}_{\text{DSS}}/\Delta T_J$	$\text{BV}_{\text{DSS}}$ Temperature Coefficient	Reference to $25^{\circ}\text{C}$ , $\text{I}_{\text{D}}=-1\text{mA}$	---	-0.021	---	$\text{V}/^{\circ}\text{C}$
$\text{R}_{\text{DS}(\text{ON})}$	Static Drain-Source On-Resistance <sup>2</sup>	$\text{V}_{\text{GS}}=-10\text{V}$ , $\text{I}_{\text{D}}=-8\text{A}$	---	13	18	$\text{m}\Omega$
		$\text{V}_{\text{GS}}=-4.5\text{V}$ , $\text{I}_{\text{D}}=-4\text{A}$	---	19	30	
$\text{V}_{\text{GS}(\text{th})}$	Gate Threshold Voltage	$\text{V}_{\text{GS}}=\text{V}_{\text{DS}}$ , $\text{I}_{\text{D}}=-250\mu\text{A}$	-1.0	---	-2.5	V
$\Delta \text{V}_{\text{GS}(\text{th})}$	$\text{V}_{\text{GS}(\text{th})}$ Temperature Coefficient		---	-4.2	---	$\text{mV}/^{\circ}\text{C}$
$\text{I}_{\text{DSS}}$	Drain-Source Leakage Current	$\text{V}_{\text{DS}}=-24\text{V}$ , $\text{V}_{\text{GS}}=0\text{V}$ , $T_J=25^{\circ}\text{C}$	---	---	1	$\text{uA}$
		$\text{V}_{\text{DS}}=-24\text{V}$ , $\text{V}_{\text{GS}}=0\text{V}$ , $T_J=55^{\circ}\text{C}$	---	---	5	
$\text{I}_{\text{GSS}}$	Gate-Source Leakage Current	$\text{V}_{\text{GS}}=\pm 20\text{V}$ , $\text{V}_{\text{DS}}=0\text{V}$	---	---	$\pm 100$	nA
$\text{g}_{\text{fs}}$	Forward Transconductance	$\text{V}_{\text{DS}}=-5\text{V}$ , $\text{I}_{\text{D}}=-8\text{A}$	---	24	---	S
$\text{Q}_{\text{g}}$	Total Gate Charge (-4.5V)	$\text{V}_{\text{DS}}=-15\text{V}$ , $\text{V}_{\text{GS}}=-4.5\text{V}$ , $\text{I}_{\text{D}}=-8\text{A}$	---	22	---	$\text{nC}$
$\text{Q}_{\text{gs}}$	Gate-Source Charge		---	5.4	---	
$\text{Q}_{\text{gd}}$	Gate-Drain Charge		---	7	---	
$\text{T}_{\text{d}(\text{on})}$	Turn-On Delay Time	$\text{V}_{\text{DD}}=-15\text{V}$ , $\text{V}_{\text{GS}}=-10\text{V}$ , $\text{R}_G=3.3\Omega$ , $\text{I}_{\text{D}}=-1\text{A}$	---	32	---	$\text{ns}$
$\text{T}_r$	Rise Time		---	34	---	
$\text{T}_{\text{d}(\text{off})}$	Turn-Off Delay Time		---	71	---	
$\text{T}_f$	Fall Time		---	10.2	---	
$\text{C}_{\text{iss}}$	Input Capacitance	$\text{V}_{\text{DS}}=-15\text{V}$ , $\text{V}_{\text{GS}}=0\text{V}$ , $f=1\text{MHz}$	---	2213	---	$\text{pF}$
$\text{C}_{\text{oss}}$	Output Capacitance		---	311	---	
$\text{C}_{\text{rss}}$	Reverse Transfer Capacitance		---	234	---	

**Diode Characteristics**

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$\text{I}_s$	Continuous Source Current <sup>1,5</sup>	$\text{V}_{\text{G}}=\text{V}_{\text{D}}=0\text{V}$ , Force Current	---	---	-27	A
$\text{I}_{\text{SM}}$	Pulsed Source Current <sup>2,5</sup>		---	---	-60	A
$\text{V}_{\text{SD}}$	Diode Forward Voltage <sup>2</sup>	$\text{V}_{\text{GS}}=0\text{V}$ , $\text{I}_{\text{s}}=-1\text{A}$ , $T_J=25^{\circ}\text{C}$	---	---	-1.2	V

Note :

- 1.The data tested by surface mounted on a 1 inch<sup>2</sup> FR-4 board with 2OZ copper.
- 2.The data tested by pulsed , pulse width  $\leq 300\mu\text{s}$  , duty cycle  $\leq 2\%$
- 3.The EAS data shows Max. rating . The test condition is  $\text{V}_{\text{DD}}=-25\text{V}$ , $\text{V}_{\text{GS}}=-10\text{V}$ , $L=0.1\text{mH}$ , $\text{I}_{\text{AS}}=-38\text{A}$
- 4.The power dissipation is limited by  $150^{\circ}\text{C}$  junction temperature
- 5.The data is theoretically the same as  $\text{I}_{\text{D}}$  and  $\text{I}_{\text{DM}}$  , in real applications , should be limited by total power dissipation.

**N-Ch and P-Ch Fast Switching MOSFETs**
**N-Channel Typical Characteristics**

**Fig.1 Typical Output Characteristics**

**Fig.2 On-Resistance v.s Gate-Source**

**Fig.3 Forward Characteristics Of Reverse**

**Fig.4 Gate-Charge characteristics**

**Fig.5 Normalized  $V_{GS(th)}$  v.s  $T_J$** 

**Fig.6 Normalized  $R_{DS(on)}$  v.s  $T_J$**



N-Ch and P-Ch Fast Switching MOSFETs




Fig.7 Capacitance




Fig.8 Safe Operating Area




Fig.9 Normalized Maximum Transient Thermal Impedance




Fig.10 Switching Time Waveform










Fig.11 Unclamped Inductive Waveform

**N-Ch and P-Ch Fast Switching MOSFETs**
**P-Channel Typical Characteristics**

**Fig.1 Typical Output Characteristics**

**Fig.2 On-Resistance v.s Gate-Source**

**Fig.3 Forward Characteristics Of Reverse**

**Fig.4 Gate-Charge Characteristics**

**Fig.5 Normalized  $V_{GS(th)}$  v.s  $T_J$** 

**Fig.6 Normalized  $R_{DS(on)}$  v.s  $T_J$**



N-Ch and P-Ch Fast Switching MOSFETs




Fig.7 Capacitance




Fig.8 Safe Operating Area




Fig.9 Normalized Maximum Transient Thermal Impedance




Fig.10 Switching Time Waveform





Fig.11 Unclamped Inductive Waveform



## PRPAK3X3 Package Outline Dimensions



SYMBOL	DIMENSIONAL REQMTS		
	MIN	NOM	MAX
A	0.70	0.75	0.80
b	0.25	0.30	0.35
c	0.10	0.15	0.25
D	3.25	3.35	3.45
D1	3.00	3.10	3.20
D2	1.78	1.88	1.98
D3	---	0.13	---
E	3.20	3.30	3.40
E1	3.00	3.15	3.20
E2	2.39	2.49	2.59
e	0.65BSC		
H	0.30	0.39	0.50
L	0.30	0.40	0.50
L1	---	0.13	---
K	0.30	---	---
$\theta$	---	10°	12°
M	*	*	0.15
* Not specified			

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for MOSFET category:***

***Click to view products by HUASHUO manufacturer:***

Other Similar products are found below :

[IRFD120](#) [JANTX2N5237](#) [2SK2267\(Q\)](#) [BUK455-60A/B](#) [TK100A10N1,S4X\(S](#) [MIC4420CM-TR](#) [VN1206L](#) [NDP4060](#) [SI4482DY](#)  
[IRS2092STRPBF-EL](#) [IPS70R2K0CEAKMA1](#) [TK31J60W5,S1VQ\(O](#) [TK31J60W,S1VQ\(O](#) [TK16J60W,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#)  
[DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE2384](#) [DMC2700UDMQ-7](#) [DMN2080UCB4-7](#)  
[DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [DMP22D4UFO-7B](#) [IPS60R3K4CEAKMA1](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)  
[STF5N65M6](#) [IRF40H233XTMA1](#) [STU5N65M6](#) [DMN6022SSD-13](#) [DMN13M9UCA6-7](#) [DMTH10H4M6SPS-13](#) [IPS60R360PFD7SAKMA1](#)  
[DMN2990UFB-7B](#) [SSM3K35CT,L3F](#) [IPLK60R1K0PFD7ATMA1](#) [2N7002W-G](#) [MCAC30N06Y-TP](#) [IPWS65R035CFD7AXKSA1](#)  
[MCQ7328-TP](#) [SSM3J143TU,LXHF](#) [DMN12M3UCA6-7](#) [PJMF280N65E1\\_T0\\_00201](#) [PJMF380N65E1\\_T0\\_00201](#)  
[PJMF280N60E1\\_T0\\_00201](#) [PJMF600N65E1\\_T0\\_00201](#) [PJMF900N65E1\\_T0\\_00201](#)