


COAXIAL CONNECTOR, PGPBX, 50 Ohm, Straight PCB plug (male)
81_PGPBX-X50-0-W4/111_N

Properties

- Robust one-piece design
- High tolerance compensation between boards
- Excellent Radio Frequency (RF) performance
- High isolation between channels
- Customizable upon request



Product configuration

Interface type
PGPBX

Interface and material data

Piece parts	Material	Plating
Centre contact	Bronze / Brass	SUCOPRO / Gold Plating
Outer conductor	Bronze / Brass	SUCOPRO / Gold Plating
Body	Bronze / Brass	SUCOPRO / Gold Plating
Other body part	Stainless steel	Passivated (Plating)
Insulator	PTFE / LCP	

Electrical data

Impedance	50 Ω
Interface frequency	6 GHz

Electrical Data (frequency related)

Frequency range	Return loss	VSWR
0 GHz ... 4 GHz	20 dB	1.22
4 GHz ... 6 GHz	18 dB	1.28

Mechanical data

Weight	0.00146 kg
Mating cycles	100
Board mounting type	surface mount
Height above PCB HA	7.5 mm

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Connectors](#) / [Coaxial Connectors](#) ***category:***

Click to view products by [Huber & Suhner](#) ***manufacturer:***

Other Similar products are found below :

[6002-7051-003](#) [6059674-1](#) [630059-000](#) [M55339/15-00491](#) [7002-1541-010](#) [7002-1572-002](#) [7003-1572-002](#) [7004-1512-000](#) [7009-1511-004](#)
[7105-1521-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7405-1521-005](#) [7405-1521-019](#) [7405-1521-802](#) [755-74-5](#) [7706-2](#) [873183](#)
[PL375-33](#) [95-850-148-3](#) [R107003010W](#) [R112186000](#) [R113082097](#) [R113236000](#) [R113240097](#) [R114083000](#) [R114670000W](#) [R121053000](#)
[R124072220W](#) [R124076450](#) [R124175123](#) [R125075001](#) [R125414001](#) [R125415030](#) [R125415271](#) [R141007161](#) [R141574161W](#)
[R142004000W](#) [R142076000W](#) [R142076161W](#) [R142184000W](#) [R142676700](#) [R143012000](#) [R143075000W](#) [R143089117](#) [R143235161W](#)
[R143292700](#) [R143557000](#) [R161008000](#)