

Assemblies

MB12_MPMF_MPMF_O420y_xx.x_LL

MB12_MPMF_MPMF_O420y_xx.x_LL

Properties

- Floating ferrule design optimizing physical contact
- Removable housing for quick gender change and easy re-polishing
- Elliptical guide pin tip to enhance mating abilities



General data	
Assembly family	Base-12 MTP to MTP
Application Area	Indoor
Fiber quantity	12
Polarity	Methode B
Performance specification standard	IEC 61753-1 category C
Flammability rating	UL 94 V-0
Operation temperature	-10 °C ... 60 °C

Side A / Left	
Interface	connectorized
Type	Fiber Optic Connector
Connector family	MTP Pro®
Gender	Female
Performance class H+S	L
Polishing	UPC
Insertion loss max.	≤ 0.35 dB
Insertion loss typical	≤ 0.1 dB
Return loss	≥ 30 dB

Side B / Right	
Interface	connectorized
Type	Fiber Optic Connector
Connector family	MTP Pro®
Gender	Female
Performance class H+S	L
Polishing	UPC
Insertion loss max.	≤ 0.35 dB
Insertion loss typical	≤ 0.1 dB

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fibre Optic Cable Assemblies](#) ***category:***

Click to view products by [Huber & Suhner](#) ***manufacturer:***

Other Similar products are found below :

[7-21002-9](#) [1-5018030-0](#) [2061529-7](#) [5492011-9](#) [33262310050018](#) [33262310050017](#) [33262310050016](#) [54036](#) [5018030-1](#)
[FX2ERLNLNSNM0.5](#) [MIKROE-3728](#) [FA04474](#) [17-300870-23](#) [TCP-Q151B-NNE22](#) [FC0LC02](#) [FB4LC30](#) [FC0LC05](#) [FB4LC20](#) [FB2LC30](#)
[FB2LC20](#) [FB4SC30](#) [59641](#) [FB4SC20](#) [1828753-1](#) [106273-0629](#) [106283-5304](#) [111025-1210](#) [1400622](#) [5492011-4](#) [ICD040GVP163D-07](#)
[1413826](#) [1400604](#) [1400688](#) [DK-2922-01](#) [DK-2922-02](#) [DK-2933-02](#) [1657119](#) [1657122](#) [33262310050015](#) [33262310050012](#) [17-300870-01](#)
[10114734-2030LF](#) [DK-2933-03](#) [33262310050011](#) [33262310050014](#) [PCRS_LCMX_LCMX_O321T_01.0_MM](#)
[PCRS_LCMX_LCMX_O321T_03.0_MM](#) [PCRS_LCMX_LCMX_O421T_02.0_LL](#) [PCRS_LCMX_LCMX_O421T_03.0_LL](#)
[PCRS_LCMX_LCMX_O421T_05.0_LL](#)