

TECHNICAL DATA SHEET

Thermoplastic Elastomer TPE

General notes:

- » **TPE** Olefinic Thermoplastic Elastomer, Permanent Antistatic
- » Soft Plastic, was developed in order to achieve a surface resistance 10^8 - 10^9 Ohm in order to minimize the possibility of charge generation by wearing

- » **ESD Protection**



Soft plastic (TPE)



Upper side

Mechanical properties

Tensile strength
Tensile elongation
Hardness, Shore

2 MPa
10 +%
65-75 A

ISO 527 ASTM D 638
ISO 527 ASTM D 638
D-785

Polypropylen compound PP

General notes:

- » **PP** polypropylene-compound
- » Hard Plastic, its function is to ground the metal tool (through the operators hand and the ESD wrist strap)

- » **ESD Protection**



Hard plastic (PP)



Bottom side

Mechanical properties

Tensile strength at break (5mm/min)
Elongation at break (5mm/min)
Tensile modulus +23°C
Tensile strength +23°C
Izod-Impact strength (notched) +23°C

20 MPa
>10%
1650 MPa
190 MPa
13 kJ/m

ISO 527 ASTM D 638
ISO 527 ASTM D 638
ISO 527 ASTM D 638
ISO 527 ASTM D 638
ISO 179/2C

Thermal properties

Temp. of defl. under load (1.80 MPa)
VICAT softening point B (49 N)

56 °C
70 °C

ISO 75 ASTM D 648
ISO 306

Other properties

Density

0.97 g/cm³

ISO 1183

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pliers & Tweezers](#) category:

Click to view products by [Ideal-Tek](#) manufacturer:

Other Similar products are found below :

[0031](#) [32750](#) [PN-5050/38D](#) [PG-TP-30D](#) [PG-DP-18-N](#) [G77015](#) [4-1532129-2](#) [77 12 115](#) [0037](#) [T0058765801](#) [571](#) [76C](#) [37 31 125](#) [RX 8130](#)
[37 33 125](#) [DRP10N](#) [32 11 135](#) [36 12 130](#) [0036](#) [64 11 115](#) [0032](#) [T3627B 7](#) [HT-109](#) [6211-06](#) [6214-45](#) [6217-05](#) [6231-07](#) [6231-08](#) [6411-06](#)
[DP15N](#) [DP20N](#) [PN 5050/19D](#) [PNI 5000](#) [TP 5000/15D](#) [TR 20 M](#) [TR 25 15](#) [TR 25 P A](#) [TR 5000](#) [TR 5000 10 D](#) [TR 5000 PG](#) [TR 5000 PR](#)
[TR 58 R A D](#) [TR 58 R A](#) [43333](#) [102ACAX](#) [103ACA](#) [141SAP](#) [150SAD](#) [150SAMB](#) [151SA](#)