

## Product: igutek P360

### General Properties:

density:	1.24 g/cm <sup>3</sup>
colour:	light beige
saturation with moisture absorption at 23°C / 50% r. h.:	0.5 weight %
saturation with water:	2.1 weight %

### Mechanical Properties:

flexural modulus:	1300 MPa
flexural strength:	50 MPa

### Thermal Properties:

highest long term service temperature <sup>1)</sup> :	110°C
highest short term service temperature <sup>1), 2)</sup> :	130°C
lowest service temperature:	-30°C

### Electrical Properties:

surface resistivity:	>10 <sup>12</sup> Ω
----------------------	---------------------

<sup>1)</sup> relaxation possible

<sup>2)</sup> without additional load; no movement

The information on this Product Data Sheet is based on our current knowledge of the specified product. None of the information comprises one or more guarantees on certain properties.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Other Tools](#) category:*

*Click to view products by [Iigus](#) manufacturer:*

Other Similar products are found below :

[899-2-KT46](#) [568681-1](#) [5800-0090](#) [58061-1](#) [59085](#) [593033](#) [593072](#) [593564100](#) [593575](#) [593593](#) [010-0003-0000](#) [011349-000](#) [599-2021-3-NME](#) [601YSY](#) [602-JJ-03](#) [602SPB](#) [603-JJY-04](#) [CRTN1013](#) [CS16](#) [6-1579014-0](#) [6203](#) [6240-1](#) [M-5Z](#) [M6816](#) [660-29ABT1](#) [662508-1](#) [CVHD-950X-93.333](#) [671-GP-04-KT39-73207](#) [679793-1](#) [690191-1](#) [690317-2](#) [691409-4](#) [692006-2](#) [692655-7](#) [699-JJ-02](#) [MA2DPCC](#) [6TBJ05](#) [7001917104](#) [7002-5189](#) [7002-5295](#) [7002-5340](#) [7003910101](#) [7010901001](#) [7010901002](#) [D-306F](#) [70.140.2453](#) [70.353.0635.1](#) [70-399](#) [70-401](#)  
[7060](#)