


**IL2418**

# Telephone Tone Ringer with Bridge Diode

The IL2418 is a monolithic integrated circuit telephone tone ringer with bridge diode, when coupled with an appropriate transducer, it replaces the electro-mechanical bell. The device is designed for use with either a piezo transducer or an inexpensive transformer coupled speaker to produce a pleasing tone composed of a high frequency ( $f_R$ ) alternating with a low frequency ( $f_L$ ) resulting in a warble frequency. The supply voltage is obtained from the AC ring signal and the circuit is designed so that noise on the line or variation of the ringing signal can not affect correct operation of the device.


- On chip high voltage full wave diode bridge rectifier
- Low current consumption, in order to allow the parallel operation of the 4 devices
- Low external component count
- Tone and switching frequencies adjustable by external components
- High noise immunity due to built-in voltage-current hysteresis
- Activation voltage adjustable
- Internal zener diodes to protect against over voltages
- Ringer impedance adjustable with external components




### ORDERING INFORMATION

Device	Operating Temperature Range	Package	Packing
IL2418N	$T_A = -40^\circ \text{ to } 70^\circ \text{ C}$	DIP8	Tube
IL2418D		SOP8	Tube
IL2418DT		SOP8	Tape & Reel

### PIN ASSIGNMENT



### BLOCK DIAGRAM



**MAXIMUM RATINGS\*** ( $T_A = 25^\circ\text{C}$ )

Symbol	Parameter	Value	Unit
$V_{TP}$	Calling Voltage (f = 50 Hz) Continuous	120	V <sub>rms</sub>
$V_{TP}$	Calling Voltage (f = 50 Hz) 5 Sec ON/10 Sec OFF	200	V <sub>rms</sub>
$I_{CC}$	Supply Current	22	mA
Tstg	Storage and Junction Temperature	-60 to +125	°C

\* Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

**RECOMMENDED OPERATING CONDITIONS**

Symbol	Parameter	Min	Max	Unit
$V_{CC}$	Supply Voltage		26	V
$T_A$	Operating Temperature	-40	+70	°C

This device contains protection circuitry to guard against damage due to high static voltages or electric fields. However, precautions must be taken to avoid applications of any voltage higher than maximum rated voltages to this high-impedance circuit. For proper operation,  $V_{IN}$  and  $V_{OUT}$  should be constrained to the range  $GND \leq (V_{IN} \text{ or } V_{OUT}) \leq V_{CC}$ .

Unused inputs must always be tied to an appropriate logic voltage level (e.g., either GND or  $V_{CC}$ ). Unused outputs must be left open.


**ELECTRICAL CHARACTERISTICS** ( $T_A = 25^\circ\text{C}$ )

Symbol	Parameter	Test Conditions	Guaranteed Limits		Unit
			Min	Max	
$I_{CC}$	Current Consumption without Load	$V_S = 8.8 \text{ to } 26 \text{ V}$		1.8	mA
$V_{ON}$	Activation Voltage		12.2	13	V
$V_{ONR}$	Activation Voltage Range	$R_A = 1 \text{ K}\Omega$	8	10	V
$V_{SUS}$	Sustaining Voltage		8	8.8	V
$R_D$	Differential Resistance in Off Condition	$V_{TIP} = 8.0 \text{ V}$ $V_{RING} = 0 \text{ V}$	6.4	3500	K $\Omega$
$V_{OUT}$	Output Voltage Swing	$V_S = 26 \text{ V}$ , $V_{SRC} = 8.0 \text{ V}$ , $V_{OFR} = 8.0 \text{ V}$	21	25.5	V
$I_{OUT}$	Short Circuit Current	$V_S = 26 \text{ V}$	30	80	mA

**AC CHARACTERISTICS**

Symbol	Parameter	Test Conditions	Guaranteed Limits		Unit
			Min	Max	
f <sub>H1</sub> f <sub>H2</sub>	Output Frequencies	V <sub>CC</sub> = 26 V, R <sub>1</sub> = 14 KΩ	1960	2570	Hz
		V <sub>SCR</sub> = 0 V V <sub>SCR</sub> = 6 V	1420	1840	Hz
	f <sub>H</sub> Range max	V <sub>CC</sub> = 26 V, R <sub>1</sub> = 1.7 KΩ, V <sub>SCR</sub> = 0 V	14		KHz
	f <sub>H</sub> Range min	V <sub>CC</sub> = 26 V, R <sub>1</sub> = 27 KΩ, V <sub>SCR</sub> = 6.0 V		0.11	KHz
f <sub>L</sub>	Sweep Frequency	V <sub>CC</sub> = 26 V, C <sub>1</sub> = 100 nF	7.0	13.0	Hz

**TEST AND APPLICATION CIRCUIT**






**DESCRIPTION**

The IL2418 tone ringer derives its power supply by rectifying the AC ringing signal. It uses this power to activate two tone generators. The two tone frequencies generated are switched by internal oscillator in a fast sequence and made audible across an output amplifier in the loudspeaker; both tone frequencies and the switching frequency can be externally adjusted.

The device can drive either directly a piezo ceramic converter (buzzer) or small loudspeaker. In case of using a loud-speaker, a transformer is needed.

An internal shunt voltage regulator provides DC voltage to the output stage, low frequency oscillator, and high frequency oscillator. To protect the IC from telephone line transients, a zener Diode is included.

**N SUFFIX PLASTIC DIP  
(MS - 001BA)**






Symbol	Dimension, mm	
	MIN	MAX
A	8.51	10.16
B	6.10	7.11
C		5.33
D	0.36	0.56
F	1.14	1.78
G	2.54	
H	7.62	
J	0°	10°
K	2.92	3.81
L	7.62	8.26
M	0.20	0.36
N	0.38	

**NOTES:**

- Dimensions "A", "B" do not include mold flash or protrusions.  
Maximum mold flash or protrusions 0.25 mm (0.010) per side.

**D SUFFIX SOIC  
(MS - 012AA)**



Symbol	Dimension, mm	
	MIN	MAX
A	4.80	5.00
B	3.80	4.00
C	1.35	1.75
D	0.33	0.51
F	0.40	1.27
G	1.27	
H	5.72	
J	0°	8°
K	0.10	0.25
M	0.19	0.25
P	5.80	6.20
R	0.25	0.50

**NOTES:**

- Dimensions A and B do not include mold flash or protrusion.
- Maximum mold flash or protrusion 0.15 mm (0.006) per side for A; for B - 0.25 mm (0.010) per side.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Audio DSPs](#) category:*

*Click to view products by [IKSEMICON](#) manufacturer:*

Other Similar products are found below :

[E-TDA7377A](#) [TDA7716N](#) [BR281W31A101V1G](#) [LC823425-12G1-LR-H](#) [TDA7419N](#) [R3910-CFAB-E1B](#) [HMC474MP86ETR](#)  
[AMIS30660CANH6G](#) [B300W35A102XYG](#) [MAX9892ERT+T](#) [MAX9892ELTT](#) [SB3229-E1](#) [NJW1157BFC2](#) [ZL38060LDG1](#) [SB3231-E1](#)  
[HMC1022-SX](#) [SA3229-E1-T](#) [LC75056PE-H](#) [TDA7729](#) [NJW1195AV](#) [WM5102ECS/R](#) [CI1103](#) [WM5102ECS/R](#) [100-CG1820](#) [CS48L10-](#)  
[CNZ](#) [CS48L10-CNZR](#) [CS47024C-CQZ](#) [CS48L10-CWZR](#) [CS48L11-CNZ](#) [HMC618LP3ETR](#) [HMC604LP3ETR](#) [HMC5622LS7TR](#)  
[HMC288MS8ETR](#) [HMC240A](#) [STA323W13TR](#) [BU9408KS2](#) [DSPB56725AF](#) [TAS3204PAGR](#) [ADAU1467WBCPZ300](#)  
[ADAU1463WBCPZ300](#) [BD37514FS-E2](#) [ADAU1463WBCPZ150](#) [ADAU1466WBCPZ300](#) [NJM2294V-TE1](#) [LC823450TA-2H](#) [NJM2537V-](#)  
[TE1](#) [TWL1103TPBSQ1](#) [LC823450XDTBG](#) [HMC-AUH312-SX](#) [ADAV4622BSTZ](#)