

## OptiMOS™ -3 Small-Signal-Transistor

### Features


- N-channel
- Enhancement mode
- Logic level (4.5V rated)
- Avalanche rated
- Qualified according to AEC Q101
- 100%lead-free; Halogen-free; RoHS compliant



Halogen-Free

### Product Summary

$V_{DS}$	60	V
$R_{DS(on),max}$	$V_{GS}=10\text{ V}$	60
	$V_{GS}=4.5\text{ V}$	90
$I_D$	3.2	A



Type	Package	Tape and Reel Information	Marking	Halogen-free	Package
BSS606N	PG-SOT-89	H6327: 3000 pcs/ reel	KE	Yes	Non-dry

**Maximum ratings**, at  $T_j=25\text{ }^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current	$I_D$	$T_A=25\text{ }^\circ\text{C}$	3.2	A
		$T_A=70\text{ }^\circ\text{C}$	2.6	
Pulsed drain current	$I_{D,pulse}$	$T_A=25\text{ }^\circ\text{C}$	12.8	
Avalanche energy, single pulse	$E_{AS}$	$I_D=3.2\text{ A}, R_{GS}=25\text{ }\Omega$	14	mJ
Reverse diode dv/dt	dv/dt	$I_D=3.2\text{ A}, V_{DS}=48\text{ V}, di/dt=100\text{ A}/\mu\text{s}, T_{j,max}=150\text{ }^\circ\text{C}$	6	kV/ $\mu\text{s}$
Gate source voltage	$V_{GS}$		$\pm 20$	V
Power dissipation <sup>1)</sup>	$P_{tot}$	$T_A=25\text{ }^\circ\text{C}$	1.0	W
Operating and storage temperature	$T_j, T_{stg}$		-55 ... 150	$^\circ\text{C}$
ESD Class		JESD22-A114 -HBM	class 0 (< 250V)	
Soldering Temperature			260 $^\circ\text{C}$	
IEC climatic category; DIN IEC 68-1			55/150/56	

<sup>1)</sup> Value refers to minimum footprint

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

**Thermal characteristics**

Thermal resistance, junction - case	$R_{thJC}$		-	-	10	K/W
SMD version, device on PCB	$R_{thJA}$	minimal footprint	-	-	125	
		6 cm <sup>2</sup> cooling area <sup>2)</sup>	-	-	70	

**Electrical characteristics**, at  $T_j=25$  °C, unless otherwise specified

**Static characteristics**

Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS}=0$ V, $I_D=250$ µA	60	-	-	V
Gate threshold voltage	$V_{GS(th)}$	$V_{DS}=0$ V, $I_D=15$ µA	1.3	1.8	2.3	
Drain-source leakage current	$I_{DSS}$	$V_{DS}=60$ V, $V_{GS}=0$ V, $T_j=25$ °C	-	-	1	µA
		$V_{DS}=60$ V, $V_{GS}=0$ V, $T_j=150$ °C	-	-	100	
Gate-source leakage current	$I_{GSS}$	$V_{GS}=20$ V, $V_{DS}=0$ V	-	-	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	$V_{GS}=4.5$ V, $I_D=2.6$ A	-	66	90	mΩ
		$V_{GS}=10$ V, $I_D=3.2$ A	-	47	60	
Transconductance	$g_{fs}$	$ V_{DS} >2 I_D R_{DS(on)max}, I_D=2.6$ A	-	6	-	s

<sup>2)</sup> Performed on 40mmx40mmx1.5mm epoxy FR4 PCB with 6cm<sup>2</sup> (one layer, 70µm thick) copper area for drain connection. PCB is vertical without blown air.

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

**Dynamic characteristics**

Input capacitance	$C_{iss}$	$V_{GS}=0 \text{ V}, V_{DS}=25 \text{ V}, f=1 \text{ MHz}$	-	494	657	pF
Output capacitance	$C_{oss}$		-	131	174	
Reverse transfer capacitance	$C_{rss}$		-	10.2	15.3	
Turn-on delay time	$t_{d(on)}$	$V_{DD}=30 \text{ V}, V_{GS}=10 \text{ V}, I_D=3.2 \text{ A}, R_{G,ext}=6 \Omega$	-	5.6	-	ns
Rise time	$t_r$		-	2.6	-	
Turn-off delay time	$t_{d(off)}$		-	13	-	
Fall time	$t_f$		-	2.1	-	

**Gate Charge Characteristics**


Gate to source charge	$Q_{gs}$	$V_{DD}=48 \text{ V}, I_D=3.2 \text{ A}, V_{GS}=0 \text{ to } 5 \text{ V}$	-	1.6	2.1	nC
Gate to drain charge	$Q_{gd}$		-	1.0	1.4	
Gate charge total	$Q_g$		-	3.7	5.6	
Gate plateau voltage	$V_{plateau}$		-	3.2	-	V

**Reverse Diode**


Diode continuous forward current	$I_s$	$T_A=25 \text{ }^\circ\text{C}$	-	-	0.9	A
Diode pulse current	$I_{s,pulse}$		-	-	12.8	
Diode forward voltage	$V_{SD}$	$V_{GS}=0 \text{ V}, I_F=3.2 \text{ A}, T_j=25 \text{ }^\circ\text{C}$	-	0.8	1.1	V
Reverse recovery time	$t_{rr}$	$V_R=30 \text{ V}, I_F=3.2 \text{ A}, di_F/dt=100 \text{ A}/\mu\text{s}$	-	22	-	ns
Reverse recovery charge	$Q_{rr}$		-	11	-	nC

**1 Power dissipation**

$$P_{\text{tot}} = f(T_A)$$



**2 Drain current**

$$I_D = f(T_A); V_{GS} \geq 10 \text{ V}$$


**3 Safe operating area**


$$I_D = f(V_{DS}); T_A = 25 \text{ °C}; D = 0$$

parameter:  $t_p$


**4 Max. transient thermal impedance**

$$Z_{\text{thJA}} = f(t_p)$$


parameter:  $D = t_p/T$



### 5 Typ. output characteristics

$I_D=f(V_{DS})$ ;  $T_j=25\text{ }^\circ\text{C}$


parameter:  $V_{GS}$



### 6 Typ. drain-source on resistance


$R_{DS(on)}=f(I_D)$ ;  $T_j=25\text{ }^\circ\text{C}$

parameter:  $V_{GS}$




### 7 Typ. transfer characteristics


$I_D=f(V_{GS})$ ;  $|V_{DS}|>2|I_D|R_{DS(on)\max}$






### 8 Typ. forward transconductance

$g_{fs}=f(I_D)$ ;  $T_j=25\text{ }^\circ\text{C}$







**9 Drain-source on-state resistance**
 $R_{DS(on)} = f(T_j); I_D = 3.2 \text{ A}; V_{GS} = 10 \text{ V}$ 

**10 Typ. gate threshold voltage**
 $V_{GS(th)} = f(T_j); V_{DS} = V_{GS}; I_D = 15 \mu\text{A}$ 

 parameter:  $I_D$ 

**11 Typ. capacitances**
 $C = f(V_{DS}); V_{GS} = 0 \text{ V}; f = 1 \text{ MHz}; T_j = 25^{\circ}\text{C}$ 

**12 Forward characteristics of reverse diode**
 $I_F = f(V_{SD})$ 

 parameter:  $T_j$ 



**13 Avalanche characteristics**
 $I_{AV} = f(t_{AV})$ ;  $R_{GS} = 25 \Omega$ 

parameter:  $T_{j(\text{start})}$ 

**14 Typ. gate charge**
 $V_{GS} = f(Q_{\text{gate}})$ ;  $I_D = 3.2 \text{ A pulsed}$ 


parameter:  $V_{DD}$ 

**15 Drain-source breakdown voltage**
 $V_{BR(DSS)} = f(T_j)$ ;  $I_D = 250 \mu\text{A}$ 

**16 Gate charge waveforms**


### SOT-89


#### Package Outline:



#### Footprint:



#### Packaging:



Dimensions in mm

**Published by**  
**Infineon Technologies AG**  
**81726 Munich, Germany**  
**© 2009 Infineon Technologies AG**  
**All Rights Reserved.**

#### **Legal Disclaimer**

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

#### **Information**

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office ([www.infineon.com](http://www.infineon.com)).

#### **Warnings**

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.  
Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for MOSFET category:***

***Click to view products by Infineon manufacturer:***

Other Similar products are found below :

[614233C](#) [648584F](#) [IRFD120](#) [JANTX2N5237](#) [FCA20N60\\_F109](#) [FDZ595PZ](#) [2SK2545\(Q,T\)](#) [405094E](#) [423220D](#) [TPCC8103,L1Q\(CM](#)  
[MIC4420CM-TR](#) [VN1206L](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [SSM6J414TU,LF\(T](#) [751625C](#) [BUK954R8-60E](#) [GROUP A 5962-](#)  
[8877003PA](#) [NTE6400](#) [SQJ402EP-T1-GE3](#) [2SK2614\(TE16L1,Q\)](#) [2N7002KW-FAI](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [ECH8691-TL-W](#)  
[FCAB21350L1](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE221](#) [NTE222](#) [NTE2384](#) [NTE2903](#) [NTE2941](#) [NTE2945](#) [NTE2946](#) [NTE2960](#)  
[NTE2967](#) [NTE2969](#) [NTE2976](#) [NTE6400A](#) [NTE2910](#) [NTE2916](#) [NTE2956](#) [NTE2911](#) [DMN2080UCB4-7](#) [TK10A80W,S4X\(S](#)  
[SSM6P69NU,LF](#) [DMP22D4UFO-7B](#) [DMN1006UCA6-7](#)