

CoolGaN™
CoolGaN™ Transistor 100 V G3

PG-TSON-4

Features

- Ultra fast switching and high efficiency
- Space saving and highly robust package
- No reverse recovery charge
- Ultra low gate charge and output charge
- Exposed die for top-side thermal excellence
- Moisture rating MSL1
- Industrial grade 3x3 package

Potential applications

- Telecom & Datacenter 48V IBC
- Sync Rectification for AC-DC and DC-DC converters
- Robotics and drones
- Battery powered tools
- 48V servo drive
- e-Mobility, UAVs
- Class D Audio
- Solar & Energy storage systems
- Point of Load Converters



Product validation

Qualified for industrial applications according to the relevant tests of JEDEC JESD47, JESD22 and J-STD-020.

Table 1 Key performance parameters

Parameter	Value	Unit
V_{DS}	100	V
$R_{DS(on)}$	5.0	mΩ
I_D	38	A
Q_{oss}	25	nC
Q_G	6.1	nC
Q_{rr}	0	nC

Part number	Package	Marking	Related links
IGB070S10S1	PG-TSON-4	AA1	see Appendix A



Top side is exposed silicon substrate,
internally connected to source terminal.
Not recommended to use as an electrical
connection.






Table of contents

Description 1

Maximum ratings 3

Recommended operating conditions 4

Thermal characteristics 5

Electrical Characteristics 6

Electrical characteristics diagrams 8

Package outlines 13

Appendix A 16

Revision history 17

Trademarks 18

Disclaimer 18

1 Maximum ratings

at $T_j = 25\text{ °C}$, unless otherwise specified. Stresses beyond max ratings may cause permanent damage to the device. For optimum lifetime and reliability, Infineon recommends operating conditions that do not continuously exceed 80 % of the maximum ratings stated (unless otherwise explicitly stated). For further information, contact your local Infineon sales office.

Table 2 Maximum ratings

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Continuous drain-source voltage	V_{DS}	-	-	100	V	$V_{GS}=0\text{ V}$
Pulsed drain-source voltage ¹⁾	$V_{DS, pulse}$	-	-	120	V	$V_{GS}=0\text{ V}$, 1 h total time
Continuous drain current	I_D	-	-	38	A	$V_{GS}=5\text{ V}$, $T_C=25\text{ °C}$
				13		$V_{GS}=5\text{ V}$, $T_A=25\text{ °C}$, $R_{thJA}=48\text{ °C/W}$ ²⁾
Pulsed drain current ³⁾	$I_{D, pulse}$	-	-	360	A	$T_j=25\text{ °C}$
				170		$T_j=150\text{ °C}$
Pulsed gate-source voltage ¹⁾	V_{GS}	-6.5	-	6.5	V	Pulsed 100 h total time
Power dissipation	P_{tot}	-	-	23	W	$T_C=25\text{ °C}$
				2.6		$T_A=25\text{ °C}$, $R_{thJA}=48\text{ °C/W}$ ²⁾
Storage temperature	T_{stg}	-55	-	150	°C	-
Junction temperature	T_j	-40				

¹⁾ Provided as measure of robustness under abnormal operating conditions and not recommended for normal operation.

²⁾ Device on 4-layer FR4 PCB, vertical in still air.

³⁾ Pulse current limited by transfer characteristic.

2 Recommended operating conditions

Table 3 Recommended operating conditions

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Gate-source voltage	V_{GS}	-4.0	5.0	5.5	V	-

3 Thermal characteristics

Table 4 Thermal characteristics

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Thermal resistance, junction - case, top	R_{thJC}	-	1.1	1.3	°C/W	-
Thermal resistance, junction - case, bottom			3.7	5.4		
Thermal resistance, junction - ambient 1s0p	R_{thJA}	-	68	-	°C/W	On 1 layer PCB, vertical in still air.
Thermal resistance, junction - ambient 2s2p	R_{thJA}	-	48	-	°C/W	With vias on 4 layer PCB, vertical in still air.

4 Electrical Characteristics

at $T_j=25\text{ °C}$, unless otherwise specified

Table 5 Static characteristics

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Gate threshold voltage	$V_{GS(th)}$	1.2	2.1	2.9	V	$V_{DS}=V_{GS}$, $I_D=4.5\text{ mA}$
Drain-source leakage current	I_{DSS}	-	0.2	1.0	μA	$V_{DS}=100\text{ V}$, $V_{GS}=0\text{ V}$, $T_j=25\text{ °C}$
			3.0	25		$V_{DS}=100\text{ V}$, $V_{GS}=0\text{ V}$, $T_j=125\text{ °C}$
Gate-source leakage current	I_{GSS}	-	11	140	μA	$V_{GS}=5\text{ V}$, $T_j=25\text{ °C}$
			0.01	0.1		$V_{GS}=-4\text{ V}$, $T_j=25\text{ °C}$
			70	640		$V_{GS}=5\text{ V}$, $T_j=125\text{ °C}$
			0.01	0.1		$V_{GS}=-4\text{ V}$, $T_j=125\text{ °C}$
Drain-source on-state resistance	$R_{DS(on)}$	-	5.0	7.0	m Ω	$V_{GS}=5\text{ V}$, $I_D=13\text{ A}$
Gate resistance ⁴⁾	R_G	-	0.5	-	Ω	-

⁴⁾ Defined by design. Not subject to production test.

Table 6 Capacitance characteristics ⁵⁾

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Input capacitance	C_{iss}	-	650	740	pF	$V_{GS}=0\text{ V}$, $V_{DS}=50\text{ V}$, $f=1\text{ MHz}$
Output capacitance	C_{oss}		310	340		
Reverse transfer capacitance	C_{rss}		3.6	4.7		

⁵⁾ Defined by design. Not subject to production test.

Table 7 Gate charge characteristics

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Gate to source charge	Q_{gs}	-	1.8	-	nC	$V_{DS}=50\text{ V}$, $I_D=13\text{ A}$, $V_{GS}=0\text{ to }5\text{ V}$
Gate charge at threshold	$Q_{g(th)}$		1.3	-	nC	
Gate to drain charge ⁶⁾	Q_{gd}		1.7	-	nC	
Switching charge	Q_{sw}		2.2	-	nC	
Gate charge total ⁶⁾	Q_g		6.1	7.9	nC	
Gate plateau voltage	$V_{plateau}$		2.8	-	V	
Output charge ⁶⁾	Q_{oss}	-	25	28	nC	$V_{DS}=50\text{ V}$, $V_{GS}=0\text{ V}$

⁶⁾ Defined by design. Not subject to production test.

Table 8 Reverse operation

Parameter	Symbol	Values			Unit	Note / Test condition
		Min.	Typ.	Max.		
Reverse continuous current	I_S	-	-	7.4	A	$T_C=25\text{ °C}$
Pulsed current, reverse	$I_{S,pulse}$			152		
Source-Drain reverse voltage	V_{SD}	-	2.7	3.5	V	$V_{GS}=0\text{ V}, I_{S,pulse}=13\text{ A}, T_j=25\text{ °C}$
			2.3	-		$V_{GS}=0\text{ V}, I_{S,pulse}=0.5\text{ A}, T_j=25\text{ °C}$
Reverse recovery charge ⁷⁾	Q_{rr}	-	0	-	nC	$V_R=50\text{ V}, I_{S,pulse}=13\text{ A}, di_{S,pulse}/dt=100\text{ A}/\mu\text{s}$

⁷⁾ Defined by design. Not subject to production test.

5 Electrical characteristics diagrams







Diagram 5: Typ. output characteristics




$I_D = f(V_{DS})$; $T_j = 25\text{ °C}$; parameter: V_{GS}

Diagram 6: Typ. transfer characteristics




$I_D = f(V_{GS})$; $|V_{DS}| > 2|I_D|R_{DS(on)max}$; parameter: T_j

Diagram 7: Typ. channel reverse characteristics



$I_S = f(V_{SD})$; $T_j = 25\text{ °C}$; parameter: V_{GS}

Diagram 8: Typ. channel reverse characteristics



$I_S = f(V_{SD})$; $T_j = 125\text{ °C}$; parameter: V_{GS}







Diagram 13: Typ. capacitances




$$C=f(V_{DS}); V_{GS}=0\text{ V}$$

Diagram 14 Typ. gate charge




$$V_{GS}=f(Q_{gate}); I_D=13\text{ A pulsed; parameter: }V_{DS}$$

Diagram 15: Typ. output charge




$$Q_{oss}=f(V_{DS}), V_{GS}=0\text{ V}$$

Diagram 16: Typ. Coss stored Energy




$$E_{oss}=f(V_{DS}), V_{GS}=0\text{ V}$$

Diagram 17: Typ. gate characteristics forward




6 Package outlines



PACKAGE - GROUP NUMBER: PG-TSON-4-U02		
DIMENSIONS	MILLIMETERS	
	MIN.	MAX.
A	0.832	1.032
A1	---	0.05
b	0.20	0.40
b1	0.625	0.825
b2	1.725	1.925
c	0.20	
c1	0.192	
c2	0.192	
D	3.00	
D1	2.62	
E	3.00	
E1	2.62	
E2	0.825	
L	0.20	0.30
L1	0.25	0.35
L2	0.20	0.30
e	1.10	
e1	0.55	


NOTE: DIMENSIONS DO NOT INCLUDE MOLD FLASH, PROTRUSION OR GATE BURRS

Figure 1 Outline PG-TSON-4, dimensions in mm



All dimensions are in units mm
All pads are solder mask defined

Figure 2 Footprint drawing PG-TSON-4, dimensions in mm



All dimensions are in units mm
 The drawing is in compliance with ISO 128-30, Projection Method 1 []

Figure 3 Packaging variant PG-TSON-4, dimensions in mm

7 Appendix A

Table 9 **Related links**

- [IFX CoolGaN™ GaN webpage](#)
- [IFX CoolGaN™ reliability white paper](#)
- [IFX CoolGaN™ gate driver application note](#)
- [IFX CoolGaN™ Evaluation Boards](#)
- [IFX Packages Description-PG-TSON-4-3](#)

Revision history

IGB070S10S1

Revision 2025-04-22, Rev. 1.1

Previous revisions

Revision	Date	Subjects (major changes since last revision)
1.0	2025-01-27	Release of final version
1.1	2025-04-22	Updated static IGSS characteristics

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [GaN FETs](#) category:

Click to view products by [Infineon](#) manufacturer:

Other Similar products are found below :

[CID10N65D](#) [CID18N65D](#) [CID45N65MD](#) [CID10N65E3](#) [EPC8010](#) [EPC8009](#) [EPC8004](#) [EPC2014C](#) [CLP24H4S30PXY](#) [CCSPG1510N TR](#)
[PBFREE](#) [CCSPG1560N TR PBFREE](#) [CDF56G7032N TR13 PBFREE](#) [CDFG6558N TR13 PBFREE](#) [GRF0010](#) [GRF0020](#)
[IGB070S10S1XTMA1](#) [IGB110S101XTMA1](#) [IGB110S10S1XTMA1](#) [IGC019S06S1XTMA1](#) [IGC025S08S1XTMA1](#) [IGC033S101XTMA1](#)
[IGC033S10S1XTMA1](#) [IGC037S12S1XTMA1](#) [IGD70R140D2SAUMA1](#) [IGD70R200D2SAUMA1](#) [IGD70R270D2SAUMA1](#)
[IGD70R500D2SAUMA1](#) [IGI65D1414A3MSXUMA1](#) [IGL65R055D2XUMA1](#) [IGL65R080D2XUMA1](#) [IGL65R110D2XUMA1](#)
[IGL65R140D2XUMA1](#) [IGLD65R055D2AUMA1](#) [IGLD65R080D2AUMA1](#) [IGLD65R110D2AUMA1](#) [IGLD65R140D2AUMA1](#)
[IGLR65R140D2XUMA1](#) [IGLR65R200D2XUMA1](#) [IGLR65R270D2XUMA1](#) [IGLR70R140D2SXUMA1](#) [IGLR70R200D2SXUMA1](#)
[IGLR70R270D2SXUMA1](#) [IGLT65R035D2ATMA1](#) [IGLT65R045D2ATMA1](#) [IGLT65R110D2ATMA1](#) [IGOT65R025D2AUMA1](#)
[IGOT65R035D2AUMA1](#) [IGOT65R045D2AUMA1](#) [IGOT65R055D2AUMA1](#) [IGT65R025D2ATMA1](#)