

## SiC MOSFET

### CoolSiC™ MOSFET 650 V G2

Built on Infineon's robust 2<sup>nd</sup> generation Silicon Carbide trench technology, the 650 V CoolSiC™ MOSFET delivers unparalleled performance, superior reliability, and great ease of use. It enables cost effective, highly efficient, and simplified designs to fulfill the ever-growing system and market needs.

### Features

- Ultra-low switching losses
- Benchmark gate threshold voltage,  $V_{GS(th)} = 4.5\text{ V}$
- Robust against parasitic turn-on even with 0 V turn-off gate voltage
- Flexible driving voltage and compatible with bipolar driving scheme
- Robust body diode operation under hard commutation events
- .XT interconnection technology for best-in-class thermal performance

### Benefits

- Enables high efficiency and high power density designs
- Facilitates great ease of use and integration
- Provides the best price performance ratio compared to Industry's most ambitious roadmaps
- Reduces the size, weight and bill of materials of the systems
- Enhances system robustness and reliability

### Potential applications

- SMPS
- Solar PV inverters
- Energy storage and battery formation
- UPS
- EV charging infrastructure
- Motor drives

### Product validation




Fully qualified according to JEDEC for Industrial Applications

*Please note: The source and driver source pins are not exchangeable. Their exchange might lead to malfunction.*

**Table 1 Key Performance Parameters**

Parameter	Value	Unit
$V_{DSS}$ over full $T_{j,range}$	650	V
$R_{DS(on),typ}$	26	mΩ
$R_{DS(on),max}$	33	mΩ
$Q_{G,typ}$	42	nC
$I_{D,pulse}$	216	A
$Q_{oss} @ 400\text{ V}$	80	nC
$E_{oss} @ 400\text{ V}$	10.8	μJ

Type/Ordering Code	Package	Marking	Related Links
IMLT65R026M2H	PG-HDSOP-16	65R026M2	see Appendix A



## Table of Contents

Description .....	1
Maximum ratings .....	3
Thermal characteristics .....	4
Operating range .....	5
Electrical characteristics .....	6
Electrical characteristics diagrams .....	9
Test Circuits .....	14
Package Outlines .....	15
Appendix A .....	18
Revision History .....	19
Trademarks .....	19
Disclaimer .....	19

## 1 Maximum ratings

at  $T_j = 25^\circ\text{C}$ , unless otherwise specified.

Note: for optimum lifetime and reliability, Infineon recommends operating conditions that do not exceed 80% of the maximum ratings stated in this datasheet.

**Table 2 Maximum ratings**

Parameter	Symbol	Values			Unit	Note/ Test Condition
		Min.	Typ.	Max.		
Continuous DC drain current <sup>1)</sup>	$I_{\text{DDC}}$	-	-	82 57	A	$T_c = 25^\circ\text{C}$ $T_c = 100^\circ\text{C}$
Peak drain current <sup>2)</sup>	$I_{\text{DM}}$	-	-	216	A	$T_c = 25^\circ\text{C}$ , $V_{\text{GS}} = 18\text{ V}$
Avalanche energy, single pulse	$E_{\text{AS}}$	-	-	200	mJ	$I_{\text{D}} = 7.5\text{ A}$ , $V_{\text{DD}} = 50\text{ V}$ ; see table 11
Avalanche energy, repetitive	$E_{\text{AR}}$	-	-	1.00	mJ	$I_{\text{D}} = 7.5\text{ A}$ , $V_{\text{DD}} = 50\text{ V}$ ; see table 11
Avalanche current, single pulse	$I_{\text{AS}}$	-	-	7.5	A	-
MOSFET $dv/dt$ ruggedness	$dv/dt$	-	-	200	V/ns	$V_{\text{DS}} = 0 \dots 400\text{ V}$
Gate source voltage (static) <sup>3)</sup>	$V_{\text{GS}}$	-7	-	23	V	-
Gate source voltage (transient)	$V_{\text{GS}}$	-10	-	25	V	$t_p \leq 500\text{ ns}$ , duty cycle $\leq 1\%$
Power dissipation	$P_{\text{tot}}$	-	-	365	W	$T_c = 25^\circ\text{C}$
Storage temperature	$T_{\text{stg}}$	-55	-	150	$^\circ\text{C}$	-
Operating junction temperature	$T_j$	-55	-	175	$^\circ\text{C}$	-
Mounting torque	-	-	-	-	Ncm	-
Continuous reverse drain current <sup>1)</sup>	$I_{\text{SDC}}$	-	-	82 54	A	$V_{\text{GS}} = 18\text{ V}$ , $T_c = 25^\circ\text{C}$ $V_{\text{GS}} = 0\text{ V}$ , $T_c = 25^\circ\text{C}$
Peak reverse drain current <sup>2)</sup>	$I_{\text{SM}}$	-	-	216 65	A	$T_c = 25^\circ\text{C}$ , $t_p \leq 250\text{ ns}$ $T_c = 25^\circ\text{C}$
Insulation withstand voltage	$V_{\text{ISO}}$	-	-	n.a.	V	$V_{\text{rms}}$ , $T_c = 25^\circ\text{C}$ , $t = 1\text{ min}$

1) Limited by  $T_{j,\text{max}}$ .

2) Pulse width  $t_{\text{pulse}}$  limited by  $T_{j,\text{max}}$ .

3) The maximum gate-source voltage in the application design should be in accordance to IPC-9592B.

## 2 Thermal characteristics

**Table 3 Thermal characteristics**

Parameter	Symbol	Values			Unit	Note/ Test Condition
		Min.	Typ.	Max.		
Thermal resistance, junction - case	$R_{th(j-c)}$	-	-	0.41	°C/W	Not subject to production test. Parameter verified by design/characterization according to JESD51-14.
Soldering temperature, reflow soldering allowed	$T_{sold}$	-	-	260	°C	reflow MSL1

### 3 Operating range

Table 4 Operating range

Parameter	Symbol	Values			Unit	Note/ Test Condition
		Min.	Typ.	Max.		
Recommended turn-on voltage	$V_{GS(on)}$	-	18	-	V	-
Recommended turn-off voltage	$V_{GS(off)}$	-	0	-	V	-

## 4 Electrical characteristics

at  $T_j = 25^\circ\text{C}$ , unless otherwise specified

**Table 5 Static characteristics**

Parameter	Symbol	Values			Unit	Note/ Test Condition
		Min.	Typ.	Max.		
Drain-source voltage	$V_{\text{DSS}}$	650	-	-	V	$V_{\text{GS}} = 0\text{ V}$ , $I_{\text{D}} = 0.7\text{ mA}$
Gate threshold voltage <sup>4)</sup>	$V_{\text{GS(th)}}$	3.5	4.5	5.6	V	$V_{\text{DS}} = V_{\text{GS}}$ , $I_{\text{D}} = 7\text{ mA}$
Zero gate voltage drain current	$I_{\text{DSS}}$	-	1 3	75 -	$\mu\text{A}$	$V_{\text{DS}} = 650\text{ V}$ , $V_{\text{GS}} = 0\text{ V}$ , $T_j = 25^\circ\text{C}$ $V_{\text{DS}} = 650\text{ V}$ , $V_{\text{GS}} = 0\text{ V}$ , $T_j = 175^\circ\text{C}$
Gate-source leakage current	$I_{\text{GSS}}$	-	-	100	nA	$V_{\text{GS}} = 20\text{ V}$ , $V_{\text{DS}} = 0\text{ V}$
Drain-source on-state resistance	$R_{\text{DS(on)}}$	-	34 26 24 43	- 33 - -	m $\Omega$	$V_{\text{GS}} = 15\text{ V}$ , $I_{\text{D}} = 34.5\text{ A}$ , $T_j = 25^\circ\text{C}$ $V_{\text{GS}} = 18\text{ V}$ , $I_{\text{D}} = 34.5\text{ A}$ , $T_j = 25^\circ\text{C}$ $V_{\text{GS}} = 20\text{ V}$ , $I_{\text{D}} = 34.5\text{ A}$ , $T_j = 25^\circ\text{C}$ $V_{\text{GS}} = 18\text{ V}$ , $I_{\text{D}} = 34.5\text{ A}$ , $T_j = 175^\circ\text{C}$
Internal gate resistance	$R_{\text{G,int}}$	-	2.9	-	$\Omega$	$f = 1\text{ MHz}$

<sup>4)</sup> Tested after 1 ms pulse at  $V_{\text{GS}} = +20\text{ V}$ . "Linear mode" operation is not recommended. For assessment of potential "linear mode" operation, please contact Infineon sales office.

**Table 6 Dynamic characteristics**

External parasitic elements (PCB layout) influence switching behavior significantly.

Stray inductances and coupling capacitances must be minimized.

For layout recommendations please use provided application notes or contact Infineon sales office.

Parameter	Symbol	Values			Unit	Note/ Test Condition
		Min.	Typ.	Max.		
Input capacitance	$C_{\text{iss}}$	-	1499	-	pF	$V_{\text{GS}} = 0\text{ V}$ , $V_{\text{DS}} = 400\text{ V}$ , $f = 250\text{ kHz}$
Reverse transfer capacitance	$C_{\text{rss}}$	-	8.6	-	pF	$V_{\text{GS}} = 0\text{ V}$ , $V_{\text{DS}} = 400\text{ V}$ , $f = 250\text{ kHz}$
Output capacitance <sup>5)</sup>	$C_{\text{oss}}$	-	111	145	pF	$V_{\text{GS}} = 0\text{ V}$ , $V_{\text{DS}} = 400\text{ V}$ , $f = 250\text{ kHz}$
Output charge <sup>5)</sup>	$Q_{\text{oss}}$	-	80	103	nC	calculation based on $C_{\text{oss}}$
Effective output capacitance, energy related <sup>6)</sup>	$C_{\text{o(er)}}$	-	135	-	pF	$V_{\text{GS}} = 0\text{ V}$ , $V_{\text{DS}} = 0 \dots 400\text{ V}$
Effective output capacitance, time related <sup>7)</sup>	$C_{\text{o(tr)}}$	-	199	-	pF	$I_{\text{D}} = \text{constant}$ , $V_{\text{GS}} = 0\text{ V}$ , $V_{\text{DS}} = 0 \dots 400\text{ V}$
Turn-on delay time	$t_{\text{d(on)}}$	-	9.3	-	ns	$V_{\text{DD}} = 400\text{ V}$ , $V_{\text{GS}} = 0/18\text{ V}$ , $I_{\text{D}} = 34.5\text{ A}$ , $R_{\text{G,ext}} = 1.8\ \Omega$ ; see table 10
Rise time	$t_{\text{r}}$	-	10.1	-	ns	$V_{\text{DD}} = 400\text{ V}$ , $V_{\text{GS}} = 0/18\text{ V}$ , $I_{\text{D}} = 34.5\text{ A}$ , $R_{\text{G,ext}} = 1.8\ \Omega$ ; see table 10

**Table 6 Dynamic characteristics**

External parasitic elements (PCB layout) influence switching behavior significantly.  
Stray inductances and coupling capacitances must be minimized.  
For layout recommendations please use provided application notes or contact Infineon sales office.

Parameter	Symbol	Values			Unit	Note/ Test Condition
		Min.	Typ.	Max.		
Turn-off delay time	$t_{d(off)}$	-	16	-	ns	$V_{DD} = 400\text{ V}$ , $V_{GS} = 0/18\text{ V}$ , $I_D = 34.5\text{ A}$ , $R_{G,ext} = 1.8\ \Omega$ ; see table 10
Fall time	$t_f$	-	5.1	-	ns	$V_{DD} = 400\text{ V}$ , $V_{GS} = 0/18\text{ V}$ , $I_D = 34.5\text{ A}$ , $R_{G,ext} = 1.8\ \Omega$ ; see table 10
Turn-ON switching losses <sup>8)</sup>	$E_{on}$	-	43	-	$\mu\text{J}$	$V_{DD} = 400\text{ V}$ , $V_{GS} = 0/18\text{ V}$ , $I_D = 34.5\text{ A}$ , $R_{G,ext} = 1.8\ \Omega$
Turn-OFF switching losses <sup>8)</sup>	$E_{off}$	-	33	-	$\mu\text{J}$	$V_{DD} = 400\text{ V}$ , $V_{GS} = 0/18\text{ V}$ , $I_D = 34.5\text{ A}$ , $R_{G,ext} = 1.8\ \Omega$
Total switching losses <sup>8)</sup>	$E_{tot}$	-	76	-	$\mu\text{J}$	$V_{DD} = 400\text{ V}$ , $V_{GS} = 0/18\text{ V}$ , $I_D = 34.5\text{ A}$ , $R_{G,ext} = 1.8\ \Omega$

<sup>5)</sup> Maximum specification is defined by calculated six sigma upper confidence bound

<sup>6)</sup>  $C_{o(er)}$  is a fixed capacitance that gives the same stored energy as  $C_{oss}$  while  $V_{DS}$  is rising from 0 to 400 V.

<sup>7)</sup>  $C_{o(tr)}$  is a fixed capacitance that gives the same charging time as  $C_{oss}$  while  $V_{DS}$  is rising from 0 to 400 V.

<sup>8)</sup> Values for 4-pin configuration based on TO-263-7 measurements; MOSFET used in half-bridge configuration without external diode

**Table 7 Gate charge characteristics**

Parameter	Symbol	Values			Unit	Note/ Test Condition
		Min.	Typ.	Max.		
Plateau gate to source charge	$Q_{GS(pl)}$	-	11.0	-	nC	$V_{DD} = 400\text{ V}$ , $I_D = 34.5\text{ A}$ , $V_{GS} = 0\text{ to }18\text{ V}$
Gate to drain charge	$Q_{GD}$	-	7.9	-	nC	$V_{DD} = 400\text{ V}$ , $I_D = 34.5\text{ A}$ , $V_{GS} = 0\text{ to }18\text{ V}$
Total gate charge	$Q_G$	-	42	-	nC	$V_{DD} = 400\text{ V}$ , $I_D = 34.5\text{ A}$ , $V_{GS} = 0\text{ to }18\text{ V}$

**Table 8 Reverse diode characteristics**

Parameter	Symbol	Values			Unit	Note/ Test Condition
		Min.	Typ.	Max.		
Drain-source reverse voltage	$V_{SD}$	-	4.3	-	V	$V_{GS} = 0\text{ V}$ , $I_S = 34.5\text{ A}$ , $T_j = 25^\circ\text{C}$
MOSFET forward recovery time	$t_{fr}$	-	16 10.7	-	ns	$V_{DD} = 400\text{ V}$ , $I_S = 34.5\text{ A}$ , $di_S/dt = 1000\text{ A}/\mu\text{s}$ ; see table 9 $V_{DD} = 400\text{ V}$ , $I_S = 34.5\text{ A}$ , $di_S/dt = 4000\text{ A}/\mu\text{s}$ ; see table 9

**Table 8 Reverse diode characteristics**

Parameter	Symbol	Values			Unit	Note/ Test Condition
		Min.	Typ.	Max.		
MOSFET forward recovery charge <sup>9)</sup>	$Q_{fr}$	-	83 131	-	nC	$V_{DD} = 400\text{ V}$ , $I_S = 34.5\text{ A}$ , $di_S/dt = 1000\text{ A}/\mu\text{s}$ ; see table 9 $V_{DD} = 400\text{ V}$ , $I_S = 34.5\text{ A}$ , $di_S/dt = 4000\text{ A}/\mu\text{s}$ ; see table 9
MOSFET peak forward recovery current	$I_{frm}$	-	10.6 25	-	A	$V_{DD} = 400\text{ V}$ , $I_S = 34.5\text{ A}$ , $di_S/dt = 1000\text{ A}/\mu\text{s}$ ; see table 9 $V_{DD} = 400\text{ V}$ , $I_S = 34.5\text{ A}$ , $di_S/dt = 4000\text{ A}/\mu\text{s}$ ; see table 9

<sup>9)</sup>  $Q_{fr}$  includes  $Q_{oss}$

## 5 Electrical characteristics diagrams







Diagram 5: Typ. output characteristics




$I_D = f(V_{DS}); T_j = 25\text{ °C};$  parameter:  $V_{GS}$

Diagram 6: Typ. output characteristics




$I_D = f(V_{DS}); T_j = 175\text{ °C};$  parameter:  $V_{GS}$

Diagram 7: Typ. drain-source on-state resistance




$R_{DS(on)} = f(I_{DS}); T_j = 125\text{ °C};$  parameter:  $V_{GS}$

Diagram 8: Drain-source on-state resistance




$R_{DS(on)} = f(T_j); I_D = 34.5\text{ A}; V_{GS} = 18\text{ V}$

Diagram 9: Typ. transfer characteristics




$I_D=f(V_{GS}); V_{DS}=20V$ ; parameter:  $T_j$

Diagram 10: Typ. gate charge




$V_{GS}=f(Q_{gate}); I_D=35 A$  pulsed; parameter:  $V_{DD}$

Diagram 11: Typ. reverse characteristics




$I_{SD}=f(V_{SD}); V_{GS}=0 V$ ; parameter:  $T_j$

Diagram 12: Typ. reverse characteristics




$I_{SD}=f(V_{SD}); V_{GS}=18 V$ ; parameter:  $T_j$

Diagram 13: Avalanche energy




$E_{AS}=f(T_j); I_D=7.5\text{ A}; V_{DD}=50\text{ V}$

Diagram 14: Drain-source breakdown voltage




$V_{(BR)DSS}=f(T_j); I_D=0.7\text{ mA}$

Diagram 15: Typ. capacitances




$C=f(V_{DS}); V_{GS}=0\text{ V}; f=250\text{ kHz}$

Diagram 16: Typ. Coss stored energy




$E_{oss}=f(V_{DS})$

Diagram 17: Typ. Qoss output charge




$Q_{oss}=f(V_{DS})$

Diagram 18: Typ. Switching Losses vs R<sub>G,ext</sub>



$E=f(R_{G,ext}); V_{DD}=400\text{ V}; V_{GS}=0-18\text{ V}; I_D=34.5\text{ A}$


Diagram 19: Typ. Switching Losses vs switching current




$E=f(I_D); V_{DD}=400\text{ V}; V_{GS}=0-18\text{ V}; R_{G,ext}=1.8\ \Omega$

## 6 Test Circuits


**Table 9 Body diode characteristics (CoolSiC)**



**Table 10 Switching times (CoolSiC)**



**Table 11 Unclamped inductive load**



## 7 Package Outlines






Figure 1 Outline PG-HDSOP-16, dimensions in mm



**Figure 2 Footprint Drawing PG-HDSOP-16, dimensions in mm**



All dimensions are in units mm

The drawing is in compliance with ISO 128-30, Projection Method 1 [ ]

**Figure 3** Packaging Variant PG-HDSOP-16, dimensions in mm

## 8 Appendix A

Table 12 Related Links

- [IFX CoolSiC CoolSiC™ MOSFET 650V G2 Webpage](#)
- [IFX CoolSiC CoolSiC™ MOSFET 650V G2 Application Note](#)
- [IFX CoolSiC CoolSiC™ MOSFET 650V G2 Simulation Model](#)
- [IFX Design tools](#)

## Revision History

IMLT65R026M2H

### Revision 2024-09-06, Rev. 2.0

Previous Revision

Revision	Date	Subjects (major changes since last revision)
2.0	2024-09-06	Release of final

#### Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

**We Listen to Your Comments** Any information within this document that you feel is wrong, unclear or missing at all? Your feedback will help us to continuously improve the quality of this document. Please send your proposal (including a reference to this document) to: [erratum@infineon.com](mailto:erratum@infineon.com)

#### Published by

Infineon Technologies AG  
81726 München, Germany  
© 2024 Infineon Technologies AG  
All Rights Reserved.

#### Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie"). With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

#### Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office ([www.infineon.com](http://www.infineon.com)).

#### Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.

The Infineon Technologies component described in this Data Sheet may be used in life-support devices or systems and/or automotive, aviation and aerospace applications or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support, automotive, aviation and aerospace device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [SiC MOSFETs category](#):*

*Click to view products by [Infineon manufacturer](#):*

Other Similar products are found below :

[ADP120N080G2](#) [ADR065N028AH](#) [AIMBG120R080M1XTMA1](#) [AIMBG75R020M1HXTMA1](#) [AIMBG75R027M1HXTMA1](#)

[AIMBG75R060M1HXTMA1](#) [AIMBG75R090M1HXTMA1](#) [AIMCQ120R020M1TXTMA1](#) [AIMCQ120R030M1TXTMA1](#)

[AIMCQ120R040M1TXTMA1](#) [AIMCQ120R060M1TXTMA1](#) [AIMCQ120R080M1TXTMA1](#) [AIMCQ120R120M1TXTMA1](#)

[AIMCQ120R160M1TXTMA1](#) [AIMDQ75R020M1HXUMA1](#) [AIMDQ75R027M1HXUMA1](#) [AIMDQ75R090M1HXUMA1](#)

[AIMW120R035M1HXKSA1](#) [AIMW120R045M1XKSA1](#) [AIMW120R060M1HXKSA1](#) [AIMW120R080M1XKSA1](#)

[AIMZA75R016M1HXKSA1](#) [AIMZA75R020M1HXKSA1](#) [AIMZA75R027M1HXKSA1](#) [AIMZA75R040M1HXKSA1](#)

[AIMZA75R060M1HXKSA1](#) [AIMZA75R090M1HXKSA1](#) [AIMZA75R140M1HXKSA1](#) [AIMZH120R010M1TXKSA1](#)

[AIMZH120R020M1TXKSA1](#) [AIMZH120R030M1TXKSA1](#) [AIMZH120R040M1TXKSA1](#) [AIMZH120R060M1TXKSA1](#)

[AIMZH120R120M1TXKSA1](#) [AIMZH120R160M1TXKSA1](#) [AIMZHN120R020M1TXKSA1](#) [AIMZHN120R040M1TXKSA1](#) [C2M0025120D](#)

[C2M0040120D](#) [C2M0045170D](#) [C2M0080120D](#) [C2M0160120D](#) [C2M0280120D](#) [C2M1000170J](#) [C2M1000170J-TR](#) [C3M0015065D](#)

[C3M0015065K](#) [C3M0016120D](#) [C3M0016120K](#) [C3M0021120J2-TR](#)