



USB0010 V1.0 Datasheet

February 2025



USB0010 Specifications

- USB0010 Dongle is a USB to I2C interface that can be used to communicate with Infineon Digital controllers and Digital Point of Load converters through an XDP™ designer GUI installed on the host computer.
- It is powered by the 5 V USB supply. No external power supply is required.
- By default, the dongle supports I2C bus voltage of 3.3 V. The dongle can be converted to I2C bus voltages of 2.5 V or 1.8 V as per instructions provided in user manual.
- I2C speed settings – Can be set to 100 KHz, 200 KHz, 400 KHz and 800 KHz through the GUI.
- This Dongle is compatible with Infineon XDP™ Designer GUI V2.0 and above versions only.
- USB0010 Dongle is identified by the red color of its housing.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Interface Modules](#) *category:*

Click to view products by [Infineon](#) *manufacturer:*

Other Similar products are found below :

[9441560000](#) [73-546-001](#) [ADAM-4541-C](#) [USB-CARD-READER](#) [USB-RS485](#) [USB-SATA](#) [TD501D232H](#) [RSM232D](#) [TD502D232H](#) [RS232](#)
[TO RS485](#) [TD302D232H](#) [TD501D232H](#) [RSM232](#) [RSM232D](#) [TD301D232H](#) [TD302D232H](#) [TD502D232H](#) [SAVAK-58](#) [SAVKABELCL-24](#)
[20270](#) [20294](#) [30255](#) [50260](#) [20295](#) [20277](#) [50261](#) [EUR0001H](#) [ZHB2301G](#) [30346](#) [KS-308A](#) [KS-302A](#) [KS-304A](#) [KS-1041UA](#) [KS-1021UA](#)
[CEHBB](#) [66255](#) [50985](#) [4000-68512-0940003](#) [GPS50M](#) [2200002208](#) [4000-68112-1220000](#) [44110](#) [4000-68000-1300000](#) [4000-68512-4040001](#)
[446139](#) [60004-006](#) [2200002207](#) [1020882](#) [1021056](#) [1021058](#)