


IFN201, IFN201A, IFN202 N-Channel JFET

Features

- InterFET [N106A Geometry](#)
- Tightly screened IFN201A: $V_{GS(OFF)}$: -0.5V to -1.0V
- Low gate leakage: 750fA typical @20V
- Low C_{iss} : 3pF typical
- High radiation tolerance
- RoHS, REACH, CMR compliant
- Custom test and binning options available
- SMT and bare die package options
- Edge case SPICE modeling: [InterFET SPICE](#)

SOT23 Top View



NOTE: S/D pins are interchangeable Source Drain connections

Industry Standard Crosses

- SST201, MMBFJ201, J201, J202

InterFET Similar Parts

- 2N4338, 2N4339, 2N4867, 2N4868, 2N4869, J201, J202, 2N3458, 2N3459, 2N3460
- SMP4338, SMP4339, SMP4867, SMP4868, SMP4869, SMPJ201, SMPJ202, SMP3458, SMP3459, SMP3460

InterFET Similar Dual Parts

- IFN3954-8; IFN5197-9; IFNU231-5; IFNU401-6; IFNU410-2
- SMP3954-8; SMP5197-9; SMPU231-5; SMPU401-6; SMPU410-2

Applications

- General: Amplifiers; Low leakage switches; Signal mixers
- Audio: Tone control circuits; Headphone amplifiers; Audio filters; Preamplifier speaker drive; Microphone impedance transformation and drive; Phono preamplifiers
- Military/Aero: Radar and communication systems; Missiles and guidance systems; Radiation detection
- Medical: Medical imaging systems; Medical monitors and recorders; Ultrasound equipment

Description

The InterFET IFN201, IFN201A, and IFN202 parts are targeted for cost sensitive low noise applications. These parts are ideal for audio mic and preamplifier designs. Gate leakages are less than 1pA at 20V at room temperatures. Exact crosses for SST201, MMBFJ201, MMBFJ201, J201, and J202 JFETs.

Ordering Information

Part Number	Description	Case	Packaging
IFN201ST3; IFN201AST3; IFN202ST3	Surface Mount	SOT23	Bulk
IFN201ST3TR; IFN201AST3TR; IFN202ST3TR	7" Tape and Reel: Max 3,000 Pieces 13" Tape and Reel: Max 9,000 Pieces	SOT23	Minimum 1,000 Pieces Tape and Reel
IFN201COT; IFN201ACOT; IFN202COT	Chip Orientated Tray (COT Waffle Pack)	COT	400/Waffle Pack
IFN201CFT; IFN201ACFT; IFN202CFT	Chip Face-up Tray (CFT Waffle Pack)	CFT	400/Waffle Pack



NOTICE: Please refer to the end of this document for information on product materials, compliance, safety, and legal statements.

Electrical Characteristics

Maximum Ratings (@ $T_A = 25^\circ\text{C}$, Unless otherwise specified)

Parameters	SOT-23	Unit
V_{RGS} Reverse Gate Source and Gate Drain Voltage	-40	V
I_{FG} Continuous Forward Gate Current	50	mA
P_D Continuous Device Power Dissipation ¹	350	mW
P Power Derating ¹	2.8	mW/°C
T_J Operating Junction Temperature	-55 to 150	°C
T_{STG} Storage Temperature	-55 to 150	°C

¹ Thermal power dissipation and derating values obtained with gate pin (substrate) thermally connected to pad and/or internal layer.


Static Characteristics (@ $T_A = 25^\circ\text{C}$, Unless otherwise specified)


Parameters	Conditions	IFN201A		IFN201		IFN202		Unit
		Min	Max	Min	Max	Min	Max	
$V_{(BR)GSS}$ Gate to Source Breakdown Voltage	$V_{DS} = 0V, I_G = -1\mu A$	-40		-40		-40		V
I_{GSS} Gate to Source Reverse Current	$V_{GS} = -20V, V_{DS} = 0V$		-10		-10		-10	pA
$V_{GS(OFF)}$ Gate to Source Cutoff Voltage	$V_{DS} = 20V, I_D = 10nA$	-0.5	-1.0	-0.3	-1.5	-0.8	-4.0	V
I_{DSS} Drain to Source Saturation Current	$V_{GS} = 0V, V_{DS} = 20V$ (Pulsed)	0.2	0.8	0.2	1	0.9	4.5	mA

Dynamic Characteristics (@ $T_A = 25^\circ\text{C}$, Unless otherwise specified)

Parameters	Conditions	IFN201A		IFN201		IFN202		Unit
		Min	Typ	Min	Typ	Min	Typ	
G_{FS} Forward Transconductance	$V_{DS} = 20V, V_{GS} = 0V, f = 1kHz$	500		500		1000		μS
G_{OS} Output Conductance	$V_{DS} = 20V, V_{GS} = 0V, f = 1kHz$		1		1		3.5	μS
C_{iss} Input Capacitance	$V_{DS} = 20V, V_{GS} = 0V, f = 1MHz$		4		4		4	pF
C_{rss} Reverse Transfer Capacitance	$V_{DS} = 20V, V_{GS} = 0V, f = 1MHz$		1		1		1	pF
e_n Noise Voltage	$V_{DS} = 10V, V_{GS} = 0V, f = 1kHz$		3		3		3	nV/\sqrt{Hz}


Typical IFN201, IFN201A, IFN202 Characteristics



Typical IFN201, IFN201A, IFN202 Characteristics (Continued)



SOT23 (TO-236AB) Mechanical and Layout Data

Package Outline Data



1. All linear dimensions are in millimeters.
2. Package weight approximately 0.12 grams
3. Molded plastic case UL 94V-0 rated
4. For Tape and Reel specifications refer to InterFET CTC-021 Tape and Reel Specification, Document number: IF39002
5. Bulk product is shipped in standard ESD shipping material
6. Refer to JEDEC standards for additional information.

Suggested Pad Layout



1. All linear dimensions are in millimeters.
2. The suggested land pattern dimensions have been provided for reference only. A more robust pattern may be desired for wave soldering.

Compliance and Legal

Environment

InterFET parts follow the latest RoHS Compliance, REACH Compliance, Proposition 65 Statement, TSCA Statement, and Chemical Disposal and Waste Mitigation requirement and guidelines. For more on InterFET's Environmental Commitment please visit www.InterFET.com/environmental/.

Package materials

Parameters	SOT23	SOIC8	TO-92	Metal Case
Alloy	CDA194	C194 1/2H	C194 1/2H	Kovar
Cu	Balance	97% min	97% min	
Fe	2.1 – 2.6%	2.1 – 2.6%	2.1 – 2.6%	53%
Zn	0.05 – 0.2%	0.05 – 0.2%	0.05 – 0.15%	
P	0.015 – 0.15%	0.015 – 0.15%	0.015 – 0.15%	
Pb	0.03% max	0.03% max	0.03% max	
Ni				29%
Co				17%
Mn				0.3%
Si				0.2%
C				<0.01%
Au				Plating

Package tests

Parameters	SOT23	SOIC8	TO-92	Metal Case
MSL	Level 1	Level 1	N/A	N/A
ESD	Class M4 Machine Model Class 3A HBM			

Legal Notice

InterFET Corporation reserves the right to make corrections, enhancements, improvements, modifications, and other changes to its semiconductor products without further notice to this document and any product described herein. InterFET does not assume any liability arising out of the application or use of this document or any product described herein. Unless InterFET has explicitly designated an individual product as meeting the requirements of a particular industry standard, InterFET is not responsible for any failure to meet such industry standard requirements.

InterFET Corporation assumes no liability for a customers product design or applications. Corporate designers and others who are developing systems that incorporate InterFET products understand and agree that they remain responsible for using their independent analysis, evaluation and judgment in designing their applications. Corporate designers and others have full and exclusive responsibility to assure the safety of Designers' applications and compliance of their applications with all applicable regulations, laws and other applicable requirements.

InterFET Corporation resources are provided "as is" with potential faults. InterFET disclaims all other warranties or representations, express or implied, regarding resources or use thereof, including but not limited to accuracy or completeness, title, any widespread failure warranty and any implied warranties of merchantability, fitness for a particular purpose, and non-infringement of any third party intellectual property rights. InterFET shall not be liable for and shall not defend or indemnify designer against any claim, including but not limited to any infringement claim that relates to or is based on any combination of products even if described in InterFET resources or otherwise. In no event shall InterFET be liable for any actual, direct, special, collateral, indirect, punitive, incidental, consequential or exemplary damages in connection with or arising out of InterFET resources or use thereof, and regardless of whether InterFET has been advised of the possibility of such damages.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [InterFET manufacturer](#):

Other Similar products are found below :

[2N2609](#) [2N3821](#) [2N3823](#) [2N3954](#) [2N3971](#) [2N3972](#) [2N4091](#) [2N4093](#) [2N4117](#) [2N4118](#) [2N4118A](#) [2N4119A](#) [2N4220](#) [2N4220A](#) [2N4221](#)
[2N4222](#) [2N4338](#) [2N4339](#) [2N4341](#) [2N4391](#) [2N4393](#) [2N4416](#) [2N4416A](#) [2N4856](#) [2N4857](#) [2N4858](#) [2N4861](#) [2N4861A](#) [2N5020](#) [2N5114](#)
[2N5115](#) [2N5397](#) [2N6453](#) [2N6550](#) [DPAD1](#) [IF1320](#) [IF3601](#) [IF4500](#) [IF4500TR](#) [IF9030](#) [IFN146](#) [IFN147](#) [IFN152](#) [IFN160AST3TR](#)
[IFN160CST3TR](#) [IFN201AST3TR](#) [IFN202ST3TR](#) [IFN5434](#) [IFN5566](#) [IFN5911](#)