



Description

- Oven Controlled Crystal Oscillator (OCXO) in a miniature 7.5x5.5mm package.
- Model IQOV-116-1
- Model Issue number 1

Frequency Parameters

- Frequency 10.0MHz
- Frequency Tolerance $\pm 1.50\text{ppm}$
- Frequency Stability $\pm 0.02\text{ppm}$
- Operating Temperature Range -40.00 to 95.00°C
- Ageing $\pm 5\text{ppb}$ max per day, $\pm 0.5\text{ppm}$ max per year
- Develop frequencies: 10.0MHz, 19.2MHz, 20MHz
- Frequency Tolerance: measurement referenced to frequency observed with $T_A=25^\circ\text{C}$, $V_s=3.3\text{V}$ within 30 days after ex-works.
- Frequency Stability: temperature varied across the operating temperature range, measurement referenced to the frequency observed with $F_{\text{ref}}=(F_{\text{max}}+F_{\text{min}})/2$, $V_s=3.3\text{V}$, load=15pF, temperature variable speed less than 2°C per minute.
- Supply Voltage Variation (measurement referenced to frequency observed with $T_A=25^\circ\text{C}$, V_s varied from 3.135V to 3.465V, load=15pF): $\pm 5\text{ppb}$ max
- Load Variation (measurement referenced to frequency observed with $T_A=25^\circ\text{C}$, $V_s=3.3\text{V}$, load change=5%, load=15pF): $\pm 5\text{ppb}$ max
- Ageing: Measurement referenced to frequency observed with $T_A=25^\circ\text{C}$, $V_s=3.3\text{V}$ and after 30 days of operation.
- Short Term Stability (temperature stability, no EMI/EMC or other interference, test after powered for 1 hour ref to 25°C ; 1s): 0.05ppb max
- g-sensitivity: 1ppb/g max

Electrical Parameters


- Supply Voltage $3.3\text{V} \pm 5\%$
- Current Consumption:
Warm Up: 600mA max
Steady State: 230mA max @ 25°C
- Warm Up Time (time until the output is within $\pm 0.1\text{ppm}$, with reference to the last frequency reading taken 1hr after start-up @ 25°C): 5min max

Output Details


- Output Compatibility HCMOS
- Drive Capability 15pF
- Rise and Fall Time 6.0ns max
- Duty Cycle 45/55
- Output Low VoL (@ $V_s=3.3\text{V}$, load=15pF): 0.4V max
Output High VoH (@ $V_s=3.3\text{V}$, load=15pF): 2.4V min

Noise Parameters


- Phase Noise (max @ 25°C):
-65dBc/Hz @ 1Hz
-100dBc/Hz @ 10Hz
-130dBc/Hz @ 100Hz
-150dBc/Hz @ 1kHz
-155dBc/Hz @ 10kHz
-155dBc/Hz @ 100kHz
-155dBc/Hz @ 1MHz



Outline (mm)



Recommended Solder Pad Layout



Sales Office Contact Details:

UK: +44 (0)1460 270200

Email: info@iqdfrequencyproducts.com

Web: www.iqdfrequencyproducts.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [OCXO Oscillators](#) category:

Click to view products by [IQD](#) manufacturer:

Other Similar products are found below :

[AOCTQ5-V-10.000MHz-M10](#) [SiT5711AI-KW-33E-40.000000F](#) [NO0914AH3C508GN40](#) [8208AI23-33E26.000](#) [AOCJY-100.000MHZ-SW](#)
[AOCJY2A-10.000MHz-F-SW](#) [AOCJY3A-100.000MHz-E](#) [AOCJY3B-10.000MHz-E-SW](#) [AOCJY4A-10.000MHz-SW](#) [AOCJY3-10.000MHz-](#)
[E-SW](#) [AOCJY3A-10.000MHz](#) [AP3S1-108.000MHZ-ER](#) [ABCM-60-10.000MHZ-BC-LG](#) [ABCM-60-10.000MHZ-BC-LN](#) [AOC1409VAUC-](#)
[20.0000C](#) [AOC1409XAUC-20.0000C](#) [AOC2012VAJC-10.0000C](#) [AOC2012VAJC-19.4400C](#) [AOC2012VAJC-25.0000C](#) [AOC2012XAJC-](#)
[10.0000C](#) [AOC2012XAJC-12.8000C](#) [AOC2012XAJC-25.0000C](#) [AOC75FAKC10.0000](#) [AOC75FAKC38.4000](#) [AOC75FAKC38.8800](#)
[AOC75FAQC10.0000](#) [AOC75FAQC20.0000](#) [AOC75FAQC38.4000](#) [AOC97FAJC-10.0000](#) [AOCJY-100.000MHz-E](#) [AOCJY-100.000MHz-F](#)
[AOCJY-10.000MHz](#) [AOCJY-10.000MHz-E](#) [AOCJY-10.000MHz-E-SW](#) [AOCJY1-100.000MHz](#) [AOCJY1-100.000MHz-E-SW](#) [AOCJY1-](#)
[10.000MHz](#) [AOCJY1-10.000MHz-E-SW](#) [AOCJY1-40.000MHz-E](#) [AOCJY1A-100.000MHz](#) [AOCJY1A-10.000MHz](#) [AOCJY-20.000MHz](#)
[AOCJY-20.000MHz-F](#) [AOCJY2-100.000MHz-F](#) [AOCJY2-10.000MHz-E](#) [AOCJY2A-100.000MHz-F-SW](#) [AOCJY2-100.000MHz-E](#)
[AOCJY2-100.000MHz-E-SW](#) [AOCJY4A-10.000MHz-F-SW](#) [AOCJY4B-10.000MHz-SW](#)