

1	2	3	4	5	6	7	8	9			
NOTES1: UL Standard 1.Rated voltage/current : 300V / 10A 2.Withstanding voltage : AC1600V/1Min.							REVISION RECORD				
							REV	ECN	DESCRIPTION	DRFT	DATE
							A0		NEW		2024.03.07
IEC Standard 1.											
NOTES2: 1.Dimension shall be interpreted per ASME Y14.5–2009 2.Pitch : 5.08mm, Poles : N=04~48P 3.Operating temperature: −40°C~+105°C 4.Undimensioned tolerances:											
5.RoHS Compliance											
Ordering Information JL2EDGRHCM - 508 XX X XX											
PCB LAYOUT											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											
JILN JL2EDGRHCM -5.08											

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pluggable Terminal Blocks](#) category:

Click to view products by [JILN](#) manufacturer:

Other Similar products are found below :

[57.510.0053](#) [721-104/026-047](#) [721-204/026-045](#) [ET02015000J0G](#) [860505](#) [860516](#) [GBPACX-12](#) [93.731.4953.0](#) [950-FB/03](#) [950-NLFL-DS/03](#) [PVS02-5,00](#) [1-1986160-3](#) [121-A-111/03](#) [121-A-111/05](#) [121-M-121/04](#) [121-M-211/03](#) [121-M-221/06](#) [1377680000](#) [1546228-5](#) [ELFP03110](#) [ELFT07250](#) [ELXH071G0E](#) [1725220000](#) [1760336](#) [1855000000](#) [19346](#) [1946309](#) [1973592](#) [2-1546857-6](#) [231-110/031-000](#) [25.320.4053.1](#) [25.320.4553.9](#) [25.320.4753.1](#) [25.340.0353.1](#) [25.340.1053.1](#) [25.345.3553.0M001](#) [25.640.3553.1](#) [931-HSL/03-HT](#) [950-FL-DS/04](#) [950-LH-DS/02](#) [950-NLFL-DS/06](#) [SH04-3,50](#) [SH08-5,08](#) [SH08-5,08-K](#) [SH12-5,08](#) [SH15-5,00](#) [SHS04-5,00](#) [30.303](#) [30.305](#) [30.306](#)